

ELEMENT ELECTWORX

FULL BODY HARNESS SERIES

AFH300707

KStrong ElectWorX harnesses have been designed with Non Conductive Fittings allowing use where there are possible electrical hazards. Ideally used in Utilities, overhead Line teams on live wires protecting the user from Electrical discharge.

FEATURES

- Rear D Ring Fall Arrest
- Front Fall Arrest Loops
- Dielectric Fittings 20kV (Non Conductive)
- Elasticated Shoulder Straps
- Rear Sit Strap
- Fall Arrest Indicator Tags
- Label / Instruction Pouch
- Compass Asset Technology
- Padded work positioning belt with side D-Rings

HOW TO USE

Refer to User Instruction Manual

SCAN TO DOWNLOAD

MATERIAL COMPONENTS

Webbing:	44mm Polyester, MBS 25 kN
Fittings:	20kV Steel core with Reinforced Polymer, Black Molded, MBS 23kN
Webbing Keepers:	Elasticated Polyester
Lanyard Keepers:	Polyethylene
Rear ID plate:	Polyethylene
Padding:	Mesh Insushield & Matty

USER WEIGHT LIMIT

140 kg

WEIGHT

2.243kg

RELEVANT STANDARDS

EN 361:2002
EN 358:2018

