

## ELEMENT ELECTWORX SHOCK ABSORBING LANYARD WITH WEBBING LOOP & DIELECTRIC SCAFFOLD HOOK

KStrong ElectWorX Shock Absorbing Lanyards have been designed to be used in conditions where there are possible electrical hazards. Ideally used in Utilities, overhead Line teams on live wires protecting the user from Electrical discharge.

### FEATURES

- High Tensile Polyester Webbing
- Webbing loop for simple attachment
- Dielectric Scaffold Hook 20kV (Non Conductive)
- Label / Instruction Pouch
- Compass Asset Technology

### HOW TO USE

Refer to User Instruction Manual



SCAN TO DOWNLOAD

### MATERIAL COMPONENTS

Webbing:	30mm wide High Tenacity Polyester, MBS 25kN
Metal Components:	Specially Compounded Polymer Insulated Steel fittings Dielectric Resistance 20kV Scaffold Hooks, MBS 23kN
Stitching Thread:	High Tenacity Polyester (Colour Contrasted)
Energy Absorber:	44mm Polyester Back Up Webbing 44mm Polyamide Tear Webbing Protective Covering

### WEIGHT

1.07kg

### LENGTH

1.8m

### CAPACITY

140kg

### RELEVANT STANDARDS

EN 355:2002

