

## EPIC WORK POSITIONING LANYARD

AFL405301(PR)

KStrong has developed a range of Work Positioning Lanyards to be used in conjunction with a fall arrest Harness or Work Positioning Belt to provide additional support to the user, allowing them to work more comfortable and safer.

**Note:** A Work Positioning Lanyard must be used in conjunction with a fall arrest Harness and a separate fall arrest device such as a fall arrest Lanyard or an inertia reel.

### FEATURES

- Kernmantle Rope 12mm
- Twist Lock Karabiner
- Rope Grab Aluminum
- Abrasion Resistant Thimbles
- Compass Asset Technology
- Protective Sleeve

### HOW TO USE

Refer to User Instruction Manual 



### MATERIAL COMPONENTS

Webbing: 30mm Wide Polyester, MBS 30kN  
Kernmantle Rope: 12mm High Tenacity Polyester Rope, MBS 25kN  
Metal Components: Karabiners Silver Galvanized Steel, MBS 25kN  
Rope Grab Aluminum, MBS 15kN  
Stitching Thread: High Tenacity Polyester (Colour Contrasted)

### WEIGHT

0.750kg

### MAXIMUM LENGTH

2m

### RELEVANT STANDARDS

EN 358:2018 & EN 795:2012 TYPE B

