RETRACTABLE MINI FALL ARRESTOR 2.5M

AFS551002(SW)

The KStrong Retractable Mini Fall Arrestor has been designed for extreme workplace situations to ensure its durability and ease of use.
The Mini extends and retracts automatically, allowing the user to operate within the recommended work area. The Mini ensures the webbing is always under tension, reducing any loose excess webbing.

Features

- Compact Protective Plastic Casing.
- 360 Degree Swivel with Load Indicator.
- Supplied with 2 x Screw Gate Karabiners with 6kN gates
  - One attached to the Swivel Anchorage Eye
  - Other to the shock absorber
- Inbuilt textile Energy Absorber for shock absorption
- Minimum Breaking Strength >15kN
- Can be supplied with a variety of fittings on request

Load Capacity

140 kgs

Material

Webbing	:	Polyester
		47±1 mm. Wide
		1.3 ± 0.2 mm. Thickness
		MBS 23kN
Stitching	:	High Tenacity Polyester
Casing	:	PVC
Shock Absorber	:	Polyester webbing
Metal Components	:	Alloy Steel
		Zinc Plated
		MBS 23kN

Weight

1..35 kg ± 0.01 kg

How To Use

Refer to User Instruction Manual

SCAN TO DOWNLOAD

Relevant Standards

EN 360:2002
AS/NZS 18 91.3:2020