

IRSQ SEIZE'M RESCUE KIT (4:1 RATIO)



KStrong introduces the IRSQ RESCUE KIT specifically designed to be used to rescue a casualty who is currently suspended by a fall arrest lanyard or Fall arrest Block. Can be supplied in the following lengths.

- AFX209001 Rescue Seize M Kit 50m 4:1 Hauling, Effective length of 10m. Total Weight 9.68kg
- AFX209001(75) Rescue Seize M Kit 75m 4:1 Hauling, Effective length of 15m. Total Weight 11.73kg
- AFX209001(100) Rescue Seize M Kit 100m 4:1 Hauling, Effective length of 20m. Total Weight 13.8kg
- AFX209001(150) Rescue Seize M Kit 150m 4:1 Hauling, Effective length of 30m. Total Weight 18.18kg
- AFX209001(200) Rescue Seize M Kit 200m 4:1 Hauling, Effective length of 40m. Total Weight 22.28kg

Features

- Suitable for rescue from Fall Arrest Lanyards and Fall Arrest Blocks.
- Remote attachment. The casualty can be attached from a point of safety.
- Rescuer can raise the casualty to release their current attachment so they can be raised or lowered to safety without the need for the rescuer to access the casualty.
- Can rescue directly from an SRL using the AFG801011 Openable Rope Grab
- Extension pole adjusts from 0.75m - 3.0m
- Pre-assembled Kit. No assembly is required by user.
- Supplied in an easy to carry back pack.

How To Use

Refer to User Instruction Manual



3035-1020080002

Components

AFX204001 - Ascender Handle (Right)

Material : Aluminium alloy
Weight : 196gms ± 10gms
Complies with EN 567:1997

AFX202002- Self braking Descender

Finish : Anodized in different colors
Weight : 250gms +10gms
Complies with EN341:2011 Type 2, Class B & EN 12841 TYPE C

AFX206008- Double Mini SS Pulley with double attachment

Material : Aluminum Alloy (Side Cover),
Stainless Steel (Sheave)
Finish : Anodized (Side Cover),
Electro-polished (Sheave)
Weight : 325gms + 5gms
Complies with EN 12278:2007

AFG801011- Aluminum Openable Type Rope Grab

Material : Aluminum Alloy
Finish : CED Coating Black
MBS : 15 kN
Weight : 181gms + 10gms
Complies with EN 353-2:2002

AFX200011 - 11mm Semi Static Kernmantle Rope

Material : Polyamide
MBS : 25kN
Weight : 0.082kgs ± 0.01kgs per M
Complies with EN 1891:1998

AFA921005 - Flat webbing cross arm anchor strap

Material : Polyester
MBS : 25kN
Weight : 128gms ± 10gms
Complies with EN 795:2012 Type B

AFA926015 - Cross Arm Anchor Strap

Material : Polyester
MBS : 25kN
Weight : 270gms +10gms
Complies with EN 795:2012 Type B

AFC601105 - Steel Quarter Turn Locking Karabiner

Material : Alloy Steel
MBS : 40kN
Weight : 236gms + 10gms
Complies with EN 362:2004 Class B

AFX207001 - Rescue Pole

Material : Fiber glass
Min. Length : 0.745 meter
Max. Length : 3.0 meter
Weight : 840gms + 10gms

AFC608401 - Aluminum Scaffold Hook

Material : Aluminum Alloy (Body),
Stainless Steel (Gate and Lock)
MBS : 22kN
Weight : 480gms + 10gms
Complies with EN 362:2004, Class T

AFZ177150- Rescue Bag (suit 50m - 100m Kits)

Finish : PVC welded
Weight : 1.3Kg ± 0.020KG

AFZ177151- Rescue Bag (suit 125m - 200m Kits)

Finish : PVC welded
Weight : 1.6Kg ± 0.020KG