

IRSQ SELF EVACUATION KIT 50M

AFX209040(50)

The KStrong Self-Evacuation kit device is used for suspended work positioning, self-evacuation, or rescue operations.

Features

- Manual operated, controlled descent device makes the descent smooth and secure.
- This device enables the User to be evacuated downward.
- Fully Assembled and ready to be used.
- To descend the user simply squeezes the handle - to stop, simply let go or reduce pressure to feather your descent.
- Light, fast and safe.
- The descender can be installed/removed at any point on the rope.
- Can be supplied in various lengths on request.
- Total Kit Weight- 6.06kg

How To Use

Refer to User Instruction Manual



Components

AFC601415 - Aluminum Twist Lock karabiners

Material : Aluminum Alloy
MBS : 23 kN
Finish : Natural Silver, Colored Anodized
Weight : 84 gm + 5 gm
Complies with EN 362:2004 Class B

AFX200011(50)- 11mm Semi Static Kernmantle Rope

Material : Polyamide
MBS : 25kN
Weight : 4.1kgs ± 0.01kgs
Complies with EN 1891:1998

AFA921515 - 20mm Anchor Strap

Material : Polyester
MBS : 20kN
Weight : 165 gm +10 gm
Complies with EN 795:2012 Type B

AFX202002- Self braking Descender

Finish : Anodized in different colours
Weight : 250gms +10gms
Complies with EN341:2011 Type 2, Class B & EN 12841 TYPE C

AFZ177150- Rescue Bag

Finish : PVC Welded
Weight : 1.3Kg ± 0.020KG

