

EVAC-R 40M RESCUE KIT

AFX209070(40)

The KStrong EVAC-R Descender, Rescue and Lifting device is an Automatic and controlled descent for lifting or lowering of injured person.

Features

- Rescue from high level working platforms and require a simple rescue or evacuation solution
- Hand-wheel for lifting of injured and rescuer
- Easy to attach a powered drill using a 10mm Hexagonal head connector to assist in the rescue allowing the user to use in situations where you are required to raise the casualty up to 500m.
- Controlled descent speed: 1m/sec (85kg) and 1.5m/sec. (170kg).
- Maximum Lifting & Descent height: 500 m. Refer UIM for more details.
- Brake system - Automatic, redundant brake system with 2 fly wheel brakes.
- The maximum load of 285kg allows simultaneous descending of three persons from heights up to 500m.
- Alternating descending on both rope ends can be carried out to rescue more than three persons efficiently (shuttle system).
- Can be used with Kernmantle Rope \varnothing 11mm, EN 1891-A (EN 341, EN 1496), ANSI Z359.4:2013 & Kernmantle Rope \varnothing 9,6mm till \varnothing 11mm acc. EN 1891-A (EN 12841)C

How To Use

Refer to User Instruction Manual



Metal Components

AFX209070 - EVAC-R
Material : High Strength Aluminium Alloy & Steel
Finish : Powder Coated Black
Weight : 3.75 kg

AFX2000105 : 10.5mm Kernmantle Semi Static Rope
Length : 40 m
Weight : 3.074 kg

UFC401400 - Karabiner
Material : Aluminium Twist Lock Karabiner
Breaking Strength : 23 kN / 5000 lbs
Weight : 84 gm

AFX203001 - Edge Protector c/w 2m wire and Karabiner
Material : Stainless Steel
Weight : 650 gm

UFA20006 - Webbing Anchor Strap
Length : 1.8 m / 6 ft.
Breaking Strength : 23 kN / 5000 lbs
Weight : 165 gm

AFZ177150 - Rescue Bag
Material : PVC
Weight : 1.3 kg



Total Kit Weight

9.78 kg

Relevant Standards

Conforms to EN 341:2011 – 1A, EN 1496:2017 - B, EN 12841 Type C & ANSI Z359.4:2013