# BRUTE LOAD ARRESTOR

### AFZ18100016

## 1000KG X 16M

The Brute Load Arrestors are designed as secondary safety back-up for overhead loads, used in conjunction with a primary lifting device or support, such as a hoist or permanently suspended load.

If the primary support fails, the load arrestor will automatically stop the load from falling, thereby preventing damage to the load and, more importantly, protecting users below.

#### **Features**

- Portable and easy to install, supplied with overhead 19mm D-shackle 6 nos. of holes on each flange plate to enable Load Arrestor to be
- fixed directly to the structure (ceiling/ground). Comes with a unique load indicator that Load arrestor has arrested a
- fall. Shock Absorbing Systems
- Fast acting braking system.
- Self-Retracting Steel Cable
- Suitable to be used for Basket Ball Hoops, Stage lighting, Car . assembly, Lifts & Industrial machinery.

#### Load Capacity

1000 kgs

Material

0	0	0
3	1000 kgs	0
•	K STRONC THE STRONG	¢
۲	4486 17711880 1996/1771104/15 16 127 1996/1771104/15 16 129 1996/1996/1996/16	۲
00	6 0 0	••

290.0

## C ۱

Casing	:	High Strength Alloy Steel
Wire	:	8.0mm x 316 Stainless Steel
D-shackle	:	19 mm Steel
Minimum Breaking Strength	:	Greater than 50 kN
	:	

:

### Weight

AFZ1000010

31.12 kgs. ± 0.10 kgs.

### How To Use

Refer to User Instruction Manual

# ĺ

#### **Relevant Standards**

