BRUTE LOAD ARRESTOR 300KG X 15M

AFZ1830015

The Brute Load Arrestors are designed as secondary safety back-up for overhead loads, used in conjunction with a primary lifting device or support, such as a hoist or permanently suspended load.

If the primary support fails, the load arrestor will automatically stop the load from falling, thereby preventing damage to the load and, more importantly, protecting users below.

Features

- Portable and easy to install, simply add D shackles with the desired rating to mount.
- High Impact Polymer casing
- Shock Absorbing Systems
- Fast-acting braking system
- Self-Retracting Steel Cable
- Suitable to be used for Basket Ball Hoops, Stage lighting, car assembly, Lifts & Industrial machinery.
- Can be supplied in 15m length refer AFZ1830015

Load Capacity

300 kgs

Material

Casing : High Impact Polymer

Wire : 4.8mm Galvanized Steel – MBS 15kN

Wire Guide : Brass
Snout : Rubber
Carry Handle : Rubber

Weight

AFZ1830010 : $6.260 \text{ kgs} \pm 0.10 \text{ kgs}$. AFZ1830015 : $6.660 \text{ kgs} \pm 0.10 \text{ kgs}$.

How To Use

Refer to User Instruction Manual



Relevant Standards Machine Directive 2006/42/CE Anchorage Eye Plastic Casing Galvanised steel wire rope

