

BRUTE[™]

SERIES

BRUTE RETRACTABLE FALL ARREST BLOCKS WEBBING SHARP EGDE

KStrong has developed a range of Retractable Blocks in Webbing specifically engineered for Sharp Edge applications such as construction sites, roof tops etc. The unique design allows the user to use the Retractable Block Horizontally and is protected when subjected to a fall over a sharp edge. It is Lightweight, Compact and Robust ensuring your safety when working at heights.



CE 0598

EN 360:2002
VG11 RFU 11.060

Features and Benefits

- ◆ Swivel Anchorage Eye
- ◆ High Impact Load Bearing Polymer Casing
- ◆ Ergonomic Carry handle for ease of transportation
- ◆ 25mm Toughened Webbing
- ◆ Energy Absorber and Protective Cover
- ◆ Load Capacity 140 kgs for vertical use & 100 kgs for Horizontal use.
- ◆ MBS – 15kN
- ◆ Temperature Range : -30° to +50° C
- ◆ QR code for ease of Identification and Service History
- ◆ Steel Swivel Snap Hook with Fall Indicator

Materials

- ◆ Polymer Casing
- ◆ 25mm polyester textile webbing.- MBS 20kN
- ◆ Steel Snap Hook - MBS 23kN
- ◆ Steel Karabiner - MBS 25kN

How To Use

- ◆ Refer to User Instruction Manual 



AFS550003.5SE

Length: 3.5m
Weight: 1.9kg



AFS550006SE

Length: 6m
Weight: 2.5kg