KSTRONG
UNRIVALED SAFETY.

BRUTE™
SERIES

BRUTE SEALED RETRACTABLE FALL ARREST BLOCKS

KStrong Brute range of Sealed Blocks are designed specifically for the most extreme environments. The heavy duty sealed design, corrosion resistant material used in the Block ensures the critical working components a kept free of dirt, grease, water, and chemicals.
Ideally suited for Oil and Gas, Sewage Plants and all Offshore areas.

CE 0598

EN 360:2023 & IP69K as per ISO-20653
Vibration Test IEC 60068-2-6:2007
EN 80079-36:2016
EN 80079-37:2016
AS/NZS 1891.3 2020
ATEX 2014/34/EU

Ex II 2G

Features and Benefits

- High Impact Load Bearing Polymer Casing
- Stainless steel wire rope 4.8mm
- Ergonomic Carry Handle for ease of transportation
- Load Capacity 140kg
- MBS 15kN
- Temperature Range : -30^{0} to +50^{0} C
- QR code for ease of Identification and Service History
- ANSI Stainless Steel Swivel Snap Hook with Fall Indicator
- Corrosion Protection: Units pass 2000 hrs of Neutral Salt Spray life in a controlled environment.

Materials

- Polymer & Stainless Steel Casing
- 4.8mm Stainless Steel Wire Rope - MBS 15kN
- ANSI Stainless Steel Swivel Snap Hook - MBS 23kN
- ANSI Stainless Steel Karabiner - MBS 23kN

How To Use

- Refer to User Instruction Manual

SCAN TO DOWNLOAD

AFS570010
Length: 10m
Weight: 7.37kg

AFS570020
Length: 20m
Weight: 11.83kg

AFS570028
Length: 28m
Weight: 19.803kg