

BRUTE RETRACTABLE FALL ARREST BLOCKS (WIRE ROPE)

KStrong has developed a range of Retractable Fall Arrest Blocks with Galvanized Steel cable that is Lightweight, Compact and Robust ensuring your safety when working at heights. The Retractable Block is the ideal choice for working at height and comes standard with Snap Hook with Fall Indicator and Swivel Anchorage eye which prevents any undue twist of the wire rope while working on in the event of a fall.

Features and Benefits

- Swivel Anchorage Eye
- High Impact Load Bearing Polymer Casing
- Ergonomic Carry handle for ease of transportation
- 4.5mm Galvanised Steel Cable for added strength and safety
- Snout reduces the locking of the cable when it is suddenly released
- Load Capacity 140kg
- MBS 15kN
- Temperature Range : -30° to +50° C
- QR code for ease of Identification and Service History
- ANSI Steel Swivel Snap Hook with Fall Indicator
- Can be supplied with Stainless Steel Cable and Stainless Steel Swivel Snap Hook on Request



INCLUDED FOR ALL
SRLs ABOVE 3.5M



CE 0598

EN 360:2023
ATEX 2014/34/EU
AS/NZS 1891.3 2020



II 2G

Materials

- Polymer Casing
- 4.5mm Galvanised Steel Wire - MBS 15kN
- Galvanised ANSI Steel Snap Hook - MBS 23kN
- Galvanised ANSI Steel Karabiner - MBS 23kN

How To Use

- Refer to User Instruction Manual



SCAN TO DOWNLOAD



AFS510003.5

Length: 3.5m
Weight: 2kg



AFS510006

Length: 6m
Weight: 3kg



AFS510010

Length: 10m
Weight: 4.2kg



AFS510015

Length: 15m
Weight: 5.81kg



AFS510020

Length: 20m
Weight: 6kg



AFS510025

Length: 25m
Weight: 12.88kg



AFS510030

Length: 30m
Weight: 13.1kg