

# BRUTE<sup>™</sup> SERIES

## BRUTE RETRACTABLE FALL ARREST BLOCKS WIRE ROPE SHARP EGDE

KStrong has developed a range of Retractable Fall Arrest Blocks in Galvanized Steel Rope specifically engineered for Sharp Edge applications such as construction sites, roof tops etc. The unique design allows the user to use the Retractable Block Horizontally and is protected when subjected to a fall over a sharp edge. It is Lightweight, Compact and Robust ensuring your safety when working at heights.

### Features and Benefits

- ♦ Swivel Anchorage Eye
- ♦ High Impact Load Bearing Polymer Casing
- ♦ Ergonomic Carry handle for ease of transportation
- ♦ 4.8mm Galvanised Steel Cable for added strength and safety
- ♦ Energy Absorber and Protective Cover
- ♦ Can be Used Horizontally
- ♦ Load Capacity 140 kgs for vertical use & 100 kgs for Horizontal use.
- ♦ MBS – 15kN
- ♦ Temperature Range : -30<sup>o</sup> to +50<sup>o</sup> C
- ♦ QR code for ease of Identification and Service History
- ♦ Steel Swivel Snap Hook with Fall Indicator
- ♦ Can be supplied with Stainless Steel Cable and Stainless Steel Swivel Snap Hook on Request

### Materials

- ♦ Polymer Casing
- ♦ 4.8mm Galvanized Steel Wire- MBS 15kN
- ♦ Steel Snap Hook - MBS 23kN
- ♦ Steel Karabiner - MBS 25kN

### How To Use

- ♦ Refer to User Instruction Manual 



**CE 0598**

EN 360:2002  
VG11 RFU 11.060



**AFS510003.5SE**

Length: 3.5m  
Weight: 2.2kg



**AFS510006SE**

Length: 6m  
Weight: 3.20kg



**AFS510010SE**

Length: 10m  
Weight: 4.4kg



**AFS510015SE**

Length: 15m  
Weight: 5.85kg



**AFS510020SE**

Length: 20m  
Weight: 6.25 kg