LV3 | FULL BODY HARNESS SERIES



KStrong EPIC Series has been ergonimacal designed with AirLite padding to provide extreme comfort with breathable foam and fabric to keep you cooler for longer. It has light weight Aluminum fittings and is suitable for all environments due to the Endure Guard Technology which provides liquid protection against Oil, Dirt & Water. It also has the Intergrated Compass Asset Management feature located in the Label Pack.





AFH300401



AFH300402



AFH300404



AFH300405













	EDIC HADNESS CODES								
	EPIC HARNESS CODES								
	AFH300401	AFH300402	AFH300404	AFH300405	AFH300406				
HARNESS WEIGHT									
	1.628kg	2.227kg	2.46kg	3.2kg	0.6kg				
	FEATURES								
Aluminum Front D Ring Fall Arrest	~	~	~	~					
Aluminum Rear D Ring Fall Arrest	~	>	~	~					
Adjustable Leg Straps	~	>	~	~	~				
Adjustable Chest & Shoulder Straps	~	>		~					
Rescue Loops									
Quick Release Buckles (Aluminum)	~	>	~	~					
Breathable Shoulder & Leg Padding	~	>	~	~					
Padded Waist Belt with Aluminum Side D Rings		>	~	~					
Plastic Webbing Holders									
Rubber Web End Stops	~	>	~	~					
Rear Sit Strap	~	>		~					
Fall Arrest Indicator Tags	~	>	~	~					
Lanyard Keepers	~	>		~					
Label / Instruction Pouch	~	>	~	~	~				
Aluminum Pass Through Buckles	~	>	~	~					
Suspension Trauma Straps	~	>		~					
Compass Asset Technology	~	>	~	~	~				
Tool Loops			~						
Lower Aluminum Ventral Limited Free Fall Arrest D-ring			~						
USER WEIGHT LIMIT									
Refer to Energy Absorbing Lanyards & Fall Arrest Blocks data for maximum usage	140kg	140kg	140kg	140kg	140kg				
RELEVANT STANDARDS									
EN 361:2002	~	>	~	~					
EN 358:2018		>	~	~					
EN 813:2008			~						
EN 12277:2015					~				





	EPIC HARNESS CODES									
	AFH300401	AFH300402	AFH300404	AFH300405	AFH300406					
SUITABLE FOR										
Construction	~	~	~	~						
Maintenance	~	~	~	~						
Fall Arrest	~	~	~	~						
Ladder Safety Systems	~	~	~	~						
Roof Work	~	~	~	~						
Telecommunications			~	~						
Elevated Work Platforms										
Confined Space Entry	~	~								
Climbing			>	>	~					
Tower / Pole Work	~	~	>	~						
Rescue / Rope Acess			~							
Welding / Hot Works										
Wet & Corrosive Enviroments										
Offshore										
Electrical										





MATERIAL SPECIFICATION

WEBBING

Polyester 44mm wide

MBS 25kN

THREAD / STITCHING

High Tenacity Polyester (Colour Contrasted)

METAL COMPONENTS

Frame & Buckle Aluminum - MBS 15kN

D-RING - MBS 23kN

Finish - Silver Passivation

PADDING

Comfart Pad Made Up Of Air Mesh, Insushield & Matty





Harness Sizing Chart

