

KSTRONG T-LINE 12M C/W STAINLESS STEEL CABLE


AFA945012(SS)

SAFE CLIMBING FOR ACCESS AND EGRESS

Features

- Consists of two independent lifelines which allow the user to move in a horizontal and vertical direction.
- Prevents pendulum effect in the event of a fall.
- Suitable to work around overhead obstructions, such as pipes/services and even gantry cranes.
- Reduced fall arrest distances over larger spans (can be less than 600m).
- The T-line can be mounted with each end at different heights, for sloping roofs etc.
- The T-Line reduces the forces on the User and the supporting structure when a fall occurs.
- Rated for one user 140kg.
- Easy to install and transportable.

How To Use

Refer to User Instruction Manual 

Materials

Casing	:	Durable and High Strength Polymer
Wire Cable	:	316 Stainless Steel 4.8mm Wire
Karabiner & O-Ring	:	316 Stainless Steel, MBS 23kn
Minimum Breaking Strength	:	15kN

Weight

18.13kg± 0.50 kg

Span Lengths

Horizontal - 6.0 Meters. Vertical - 12.0 Meters.
Vertical - 6.0 Meters. Horizontal - 12.0 Meters

Relevant Standards

Conforms to EN 795:2012 TYPE C & EN 1496:2017 Class B.



SPAN LENGTH

