

## ELEMENT EXTREMEWORX SHOCK ABSORBING WEBBING LANYARD WITH ALUMINUM SNAP HOOKS

KStrong ExtremeWorX Shock Absorbing Lanyards have been designed to be used in the most hostile conditions whilst protecting the user. Ideally used in Offshore, Petrochemical Industry, Water Treatments plants and Food processing Industries. The Endure guard coating protects the webbing against oil, water, & dirt, as well as enhancing the abrasion resistant properties of the webbing.

### FEATURES

- Endure Webbing (Oil & Water Repelant)
- Tear And Cut Resistant Webbing
- Aluminum Snap Hook
- Aluminum Scaffold Hook
- Label / Instruction Pouch
- Compass Asset Technology

### HOW TO USE

Refer to User Instruction Manual



### MATERIAL COMPONENTS

|                   |   |
|-------------------|---|
| Webbing:          | 44mm wide High Tenacity Polyester, MBS 25kN<br>Endure guard - oil, water, dirt and abrasion resistant webbing |
| Metal Components: | High Tensile Aluminum Alloy Snap Hooks, MBS 23kN<br>High Tensile Aluminum Alloy Scaffold Hooks, MBS 23kN      |
| Stitching Thread: | High Tenacity Polyester (Colour Contrasted)   |
| Energy Absorber:  | 44mm Polyester Back Up Webbing<br>44mm Polyamide Tear Webbing<br>Anti-Static Shock Absorber Cover             |

### WEIGHT

0.8kg

### LENGTH

1.8m

### CAPACITY

140kg

### RELEVANT STANDARDS

EN 355:2002  
EN 354:2010  
VG11 RfU  
CNB/P/11.063

