

EXTREME TRIPOD 10FT FOR 2 USERS

KStrong Extreme Tripod has been designed for confined space entry / retrieval applications. Its simplistic design allows for easy set up providing the user a means of controlled ascent and descent in minimal time.

Features

- Double integral head mounted pulleys which is permanently incorporated in the cast aluminum head of the Tripod.
- Provides independent passing over of cable from a Winch and a Retrieval Block.
- Two auxiliary 23kN eye bolts as attachment points.
- Consists of Steel support-Feet provided with rubber sole to increase friction and impart more stability.
- Every Tripod is provided with pre-installed universal mounting attachments to easily mount the Winch and Retrieval Blocks.
- Adjustable usable height from 1.90m to 3.07m
- Steel Chain to secure the legs
- Comes with Tripod bag
- Suitable for 2 Users

How To Use

Refer User Instructions



Load Capacity

Maximum Load Capacity:

- Personal use 200kg
- Materials Handling 650 kg

Material

- Tripod Legs : Material - Aluminum Alloy
Finish- Powder Coated & Anodized.
- Cast Head : Material - Aluminum Alloy
Finish- ED Coated Black.
- Eye Bolt : Material - Aluminum Alloy eye bolt, Rated 23kN
- Locking Pins : Material - Stainless Steel locking push pins
- Chain : Material - Alloy Steel Galvanized

Weight

27.17 kg ± 0.20 kg

System Strength

23kN MBS

Relevant Standards

Conforms to EN 795:2012 Type B & AS/NZS 5532:2013



Product Code	Picture	Bracket used for Mounting
AFT710007UW		Winch AFT73020, AFT730040, AFT730042
AFT710007UR		Retrieval Blocks AFS510020R AFS510030R
AFT7100059		Tripod mounting bracket

