

IRSQ SELF EVACUATION KIT 50M

AFX209040(50)

The KStrong Self-Evacuation kit device is used for suspended work positioning, self-evacuation, or rescue operations.

Features

- Manual operated, controlled descent device makes the descent smooth and secure.
- This device enables the User to be evacuated downward.
- Fully Assembled and ready to be used.
- To descend the user simply squeezes the handle - to stop, simply let go or reduce pressure to feather your descent.
- Light, fast and safe.
- The descender can be installed/removed at any point on the rope.
- Can be supplied in various lengths on request.
- The triangular rescue harness can be suspended to a rescue hoist or a descender.
- The Evacuation Triangle is designed for rescue evacuation operations. Must not be used as fall arrest Harness.
- Supplied with Anchor Strap with wear pad

How To Use

Refer to User Instruction Manual



Components

AFC601422 - Aluminum Twist Lock karabiners

Material : Aluminum Alloy

MBS : 23 kN

Finish : Natural Silver, Colored

Weight : Anodized 84 gm + 5 gm

Complies with EN 362:2004 Class B

AFX200011(50) - 11mm Semi Static Kernmantle Rope

Material : Polyamide

MBS : 25kN

Weight : 4.1kgs ± 0.01kgs

Complies with EN 1891:1998

AFX202002 - Self braking Descender

Finish : Anodized in different colours

Weight : 250gms +10gms

Complies with EN341:2011 Type 2, Class B & EN 12841 TYPE C

AFZ177150 - RescueBag

Finish : PVC Welded

Weight : 1.3Kg ± 0.020KG

AFX201035 - Rescue Triangle

Material : Tetron

Fittings : Aluminum Anodized

Weight : 1.10kg

AFA920015 - Anchor Strap 1.5m

Material : Polyester

Fittings : Alloy Steel

Weight : 577 gm +10 gm

