

ELEMENT ELECTX FULL BODY HARNESS SERIES

**ANH3000706
& ANH300707**

KStrong ElectX harnesses have been designed with Non Conductive Fittings allowing use where there are possible electrical hazards. Ideally used in Utilities, overhead Line teams on live wires protecting the user from Electrical discharge.

FEATURES

- Rear D Ring Fall Arrest
- Front Fall Arrest Loops
- Dielectric Fittings 14kV (Non Conductive)
- Elasticated Shoulder Straps
- Rear Sit Strap
- Fall Arrest Indicator Tags
- Label / Instruction Pouch
- Compass Asset Technology

HOW TO USE

Refer to User Instruction Manual



MATERIAL COMPONENTS

Webbing:	44mm Polyester, MBS 25 kN
Fittings:	14kV Steel core with Reinforced Polymer, Black Molded, MBS 23kN
Webbing Keepers:	Elasticated Polyester
Lanyard Keepers:	Polyethylene
Rear ID plate:	Polyethylene
Padding:	Mesh Insushield & Matty

USER WEIGHT LIMIT

140 kg

WEIGHT

AFH300706 : 1.36 kg + 0.05 kg

AFH300707 : 2.02 kg + 0.05 kg

RELEVANT STANDARDS

AS/NZS 1891.1:2020

ANH300706



ANH300707

