

# BRUTE™ SERIES

## BRUTE LEADING EDGE RETRACTABLE FALL ARREST BLOCKS WEBBING

KStrong has developed a range of Retractable Blocks in Webbing specifically engineered for Leading Edge applications such as construction sites, roof tops etc. The unique design allows the user to use the Retractable Block Horizontally and is protected when subjected to a fall over a edge. It is Lightweight, Compact and Robust ensuring your safety when working at heights.

### Features and Benefits

- ◆ Swivel Anchorage Eye
- ◆ High Impact Load Bearing Polymer Casing
- ◆ Ergonomic Carry handle for ease of transportation
- ◆ 25mm Toughened Webbing
- ◆ Energy Absorber and Protective Cover
- ◆ Load Capacity 140 kgs for vertical use & 140 kgs for Horizontal use.
- ◆ Leading Edge Rated (R>0.5mm).
- ◆ MBS – 15kN
- ◆ Temperature Range : -30 to +50 C
- ◆ QR code for ease of Identification and Service History
- ◆ Steel Swivel Snap Hook with Fall Indicator

### Materials

- ◆ Polymer Casing
- ◆ 25mm polyester textile webbing.- MBS 20kN
- ◆ Steel ANSI Snap Hook - MBS 23kN
- ◆ Steel ANSI Karabiner - MBS 25kN

### How To Use

- ◆ Refer to User Instruction Manual 



**CE 0598**

EN 360:2002  
VG11 RFU 11.060



**AFS550003.5SE**

Length: 3.5m  
Weight: 2.04kg



**AFS550006SE**

Length: 6m  
Weight: 2.65kg