

# BRUTE<sup>™</sup> SERIES

## BRUTE SEALED RETRACTABLE FALL ARREST BLOCKS

KStrong Brute range of Sealed Blocks are designed specifically for the most extreme environments. The heavy duty sealed design, corrosion resistant material used in the Block ensures the critical working components are kept free of dirt, grease, water, and chemicals. Ideally suited for Oil and Gas, Sewage Plants and all Offshore areas.



INCLUDED WITH  
SEALED SRLS



### CE 0598

EN 360:2023 & IP69K as per ISO-20653  
Vibration Test IEC 60068-2-6:2007  
EN 80079-36:2016  
EN 80079-37:2016  
AS/NZS 1891.3 2020  
ATEX 2014/34/EU



### Features and Benefits

- ♦ High Impact Load Bearing Polymer Casing
- ♦ Stainless steel wire rope 4.8mm
- ♦ Ergonomic Carry Handle for ease of transportation
- ♦ Load Capacity 140kg
- ♦ MBS15kN
- ♦ Temperature Range : -30° to +50° C
- ♦ QR code for ease of Identification and Service History
- ♦ ANSI Stainless Steel Swivel Snap Hook with Fall Indicator
- ♦ Corrosion Protection: Units pass 2000 hrs of Neutral Salt Spray life in a controlled environment.

### Materials

- ♦ Polymer & Stainless Steel Casing
- ♦ 4.8mm Stainless Steel Wire Rope - MBS 15kN
- ♦ ANSI Stainless Steel Swivel Snap Hook - MBS 23kN
- ♦ ANSI Stainless Steel Karabiner - MBS 23kN

### How To Use

- ♦ Refer to User Instruction Manual 



SCAN TO DOWNLOAD



**AFS570010**

Length: 10m  
Weight: 8.1kg



**AFS570020**

Length: 20m  
Weight: 14.9kg



**AFS570028**

Length: 28m  
Weight: 24.2kg