

BRUTE[™] SERIES

BRUTE LEADING EDGE RETRACTABLE FALL ARREST BLOCKS WIRE ROPE

KStrong has developed a range of Retractable Fall Arrest Blocks in Galvanized Steel Rope specifically engineered for Leading Edge applications such as construction sites, roof tops etc. The unique design allows the user to use the Retractable Block Horizontally and is protected when subjected to a fall over a edge. It is Lightweight, Compact and Robust ensuring your safety when working at heights.



CE 0598

EN 360:2023
VG11 RFU 11.060
AS/NZS 1891.3 2020

Features and Benefits

- ◆ Swivel Anchorage Eye
- ◆ High Impact Load Bearing Polymer Casing
- ◆ Ergonomic Carry handle for ease of transportation
- ◆ 4.8mm Galvanised Steel Cable for added strength and safety
- ◆ Energy Absorber and Protective Cover
- ◆ Can be Used Horizontally
- ◆ Load Capacity 140 kgs for vertical use & 140 kgs for Horizontal use.
- ◆ Leading Edge Rated (R>0.5mm).
- ◆ MBS 15kN
- ◆ Temperature Range : -30° to +50° C
- ◆ QR code for ease of Identification and Service History
- ◆ ANSI Steel Swivel Snap Hook with Fall Indicator
- ◆ Can be supplied with Stainless Steel Cable and Stainless Steel Swivel Snap Hook on Request

Materials

- ◆ Polymer Casing
- ◆ 4.8mm Galvanized Steel Wire- MBS 15kN
- ◆ Steel ANSI Snap Hook - MBS 23kN
- ◆ Steel ANSI Karabiner - MBS 23kN

How To Use

- ◆ Refer to User Instruction Manual



AFS510003.5SE

Length: 3.5m
Weight: 2.34kg



AFS510007SE

Length: 7m
Weight: 3.28kg



AFS510010SE

Length: 10m
Weight: 4.48kg



AFS510015SE

Length: 15m
Weight: 5.95kg



AFS510020SE

Length: 20m
Weight: 7.9 kg