

# ECOR

## WORK POSITIONING LANYARDS

# TECHNICAL DATA SHEET



KStrong has developed a range of Work Positioning Lanyards to be used in conjunction with a fall arrest Harness or Work Positioning Belt to provide additional support to the user, allowing them to work more comfortably and safer.

**Note:** A Work Positioning Lanyard must be used in conjunction with a fall arrest Harness and a separate fall arrest device such as a fall arrest Lanyard or an inertia reel.

# ECOR

## WORK POSITIONING LANYARDS



ECOR Work Positioning Lanyard With Aluminum Adjuster c/w  
Snap hook

**ANL405352**



ECOR Work Positioning Lanyard With Aluminum Adjuster c/w  
Snap hook - 2.5M

**ANL405352**

# ECOR

## WORK POSITIONING LANYARDS / POLE STRAPS

LANYARD CODES			
<b>FEATURES</b>	ANL405352	ANL405352 (2.5m)	
LANYARD WEIGHT			
	1.2kg	1.25kg	
FEATURES			
KERNMANTLE ROPE 11MM	✓	✓	
STEEL QUARTER TURN KARABINER	✓	✓	
STEEL SNAP HOOK	✓	✓	
ALUMINUM ADJUSTER	✓	✓	
ALUMINUM KARABINER			
PROTECTIVE SLEEVE	✓	✓	
COMPASS ASSET TECHNOLOGY	✓	✓	
LENGTH IN METERS			
	2m	2.5m	
RELEVANT STANDARDS			
AS 1891.5:2020	✓	✓	
<b>10 Years Shelf Life From Date Of Manufacture.</b>			

# ECOR

## WORK POSITIONING LANYARDS

### MATERIAL SPECIFICATIONS

#### KERNMANTLE ROPE

- 11mm Kernmantle Rope
- MBS 25kN

#### THREAD / STITCHING

- High Tenacity Polyester (Colour Contrasted)

#### METAL COMPONENTS

- ANSI Steel Snap Hooks - MBS 23kN
- Rope Grab Aluminum - MBS 15kN
- Finish - Silver Galvanized
- ANSI Steel Quarter Turn Karabiner - MBS 23kN & Gate strength 16kN