

EPIC

WORK POSITIONING LANYARDS

TECHNICAL DATA SHEET



KStrong has developed a range of Work Positioning Lanyards to be used in conjunction with a fall arrest Harness or Work Positioning Belt to provide additional support to the user, allowing them to work more comfortably and safer.

Note: A Work Positioning Lanyard must be used in conjunction with a fall arrest Harness and a separate fall arrest device such as a fall arrest Lanyard or an inertia reel.

EPIC

WORK POSITIONING LANYARDS



EPIC Work Positioning Lanyard with Aluminum Adjuster c/w
Aluminum Snap hook

ANL405391



EPIC Work Positioning Lanyard with Aluminum Adjuster c/w
Aluminum Snap hook

ANL405351

EPIC

WORK POSITIONING LANYARDS / POLE STRAPS

LANYARD CODES		
FEATURES	ANL405391	ANL405351
LANYARD WEIGHT		
	0.98kg	1.5kg
FEATURES		
KERNMANTLE ROPE 11MM	✓	✓
KARABINER		
STEEL TRIPLE ACTION KARABINER	✓	✓
SNAP HOOK		
TRIPLE ACTION ALUMINUM SNAP KARABINERS	✓	✓
ALUMINUM ADJUSTER	✓	✓
ABRASION RESISTANT THIMBLES		
PROTECTIVE SLEEVE	✓	✓
COMPASS ASSET TECHNOLOGY	✓	✓
MAXIMUM ADJUSTABLE LENGTH IN METERS		
	2m	2m
RELEVANT STANDARDS		
AS 1891.5:2020	✓	✓
10 Years Shelf Life From Date Of Manufacture.		

EPIC

WORK POSITIONING LANYARDS

MATERIAL SPECIFICATIONS

KERNMANTLE ROPE

- 11mm Kernmantle Rope
- MBS 25kN

THREAD / STITCHING

- High Tenacity Polyester (Colour Contrasted)

METAL COMPONENTS

- Triple Action Anodized Aluminum Karabiners - MBS 23kN & Gate strength 16kN
- Rope Grab Aluminum - MBS 15kN
- Finish - Silver Galvanized
- Steel Triple action Karabiner - MBS 23kN & Gate strength 16kN