

STANDARD SRL CONDITIONING TEST PARAMETERS

	CONDITIONING	DURATION OF CONDITIONING (hr)	SPECIFICATION
EN 364:1992	WET	3	70 L/H spray
	COLD	2	at - 30 ± 2°C
	HOT	2	at 50 ± 2°C & 85% RH

	CONDITIONING	DURATION OF CONDITIONING (hr)	SPECIFICATION
EN 360:2023	WET	24 hr immerse & 1 hr drain	Fully immerse in fresh water at (10 to 30)°C
	COLD	2	at - 30 ± 2°C
	HEAT	2	at 50 ± 2°C & 85% RH
	CORROSION	24 hr exposure + 60 min drying with another 24 hr exposure & 60 min drying	Suspend to SST as per ISO 9227:2022

	CONDITIONING	DURATION OF CONDITIONING (hr)	SPECIFICATION
AS NZS 1891.3:1997	WET	3	70 L/H spray
	COLD	2	at - 20 ± 2°C
	HOT	2	at - 40 ± 2°C

	CONDITIONING	DURATION OF CONDITIONING (hr)	SPECIFICATION
ANSI Z359.14-2021_SRL	WET	3	70 L/H spray
	COLD	2	at - 40 + 0/-5°C
	HOT	2	at 54 + 6/-0°C & 85% RH

	CONDITIONING	DURATION OF CONDITIONING (hr)	SPECIFICATION
CSA Z259.2.2-17	COLD	8	at - 35 ± 2°C
	HOT	8	at - 35 ± 2°C
	SALT SPRAY	48	Neutral Salt Spray