



# FALL PROTECTION BEAM ANCHORS



PROVIDES ADJUSTABLE ANCHORAGE POINT FOR FALL ARREST SYSTEMS



FITS VARIOUS I-BEAM & H-BEAM FLANGES



SUITABLE FOR OVERHEAD & FOOT-LEVEL APPLICATIONS



USED IN FIXED POSITION OR SLIDES ALONG THE BEAM



**AFA930401**  
**EDGE BEAM CLAMP ANCHOR 90MM - 340MM**



**AFA930411**  
**EDGE BEAM CLAMP ANCHOR 75MM - 150MM**



**AFA930412**  
**EDGE TROLLEY BEAM ANCHOR 80MM - 250MM**



**AFA930413**  
**VERTICAL BEAM CLAMP ANCHOR 90MM - 340MM**

PRODUCT	FLANGE SIZE	FEATURES	SYSTEM STRENGTH	CERTIFICATION
<b>AFA930401</b>	90MM - 340MM	<ul style="list-style-type: none"> <li>Once installed, D-ring can be used for connection with a variety of Connectors</li> <li>Lightweight</li> <li>Suitable for 1-person</li> </ul>	23kN	EN 795:2012 Type B ANSI Z359.18-2017 Type A
<b>AFA930411</b>	75MM - 150MM			
<b>AFA930412</b>	80MM - 250MM	<ul style="list-style-type: none"> <li>Corrosion Resistant &amp; easy to install</li> <li>Comes with Adjustable Flanges for use on different beam sizes</li> </ul>		
<b>AFA930413</b>	90MM - 340MM	<ul style="list-style-type: none"> <li>Easily fitted &amp; removed using Adjustment Nut &amp; Locking Pin</li> <li>Suitable for Vertical &amp; Horizontal applications</li> </ul>		EN 795:2012 Type B AS/NZS 5532:2013 ANSI Z359.18-2017 Type A