

# MICRON™ SERIES

**AFS550002LD**

The MICRON LE has been designed with an integrated shock absorber allowing the User to operate at Foot level and Sharp Edge applications, providing confidence when working near an edge. It is light weight, robust and comfortable. It is compatible with a range of harnesses by using the SRL connector.

## Features

- Light Weight
- Used at Foot level.
- Twin SRL connector for connection to the Dorsal attachment of harness.
- Meets the Sharp Edge Test and Passes the Dynamic Test of Fall Factor 2.
- Twin legged retractable lanyard with Aluminum Snap hooks at termination end and Integrated Shock Pack at harness attachment end.
- Compatible to be used where anchor point not available above users head / can be used near a potential leading edge.
- Can be used Horizontally.
- Light Weight
- 360 Degree Swivel Scaffold Hooks
- Length: 2m
- Minimum Breaking Strength >15kN.
- Used Horizontally.
- Can be attached to all harnesses and used with one or two units -refer attachments AFC609100 & AFC609101.
- QR Code for ease of identification.
- Can be supplied with a range of different hook options on request.

## Load Capacity

140 Kg Vertical  
100 Kg Horizontally

## Material

Webbing	:	Technocra
	:	21mm Wide
	:	MBS: 20kN
Casing	:	High Impact Polymer
Shock Absorber	:	Polyester Webbing
Metal Components	:	Aluminium Scaffold Hook
	Material :	Aluminium Alloy Body
		SS Gate & Lock
	MBS :	22kN
Dorsal Micron Connectors	Material :	Galvanized with Golden Yellow / Silver Passivation
AFC609100	MBS :	22kN
AFC609101	MBS :	20kN (Major Axis) 15kN (Minor Axis)

## Weight

1180 gm ± 20 gm

## How To Use

Refer to User Instruction Manual



## Relevant Standards

EN 360:2002, VG11 RFU # 11.060



AFC609100



AFC609101



CE 0598