KSTRONG®
UNRIVALED SAFETY.

STATEMENT OF CONFORMANCE & WARRANTY
ENGINEERED SINGLE POINT ANCHORS

SOC

Product Certification

Code	Product	Code	Product
AFA930002	Multipurpose Anchor SS 16mm	AFA930001SS	Multipurpose Anchor SS 12mm
AFA930316	Swivel Bearing Anchor with Steel Fixing	AFA930316C	Swivel Bearing Anchor
AFA935508(100)	One Piece Concrete Anchor SS M16x100mm	AFA935515	Two Piece Concrete Anchor SS M12x110mm
AFA930310	Detent Concrete Anchor and SS Ferrule Set	AFA935502	Curved Base Purlin Anchor
AFA935503	Flat Base Purlin Anchor	AFA935504	Trapezoidal Base Purlin Anchor

KStrong certifies that the specified Engineered Single Point Anchors are designed, manufactured and tested in accordance with the following standard:

Standard	Basis	Applies To
AS/NZS 5532:2013 (Fall Arrest)	Certified	AFA930001SS, AFA935515, AFA930310, AFA935502, AFA935503, AFA935504
AS/NZS 5532:2013 (Fall Arrest)	Conforms	AFA930002, AFA930316, AFA930316C, AFA935508(100)

All anchors have a rated capacity of 15kN and are designed for a Single User in either Fall Restraint, Fall Arrest or for Abseil. For use as Single Point Anchors in Australia and New Zealand, they are strictly rated to only 15kN and a Single User.

The Engineered Single Point Anchors User Instruction Manual (UIM) has been designed to comply with AS/NZS 5532:2013 Section 7 Instructions for Use & Marking. For supplementary information, see AS/NZS 1891.4:2025 Personal equipment for work at height Part 4: Selection, use and maintenance.

Certificates Sighted

Code(s)	Certificate No.	Certification Body
AFA930001SS, AFA935515, AFA930310, AFA935502, AFA935503, AFA935504	BMP 760374 (Benchmark) – Expiry 02/02/2027	BSI Group (AS/NZS 5532:2013)

Copies of certificates and test reports are available from KStrong on request.

Disclaimer

The information provided in this statement is based on technical data obtained by KStrong under laboratory conditions and is believed to be reliable; however, KStrong makes no guarantees regarding results and assumes no liability or obligation arising from the use of this information. Since conditions of end use are beyond KStrong's control, it is the user's responsibility to assess hazard levels, determine product suitability for the intended application, and ensure the use of appropriate personal protective equipment.

All KStrong anchors must be installed, used, inspected and maintained strictly in accordance with the UIM, by trained and competent personnel. The suitability of the anchorage structure must be verified by a competent person and/or qualified engineer, and concrete anchors must be proof loaded as specified in the UIM. Installation not in accordance with the UIM, alteration of the product, or the use of non-KStrong components will void all certification and warranties.

Product Warranty

Applies to: all Engineered Single Point Anchors listed under Product Certification.

All KStrong products are manufactured under strict quality control and tested in accordance with relevant international standards to ensure reliability, durability, and user safety.

KStrong warrants that its products are free from manufacturing defects in material and workmanship for a period of two (2) years from the date of purchase, unless otherwise specified. This warranty applies under normal conditions of use, storage, and maintenance as described in the User Instruction Manual (UIM).

Warranty Conditions - This warranty is valid only when:

- The product has been used strictly in accordance with manufacturer guidelines and safety instructions.
- The product has been installed, maintained, and inspected by trained and competent personnel.
- The product has not been altered, modified, or repaired by any unauthorized party.
- The product has not been exposed to misuse, negligence, or abnormal conditions (e.g. chemical contamination, fire, impact, or excessive loading).
- The product is registered with KStrong at the time of purchase or installation, where applicable.

Exclusions - This warranty does not cover:

- Normal wear and tear resulting from regular use.
- Damage due to improper installation, storage, or maintenance.
- Products that have been subjected to a fall arrest or load event.
- Unauthorized modifications or repairs.
- Damage, corrosion, deterioration or system failure caused or contributed to by a failure to complete and document the inspection, cleaning and maintenance required by the site-specific risk assessment. The assessment must set an interval of one to three months based on environmental exposure, with earlier cleaning where significant contamination is found.
- Consequential or incidental damages arising from product failure.

Warranty Claims - To make a warranty claim:

- The client must notify KStrong or the authorized distributor in writing, providing full details of the issue, including proof of purchase, serial number, and system identification.
- The product must be returned to KStrong or its designated service centre for inspection and evaluation.
- If the defect is confirmed to be due to faulty materials or workmanship, KStrong will, at its discretion, repair or replace the product free of charge.

KStrong reserves the right to determine the validity of all warranty claims, and its decision shall be considered final and binding.

Warranty Disclaimer

This warranty is in addition to, and does not affect, the consumer's statutory rights under applicable local laws.

KStrong liability under this warranty is limited strictly to the repair or replacement of the defective product and does not extend to any indirect, incidental, or consequential damages

Inspection

The anchor product, and the surrounding anchorage structure, must be inspected by a competent person no less than once every 12 months, and must meet all specific criteria set out in the inspection record for that product.

www.KStrong.com/australia
customercare@kstrong.com.au