

KSTRONG LADDER MOUNT BRACKET

AFA930123

The KStrong Ladder Bracket AFA930123 is designed to support and secure a temporary ladder whilst accessing a roof from ground level.

Features

- The product may be surface-mounted to steel roofs as well as under tiles to timber battens. The product may also be surface mounted to the tops of parapets. By changing the orientation of rung support arm, the product may also be wall-mounted to concrete, masonry or through cladding into timber studs. Fixings not included.
- Secondary Retention Strop included for securing the ladder once supported.
- Maximum 1 User 120kg
- Each Fixing (5) must support 48kg

How To Use

See User Instruction Manual (UIM) for details of how to install and use this product. 

Components

Ladder Bracket: Powder-Coated Steel

Carabiner: Anodized Aluminium 5kN (Not for Personnel Use)

Strop: PVC-Coated Stainless Steel Cable

Product Strength

Designed to support 120kg including a 2:1 Safety Factor

Weight

4.20 kg ± 0.15 kg

Relevant Standards

Meets the Requirements of Safe Work Australia - Model Code of Practice:

Managing the Risk of Falls at Workplaces 2011. Section 9.

Inspection & Testing

This product, and the surrounding anchorage structure should be inspected before and after use by the user, and every 12 months by a competent person other than the user.

