

## CURVED BASE PURLIN ANCHOR

**AFA935502**

The KStrong Curved Base Purlin Anchor AFA935502 is designed for use as a Single Point Anchor by a Single User in Fall Restraint & Fall Arrest only. This anchor is not suitable for Abseiling.

### Features

- May be fixed through roof sheeting into the steel purlin. See User Instruction Manual (UIM) for minimum purlin size, purlin spacing and roof sheet thickness.
- Suitable for Fall Restraint & Fall Arrest only.
- Maximum 1 user when used as a Single Point Anchor.
- Fully multidirectional use when installed into Steel.
- This product may deform under 15kN loads when used as a Single Point Anchor.
- Anchorage Structural Requirement for this product when used as a Single Point Anchor is 15kN.



### How To Use

See User Instruction Manual (UIM) for details of how to install and use this product. 

### Components

Anchor Assembly : 316 Stainless Steel  
Waterproofing Washer : Neoprene Rubber

### Product Strength

15kN when used as a Single Point Anchor.

### Weight

760g +/- 25g

### Relevant Standards

Certified to AS/NZS 5532 2013.

Meets the Requirements of AS/NZS 1891.4 2025

### Inspection & Testing

This product should be inspected before and after use by the user, and every 12 months by a competent person other than the user. When installed into concrete this product must also be load-tested to 50% of its strength rating, for a period of 3 minutes, as part of its inspection by a competent person.

