IMPAXX CABLE JOINER

AFF111506

The KStrong IMPAXX Cable Joiner AFF111506 is prescribed for use as a component within a KStrong IMPAXX Engineered, Permanently Installed, Horizontal Lifeline System.

This component is strictly for use within a IMPAXX CONSTEEL Standard In-Line Shock Absorber System (AFF112100) & must NOT be used within an IMPAXX LONGSPAN In-Line Shock Absorber System (AFF114112).

Features

- May be fitted to KStrong IMPAXX Stainless Steel 8mm 7x19 and 7x7 Cable only.
- This component is strictly for use within a KStrong IMPAXX Engineered, Permanently Installed, Horizontal Lifeline System, exactly as prescribed within the User Instruction Manual (UIM). All KStrong IMPAXX Horizontal Lifeline Systems are for Fall Restraint and Fall Arrest Only, and must never be used for Abseil or Materials Handling.
- Maximum 4 Users per KStrong IMPAXX CONSTEEL Horizontal Lifeline System.
- This component is designed to accommodate the directional loading(s) imposed within the KStrong IMPAXX Horizontal Lifeline System in which it is prescribed.
- This component may deform when the KStrong IMPAXX Horizontal Lifeline System is impacted by a single or muti user fall.
- Minimum Anchorage Strength will be 26kN.



How To Use

See User Instruction Manual (UIM) for details of how to install and use this product.

Components

Stainless Steel

Product Strength

26kN

Weight

148.0 gm ± 10.0 gm

Relevant Standards

Certified to EN795:2012 Type C, CEN/TS 16415:2013 Type C, (ATEX) EN ISO 80079-36:2016 & EN ISO 80079-37:2016.

Inspection & Testing

This component of a KStrong IMPAXX Horizontal Lifeline System should be inspected before and after use by the user, and every 12 months by a competent person other than the user.

