IMPAXX SHUTTLE

AFF119025

The KStrong IMPAXX Shuttle AFF119025 is prescribed for use as a component within a KStrong IMPAXX Engineered, Permanently Installed, Horizontal Lifeline System.

This component may be used in both a IMPAXX CONSTEEL Standard In-Line Shock Absorber System (AFF112100), as well as a IMPAXX LONGSPAN In-Line Shock Absorber System (AFF114112).

Features

- May be used with all KStrong IMPAXX Horizontal Lifeline Systems where the cable is within reach of the user and/or a Self Retracting Lifeline (SRL) is not to be connected to the cable.
- This component is strictly for use within a KStrong IMPAXX Engineered, Permanently Installed, Horizontal Lifeline System, exactly as prescribed within the User Instruction Manual (UIM). All KStrong IMPAXX Horizontal Lifeline Systems are for Fall Restraint and Fall Arrest Only, and must never be used for Abseil or Materials Handling.
- Maximum 1 User per KStrong IMPAXX Shuttle and only the prescribed Locking Carabiner must be used.
- This component is designed to accommodate the directional loading(s) imposed within the KStrong IMPAXX Horizontal Lifeline System in which it is prescribed.
- This component may deform when the KStrong IMPAXX Horizontal Lifeline System is impacted by a fall.

How To Use

See User Instruction Manual (UIM) for details of how to install and use this product.



Components

Stainless Steel

Product Strength

23kN

Weight

410g

Relevant Standards

Certified to EN795:2012 Type C, CEN/TS 16415:2013 Type C, (ATEX) EN ISO 80079-36:2016 & EN ISO 80079-37:2016.

Inspection & Testing

This component of a KStrong IMPAXX Horizontal Lifeline System should be inspected before and after use by the user, and every 12 months by a competent person other than the user.



