IMPAXX OVERHEAD SHUTTLE

AFF119028

The KStrong IMPAXX Overhead Shuttle AFF119028 is prescribed for use as a component within a KStrong IMPAXX Engineered, Permanently Installed, Horizontal Lifeline System.

This component may be used in both a IMPAXX CONSTEEL Standard In-Line Shock Absorber System (AFF112100), as well as a IMPAXX LONGSPAN In-Line Shock Absorber System (AFF114112).

Features

- Must be used on all KStrong IMPAXX Horizontal Lifeline System overhead installations where the cable is out of reach of the user and/or a Self Retracting Lifeline (SRL) is to be connected to the cable.
- This component is strictly for use within a KStrong IMPAXX Engineered, Permanently Installed, Horizontal Lifeline System, exactly as prescribed within the User Instruction Manual (UIM). All KStrong IMPAXX Horizontal Lifeline Systems are for Fall Restraint and Fall Arrest Only, and must never be used for Abseil or Materials Handling.
- Maximum 1 Users per KStrong IMPAXX Overhead Shuttle and only the prescribed Locking Carabiner must be used.
- This component is designed to accommodate the directional loading(s) imposed within the KStrong IMPAXX Horizontal Lifeline System in which it is prescribed.
- This component may deform when the KStrong IMPAXX Horizontal Lifeline System is impacted by a single or muti user fall.

How To Use

See User Instruction Manual (UIM) for details of how to install and use this product.



Components

Stainless Steel

Product Strength

15kN

Weight

1.34kg

Relevant Standards

Certified to EN795:2012 Type C, CEN/TS 16415:2013 Type C, (ATEX) EN ISO 80079-36:2016 & EN ISO 80079-37:2016.

Inspection & Testing

This component of a KStrong IMPAXX Horizontal Lifeline System should be inspected before and after use by the user, and every 12 months by a competent person other than the user.

