EPIC WORK POSITIONING LANYARD WITH ALUMINUM

AFL405351(PR)

ADJUSTER & PROTECTIVE SLEEVE

KStrong has developed a range of Work Positioning Lanyards to be used in conjunction with a fall arrest Harness or Work Positioning Belt to provide additional support to the user, allowing them to work more comfortable and safer.

Note: A Work Positioning Lanyard must be used in conjunction with a fall arrest Harness and a separate fall arrest device such as a fall arrest Lanyard or an inertia reel.

FEATURES

- Kernmantle Rope 12mm c/w protective sleeve
- Aluminum Snap Hook & Karabiner
- Rope Grab Aluminum
- Abrasion Resistant Thimble
- Compass Asset Technology

HOW TO USE

Refer to User Instruction Manual





MATERIAL COMPONENTS

Webbing Sleeve: Polyester, MBS 30kN

Kernmantle Rope: 12mm High Tenacity Polyester Rope, MBS 25kN Metal Components: Snap Hook & Karabiner Aluminum, MBS 23kN

Rope Grab Aluminum, MBS 15kN

Stitching Thread: High Tenacity Polyester (Colour Contrasted)

WEIGHT

0.655 kg

LENGTH

2m

RELEVANT STANDARDS

EN 358:2018

