

BRUTE LOAD ARRESTOR 400KG X 10M

AFZ1840010

The Brute Load Arrestors are designed as secondary safety back-up for overhead loads, used in conjunction with a primary lifting device or support, such as a hoist or permanently suspended load.

If the primary support fails, the load arrestor will automatically stop the load from falling, thereby preventing damage to the load and, more importantly, protecting users below.

Features

- Portable and easy to install, simply add D shackles with the desired rating to mount.
- High Impact Polymer casing
- Shock Absorbing Systems
- Fast-acting braking system
- Self-Retracting Steel Cable
- Suitable to be used for Basket Ball Hoops, Stage lighting, Car assembly, Lifts & Industrial machinery.
- Can be supplied in different lengths, refer –
 - AFZ1840015 – 15m
 - AFZ1840020 – 20m

Load Capacity

400 kgs

Material

Casing	:	High Impact Polymer
Wire	:	5.8mm Galvanised Steel – MBS 20kN
Wire Guide	:	Brass
Snout	:	Rubber
Carry Handle	:	Rubber

Weight

AFZ1840010	:	11.160 kgs. ± 0.10 kgs.
AFZ1840015	:	11.660 kgs. ± 0.10 kgs.
AFZ1840020	:	12.160 kgs. ± 0.10 kgs.

How To Use

Refer to User Instruction Manual



Relevant Standards

Machine Directive 2006/42/CE

