

KSTRONG TEMPORARY RETRACTABLE WIRE 18M HORIZONTAL LIFELINE

AFA940014


KStrong Temporary Horizontal Wire Retractable Lifeline has been designed to be easily installed in a horizontal plane allowing the user to have access to a suitable anchorage whilst working over large distances.

Features

- Handy and portable design.
- Extremely easy to install; retractable lifeline is simply pulled out for installation up to the required length and retracted back with the built-in winch into an easy-to-carry case.
- Inbuilt Winch for easy retraction of rope back into the housing/case for fast, simple and safe dismantle. Hence, eliminating large and bulky coils of cable that are difficult to set-up and store.
- Has inbuilt shock absorption mechanism to limit the impact forces during fall arrest. Suitable for 2 users.



How To Use

Refer to User Instruction Manual 

Metal Components

Wire Rope	:	Construction - 7X19 Galvanized steel wire (MBS-22 kN)
Swivel Snap Hook	:	Material - Alloy Steel (MBS-23 kN)
Casing	:	Material - Durable & High Strength Polymer
O-rings	:	Material - Alloy Steel (MBS-23 kN)
Universal Life Line Tension Indicator	:	Material - Stainless Steel (MBS-25 kN)

System Strength and Span


Minimum Breaking Strength	:	22kN
Maximum Span	:	18m

Weight

14.390 kgs ± 0.20 kgs

Relevant Standards

EN 795:2012 Type C & TS 16415:2013 Type C (for up to 2 Users)

 II 2G
Ex h IIc T6 Gb
EN 80079-36:2016
EN 80079-37:2016

 0598

