

BRUTE™ SERIES

BRUTE LEADING EDGE RETRACTABLE FALL ARREST BLOCKS WEBBING

KStrong has developed a range of Retractable Blocks in Webbing specifically engineered for Leading Edge applications such as construction sites, roof tops etc. The unique design allows the user to use the Retractable Block Horizontally and is protected when subjected to a fall over a edge. It is Lightweight, Compact and Robust ensuring your safety when working at heights.

Features and Benefits

- ◆ Swivel Anchorage Eye
- ◆ High Impact Load Bearing Polymer Casing
- ◆ Ergonomic Carry handle for ease of transportation
- ◆ 25mm Toughened Webbing
- ◆ Energy Absorber and Protective Cover
- ◆ Load Capacity 140 kgs for vertical use & 140 kgs for Horizontal use.
- ◆ Leading Edge Rated (R>0.5mm).
- ◆ MBS 15kN
- ◆ Temperature Range : -30° to +50° C
- ◆ QR code for ease of Identification and Service History
- ◆ ANSI Steel Swivel Snap Hook with Fall Indicator

Materials

- ◆ Polymer Casing
- ◆ 25mm polyester textile webbing.- MBS 20kN
- ◆ ANSI Steel ANSI Snap Hook - MBS 23kN
- ◆ ANSI Steel ANSI Karabiner - MBS 23kN

How To Use

- ◆ Refer to User Instruction Manual 



CE 0598

EN 360:2023

AS/NZS 1891.3 2020



AFS550003.5SE

Length: 3.5m
Weight: 1.9kg



AFS550007SE

Length: 7m
Weight: 2.89kg