

ECOR

ENERGY ABSORBING WEBBING LANYARD

TECHNICAL DATA SHEET



KStrong has developed a range of Shock Absorbing Webbing Lanyards to ensure the user is protected when working at heights. The shock absorber effectively arrests the fall, minimising the forces to the body.

ECOR

ENERGY ABSORBING 44MM WEBBING LANYARD



ENERGY ABSORBING 44MM WEBBING LANYARD C/W SNAP HOOKS

ANL408131



ENERGY ABSORBING 44MM WEBBING LANYARD C/W SNAP HOOK & SCAFFOLD HOOK

ANL408141



ENERGY ABSORBING 44MM WEBBING FORKED LANYARD C/W SNAP HOOK & SCAFFOLD HOOKS

ANL408612

ECOR

ENERGY ABSORBING WEBBING LANYARD

LANYARD CODES			
FEATURES	ANL408131	ANL408141	ANL408612
LANYARD WEIGHT			
	1030gm	1270gm	2020gm
FEATURES			
44MM WEBBING	✓	✓	✓
SNAP HOOK	✓	✓	✓
SCAFFOLD HOOK		✓	✓
LABEL PACK	✓	✓	✓
ENERGY ABSORBER	✓	✓	✓
COMPASS ASSET TECHNOLOGY	✓	✓	✓
LENGTH IN METERS			
	2m	2m	2m
CAPACITY			
	140kg	140kg	140kg
RELEVANT STANDARDS			
AS 1891.5:2020	✓	✓	✓
10 Year Shelf Life From Date Of Manufacture.			

ECOR

ENERGY ABSORBING WEBBING LANYARD

MATERIAL SPECIFICATIONS

WEBBING

- Polyester 44mm wide
- MBS 25kN

THREAD / STITCHING

- High Tenacity Polyester (Colour Contrasted)

METAL COMPONENTS

- ANSI Steel Snap Hooks - MBS 23kN
- ANSI Scaffold Hook Steel - MBS 23kN
- D Ring - MBS 23kN
- Finish - Silver Galvanized

ENERGY ABSORBER

- 44mm Polyester Back Up Webbing
- 44mm Polyamide Tear Webbing
- Clear Protective Covering