

ELEMENT

ATEX ENERGY ABSORBING WEBBING LANYARD

TECHNICAL DATA SHEET



KStrong ATEX Shock Absorbing Lanyards have been designed to be used in potentially explosive atmospheres whilst protecting the user. Ideally used in Mining, Petrochemical industries & Confined Space where there is need to prevent any electrostatic discharge igniting the explosive atmosphere.

ELEMENT

ATEX ENERGY ABSORBING 44MM WEBBING LANYARD



ATEX ENERGY ABSORBING 44MM WEBBING LANYARD C/W STAINLESS STEEL SNAP HOOKS

ANL408721



ATEX ENERGY ABSORBING 44MM WEBBING LANYARD C/W STAINLESS STEEL SNAP
HOOK AND SCAFFOLD HOOK

ANL408731



ATEX ENERGY ABSORBING 44MM WEBBING FORKED LANYARD C/W
STAINLESS STEEL SNAP HOOK AND SCAFFOLD HOOKS

ANL408825

ELEMENT

ATEX ENERGY ABSORBING 44MM WEBBING LANYARD

LANYARD CODES			
FEATURES	ANL408721	ANL408731	ANL408825
LANYARD WEIGHT			
	0.72kg	1.04kg	1.13kg
FEATURES			
ANTI-STATIC 44MM WEBBING	✓	✓	✓
STAINLESS STEEL SNAP HOOK	✓	✓	✓
STAINLESS STEEL SCAFFOLD HOOK		✓	✓
LABEL PACK	✓	✓	✓
ANTI-STATIC ENERGY ABSORBER COVER	✓	✓	✓
ENERGY ABSORBER	✓	✓	✓
COMPASS ASSET TECHNOLOGY	✓	✓	✓
LENGTH IN METERS			
	2m	2m	2m
CAPACITY			
	140kg	140kg	140kg
RELEVANT STANDARDS			
AS 1891.5:2020	✓	✓	✓
10 Year Shelf Life From Date Of Manufacture.			

ELEMENT

ATEX ENERGY ABSORBING 44MM WEBBING LANYARD

MATERIAL SPECIFICATIONS

WEBBING

- 44mm wide Anti-Static Polyester
- MBS 23kN

THREAD / STITCHING

- Anti-Static High Tenacity Conduction Polyester Thread (Colour Contrasted)

METAL COMPONENTS

- Stainless Steel Snap Hooks- MBS 23kN & Gate strength 6kN
- Stainless Steel Scaffold Hook- MBS 23kN & Gate strength 6kN

ENERGY ABSORBER

- 44mm Polyester Back Up Webbing
- 44mm Polyamide Tear Webbing
- Anti-Static Shock absorber Cover