

ELEMENT

**EXTREMEX ENERGY ABSORBING
WEBBING LANYARD**

TECHNICAL DATA SHEET



KStrong ExtremeX Shock Absorbing Lanyards have been designed to be used in the most hostile conditions whilst protecting the user. Ideally used in Offshore, Petrochemical Industry, Water Treatments plants and Food processing Industries. The Endure guard coating protects the webbing against oil, water, & dirt, as well as enhancing the abrasion resistant properties of the webbing.

ELEMENT

EXTREMEX ENERGY ABSORBING 44MM WEBBING LANYARD



EXTREMEX ENERGY ABSORBING 44MM WEBBING LANYARD C/W SNAP HOOKS

ANL408741



EXTREMEX ENERGY ABSORBING 44MM WEBBING LANYARD C/W SNAP HOOK AND SCAFFOLD HOOK

ANL408751



EXTREMEX ENERGY ABSORBING 44MM WEBBING LANYARD C/W SNAP HOOK AND SCAFFOLD HOOKS

ANL408845

ELEMENT

EXTREMEX ENERGY ABSORBING 44MM WEBBING LANYARD

LANYARD CODES			
FEATURES	ANL408741	ANL408751	ANL408845
LANYARD WEIGHT			
	0.98kg	1.26kg	1.96kg
FEATURES			
TEAR AND CUT RESISTANT 44MM WEBBING	✓	✓	✓
STAINLESS STEEL SNAP HOOK	✓	✓	✓
STAINLESS STEEL SCAFFOLD HOOK		✓	✓
LABEL PACK	✓	✓	✓
ANTI-STATIC ENERGY ABSORBER COVER	✓	✓	✓
ENERGY ABSORBER	✓	✓	✓
COMPASS ASSET TECHNOLOGY	✓	✓	✓
LENGTH IN METERS			
	2m	2m	2m
CAPACITY			
	140kg	140kg	140kg
RELEVANT STANDARDS			
AS 1891.5:2020	✓	✓	✓
10 Year Shelf Life From Date Of Manufacture.			

ELEMENT

EXTREMEX ENERGY ABSORBING 44MM WEBBING LANYARD

MATERIAL SPECIFICATIONS

WEBBING

- 44mm Wide Polyester, MBS 25kN
- Endure guard- Oil, Water, Dirt and Abrasion Resistant Webbing

THREAD / STITCHING

- High Tenacity Polyester (Colour Contrasted)

METAL COMPONENTS

- Stainless Steel Snap Hooks- MBS 23kN & Gate strength 6kN
- Stainless Steel Scaffold Hook- MBS 23kN & Gate strength 6kN

ENERGY ABSORBER

- 44mm Polyester Back Up Webbing
- 44mm Polyamide Tear Webbing
- Anti-Static Shock absorber Cover