



FALL PROTECTION ANCHOR STRAP



LIGHTWEIGHT & CONVENIENT ANCHOR
FOR POSTS AND BEAMS



DURABLE WEBBING
AND HEAVY DUTY STITCHING



MEETS ALL APPLICABLE
STANDARDS FOR FALL
ARREST



AVAILABLE IN
VARIETY OF
LENGTHS

WEBBING



AFA920015
**CHOKER STYLE ANCHOR STRAP W/
WEAR PAD 1.5M**



AFA921515
WEBBING ANCHOR STRAP 1.5M



AFA927015
**HOTWORX WELDERS ANCHOR STRAP
1.5M**



AFA921005
FLAT WEBBING CROSS ARM ANCHOR STRAP 0.5M



AFA921010
FLAT WEBBING CROSS ARM ANCHOR STRAP 1.0M



AFA910118

STEEL WIRE ROPE CHOKER SLING W/ O-RINGS 1.8M

PRODUCT	FEATURES	SYSTEM STRENGTH	CERTIFICATION
AFA920015	<ul style="list-style-type: none"> Anchor strap with a wear guard has a choking configuration and is small, lightweight, and flexible making it easy to handle and install in the field. Steel rings allow any type of connector to be hooked to it Comes with a wear protector for wrapping around sharp objects and increases the life of the sling 	23kN	AS/NZS 5532:2013 EN 795:2012 Type B
AFA921515	<ul style="list-style-type: none"> Option to wrap the sling in a single, double or triple style or tie end to end making it a versatile and handy temporary anchor points 20mm wide polyester webbing 	23kN	AS/NZS 5532:2013 EN 795:2012 Type B
AFA921005	<ul style="list-style-type: none"> Provides a portable fall arrest rated anchorage point Durable, lightweight, portable and easy to install High strength rated to 25kN for personal use Ideal for use as an anchorage connector for fall arrest, restraint, work positioning, suspension or rescue systems 	23kN	AS/NZS 5532:2013 EN 795:2012 Type B
AFA921010			
AFA927015	<ul style="list-style-type: none"> Ideal anchorage solution to anchor fall arrest blocks overhead Heavy duty webbing resists cuts and abrasions Ideal for structural steel beams other rated structures Simple Choke-on attachment can be moved and reused Can be used as temporary and semi-permanent anchor To be wrapped around structures to create a secure anchor point 	23kN	AS/NZS 5532:2013 EN 795:2012 Type B ISO 9150:1988 EN ISO 15025:2002
AFA910118	<ul style="list-style-type: none"> Can be used as temporary and semi-permanent anchor To be wrapped around structures to create a secure anchor point Suited for sharp edges PVC protective sleeve for added protection Easy to install Lightweight and durable 	23kN	AS/NZS 5532:2013 EN 795:2012 Type B