



FALL PROTECTION BEAM ANCHORS



PROVIDES ADJUSTABLE ANCHORAGE POINT FOR FALL ARREST SYSTEMS



FITS VARIOUS I-BEAM & H-BEAM FLANGES



SUITABLE FOR OVERHEAD & FOOT-LEVEL APPLICATIONS



USED IN FIXED POSITION OR SLIDES ALONG THE BEAM



AFA930401
EDGE BEAM CLAMP ANCHOR 90MM - 340MM



AFA930411
EDGE BEAM CLAMP ANCHOR 75MM - 150MM



AFA930412
EDGE TROLLEY BEAM ANCHOR 80MM - 250MM



AFA930413
VERTICAL BEAM CLAMP ANCHOR 90MM - 340MM

PRODUCT	FLANGE SIZE	FEATURES	SYSTEM STRENGTH	CERTIFICATION
AFA930401	90MM - 340MM	<ul style="list-style-type: none"> Once installed, D-ring can be used for connection with a variety of Connectors Lightweight Suitable for 1-person 	23kN	AS/NZS 5532:2013 EN 795:2012 Type B ANSI Z359.18-2017 Type A
AFA930411	75MM - 150MM			
AFA930412	80MM - 250MM	<ul style="list-style-type: none"> Corrosion Resistant & easy to install Comes with Adjustable Flanges for use on different beam sizes 		
AFA930413	90MM - 340MM	<ul style="list-style-type: none"> Easily fitted & removed using Adjustment Nut & Locking Pin Suitable for Vertical & Horizontal applications 		