







# FALL PROTECTION CONCRETE ANCHORS

-  CAN BE FIXED ON WALLS, CEILING, ROOFTOPS OR STEEL STRUCTURES
-  MADE OF HIGH-STRENGTH **STAINLESS STEEL** COMPONENTS
-  DESIGNED FOR **QUICK & FLEXIBLE** INSTALLATION
-  SUPPORTS **HIGH LOAD** CAPACITY

## CONCRETE ANCHORS



**AFA930002**  
**SS ABSEILING ANCHOR**



**AFA930001SS**  
**SINGLE STAINLESS STEEL POINT ANCHOR**



**AFA930301**  
**REMOVABLE CONCRETE ANCHOR**



**AFA935515**  
**STAINLESS STEEL M12 CONCRETE ANCHOR POINT**



**AFA935508(100)**  
**STAINLESS STEEL M16 CONCRETE ANCHOR POINT**



**AFA930310**  
**REMOVABLE CONCRETE ANCHOR C/W SLEEVE**

# SWIVEL ANCHORS



**AFA930316**  
**SWIVEL D-RING FORGED ANCHOR**



**AFA930316C**  
**SWIVEL D-RING FORGED CONCRETE ANCHOR**

PRODUCT	FEATURES	SYSTEM STRENGTH	CERTIFICATION
<b>AFA930002</b>	<ul style="list-style-type: none"> <li>Forged Stainless Steel Abseiling Anchor</li> <li>Steel Fixing - M16 Steel Bolt &amp; Nut Required</li> <li>Concrete Fixing use - M16 Chemical Fastener</li> </ul>	40kN	EN 795:2012 Type A AS/NZS 5532:2013
<b>AFA930001SS</b>	<ul style="list-style-type: none"> <li>Forged Stainless Steel single point anchor.</li> <li>Sustains the load impact in all three axis 'X', 'Y', &amp; 'Z'</li> <li>Reusable &amp; extremely durable</li> <li>No sharp edges or burrs</li> <li>Steel Fixing - M12 Steel Bolt &amp; Nut Required</li> <li>Concrete Fixing use - M12 Chemical Fastener</li> </ul>	45kN	EN 795:2012 Type A ANSI Z 359.1:2007 TS 16415:2013 Type A AS/NZS 5532:2013
<b>AFA930301</b>	<ul style="list-style-type: none"> <li>Can be removed without damaging the structure or anchor allowing reuse</li> <li>Suitable for pre-defined hole of diameter 18-19mm through a drilling depth of 110mm</li> <li>Can be used in concrete, rock, or other suitable substrates</li> </ul>	15kN	EN 795:2012 Type B AS/NZS 5532:2013
<b>AFA935515</b>	<ul style="list-style-type: none"> <li>14mm dia. x 110mm hole required for bolt</li> <li>Supplied with Stainless Steel ID Tag</li> <li>Chemical Adhesive Capsule not supplied with bolt. HVU 10HVU M12x110 Code: 256693</li> </ul>	23kN	EN 795:2012 Type A AS/NZS 5532:2013
<b>AFA935508(100)</b>	<ul style="list-style-type: none"> <li>18mm dia. x 110mm hole required for bolt</li> <li>Supplied with Stainless Steel ID Tag</li> <li>Chemical Adhesive Capsule not supplied with bolt. HVU M16x125 Code: 256694</li> </ul>	23kN	EN 795:2012 Type A AS/NZS 5532:2013
<b>AFA930310</b>	<ul style="list-style-type: none"> <li>Suitable for vertical, horizontal and Overhead applications</li> <li>For use as an anchorage point for fall protection equipment</li> <li>Simply insert Swivel D-Ring Pin and lock into the threaded Stud</li> <li>The Swivel Eye pin can be removed and reused in another threaded Stud</li> <li>Install into Concrete with minimum thickness of 150mm, drill hole size is 20mm x 110mm</li> </ul>	15kN	EN 795:2012 Type A AS/NZS 5532:2013
<b>AFA930316</b>	<ul style="list-style-type: none"> <li>360 degree Swivel D-Ring Anchor point that can Pivot or Flip 180 degrees to self align with direction of load</li> <li>Suitable for Metal Structures supplied with M16 bolt x 110</li> </ul>	44kN	EN 795:2012 Type A ANSI Z359.18-2017 Type A AS/NZS 5532:2013
<b>AFA930316C</b>	<ul style="list-style-type: none"> <li>Anchor designed to be fixed into concrete structures.</li> <li>For Concrete structures use M16 Bolt</li> </ul>	44kN	EN 795:2012 Type A AS/NZS 5532:2013