

KSTRONG INSPECTION, MAINTENANCE AND LIFESPAN FOR SRL'S, TYPE 3 RESCUE RETRIEVALS AND WINCHES

Products	Pre-Use Check Required (Refer Check list)	Maximum interval between Periodic Inspections	Authorized Service Period	Inspection and Servicing conducted by	Lifespan
Webbing SRL's					
Mini 2.5m	YES	6 Months	Non Serviceable	Trained Personnel	10 Years
Vulcan 2m	YES	6 Months	Non Serviceable	Trained Personnel	10 Years
Brute 3.5m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	10 Years
Brute 6m - 12m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited
Brute Sharp Edge 3.5m - 7.0m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited
Wire SRL's					
Brute 3.5m	YES	6 Months	3 Years*	Trained Personnel	10 Years
Brute 6m - 30m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited
Brute Sealed 10m - 30m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited
Brute Sharpe Edge 3.5m - 20m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited
Type 3 Rescue Retrievals					
20m - 30m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited
Brute Sealed 20m - 30m	YES	6 Months	3 Years*	Authorized service centre or Trained personnel	Unlimited

The following factors can reduce the Lifespan of the product: intense use, contact with chemical substances, specially aggressive environments, extreme temperature exposure, UV exposure, abrasions, cuts, violent impacts, incorrect use or lack of maintenance.

Unlimited Lifespan is determined if the product has been serviced in accordance with the relevant UIM and the service register is up to date.

DISCLAIMER: Prior to use, the end user must read and understand the manufacturer's instructions supplied with this product at the time of shipment and seek training from their employer's trained personnel on the proper usage of the product.

The manufacturer is not liable or responsible for any loss, damage or injury caused or incurred by any person on grounds of improper usage or installation of this product.

Product **"Must"** be withdrawn from service if a fall has occurred, failed the pre use check (refer check list) or comes in contact with Chemicals.

The product must be returned to the service provider for evaluation.

*A period of not longer than 3 years is recommended for Infrequent to light usage, where the type of use may be moderate to light a 2 year period is recommend. Products subjected to severe or heavy usage should be serviced at least annually.

If the equipment is in heavy usage or is used in a harsh environment, then the frequency of inspection should be increased in accordance with the relevant UIM