

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

Declaration #: DOC-UFA30031

Declaration Date: 09/09/2025

Item #: UFH11502G

Description: KStrong® 4-way Anchor Plate

Brand Name: KStrong

Manufacturer: KStrong

Address: 18505 Intercontinental Crossing, Houston, TX 77073

Additional Items Conforming
Under this Declaration (If Applicable):

KStrong declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

ANSI Z359.18 – 2017

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014



Level 1:

KStrong Lab Outside the Scope of ISO/IEC Standard 17025:2017



Level 2:

KStrong Lab Within the Scope of ISO/IEC Standard 17025:2017




Level 3:

Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017

Supporting Documentation: KS-Test-UFA30031.pdf

This Certificate is a guarantee that the above standard(s) was met by the requirements of such standard. Testing was performed under normal operation mode. The results of testing apply only to the particular sample tested and the specific test carried out. This Certificate is only issued for products which have passed the testing requirements of listed standard(s).

Authorized Signature:


John H. Kemp Jr.
President - KStrong

ISO 17025 Accredited Test Laboratory

intertek
Total Quality. Assured.



Intertek Testing Services NA, Inc.
3933 US Rt. 11
Cortland, NY 13045
Tel: 1 607-753-6711
www.intertek.com

Accrediting Agency



A2LA
5202 Presidents Court, Ste 220
Frederick, MD 21703
Tel: 301.644.3248
info@A2LA.org

KSTRONG INC. TEST REPORT

SCOPE OF WORKs

ANSI Z359.18 – 2017 Safety Requirements for Anchorage Connectors for Active Fall Protection Systems

REPORT NUMBER

106243287CRT-001

ORIGINAL REPORT NUMBER

105940655CRT-001

ISSUE DATE

September 9, 2025

PAGES

8

DOCUMENT CONTROL NUMBER

GFT-OP-10a (6-March-2017)

© 2017 INTERTEK





Total Quality. Assured.

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025

3933 US Route 11

Cortland, New York ,USA

13045

Telephone: 607-758-6246

Facsimile: NA

www.intertek.com

KStrong Inc.

18505 Intercontinental Crossing,

Houston, Texas

77073, USA

Report Number..... : 106243287CRT-001

Signed Quote Number..... : Qu-01549717

PO Number..... N/A

Name of Testing Laboratory

Preparing the Report : Intertek Testing Services NA Inc.

Test Specification:

Standard..... : ANSI/ASSP Z359.18-2017

Date(s) of Testing..... : 09/10/2024 – 09/11/2024

Product Description:

Product Type: : Anchor

Brand Name: : KStrong

Model Number(s): : UFA30031

Model Sharing : N/A

Date(s) Samples Received : 6/26/24

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025



SECTION 1

SUMMARY OF TESTING

| TESTS COMPLETED | ANSI/ASSP Z359.18-2017 CLAUSE | STATUS |
|--|----------------------------------|--------|
| Design Requirements | 3 | PASS |
| Conditioning (Pre Dynamic Strength) Non Textile Abrasion | 4.2.2.1.2 | PASS |
| Dynamic Strength Test- Type A | 4.2.2.1.4 | PASS |
| Residual Dynamic Strength- Type A | 4.2.3.1 | PASS |
| Static Strength Test (Per loading direction) | 4.2.1.1 | PASS |

SECTION 2

This test report concludes the work anticipated in the testing phase of your project. If there are any questions regarding this report please contact the undersigned at 607-753-6711.

| | | | |
|----------------------|---|---------------------|---|
| COMPLETED BY: | Alex Smith | REVIEWED BY: | Matthew Stevens |
| TITLE: | Technician | TITLE: | Team Leader |
| SIGNATURE: |  | SIGNATURE |  |
| DATE | 09/09/2025 | DATE: | 09/09/2025 |

Please see attached test data for details.

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025

SECTION 3**TESTING EQUIPMENT CALIBRATION INFORMATION**

| USED FOR TEST | DESCRIPTION | MANUFACTURER | CONTROL NO. | MODEL NO. | SERIAL NO. | CAL. DATE | CAL. DUE |
|---------------|---------------------|--------------|-------------|-----------|------------|-----------|----------|
| X | Drop Test Structure | Intertek | NA | CAT. 3 | - | N/A | N/A |
| X | Test Dead Weight | NA | 15064 | 282 lbs | - | VBV | VBV |
| X | Load Cell | Interface | L099 | - | - | 10/27/23 | 10/27/24 |
| X | Load Cell | Interface | G139 | - | - | 03/21/24 | 03/21/25 |
| X | Tape Measure | Kobalt | H422 | - | - | 07/02/24 | 07/02/25 |

SECTION 3**SUPPLEMENTAL TEST DATA**

| SECTION (TEST) | REQUIREMENT | RESULTS | COMPLIANCE |
|----------------|---|---------|------------|
| 3 | Design Requirements | | PASS |
| 3.1.1 | Connection points shall meet the following requirements: | | PASS |
| | A) A connection point shall support only one user or system at a time. | | |
| | B) A connection point eye on a type T anchorage connector shall be closed eye with a minimum 1" inside radius. | | |
| | C) Except for cinching anchorage connectors, anchorage connectors shall not have closed loops that are not intended for, or could be mistaken for, a connection point. | | PASS |
| | D) Anchorage connectors that include an operable gate, rings, buckle, adjuster or other hardware covered by ANSI Z359.12 shall use hardware that complies with the requirements of that standard. | | PASS |
| | E) Multiple connection points shall only be permitted on tripod and davit style anchorage connectors. | | N/A |
| 3.1.2 | Anchorage connector surfaces that can come in contact with other components shall be free of burrs, pits, sharp corners and roughness that could accelerate cutting or abrading of the components. | | PASS |
| 3.1.3.1 | Corrosion Resistance: all hot-dip galvanized steel shall conform with ASTM A123/A123M, standard specification for Zinc (hot-dip galvanized) Coatings on iron and steel products. | | PASS |
| 3.1.3.2.1 | Type A and Type T: load bearing metallic materials used in the anchorage connectors shall maintain adequate toughness at temperatures between -30 degrees F (-34C) and +130 degrees F (+54C) or be engineered to account for the reduced toughness at low temperatures. Metallic components that have been tested and certified as meeting ANSI Z359.12 are deemed to comply with this section. | | PASS |
| 3.1.3.2.2 | Type D anchorage connectors shall be clearly labeled with a minimum service temperature of -10 degrees F (-23 C) if load bearing parts are made of materials specified in sections 3.1.3.2.2 | | N/A |
| 3.1.3.2.3 | Where a type D anchorage connector is allowed to be used in temperatures below -10 degrees F (-23 C), a qualified person shall verify the anchorage connector will perform as specified per the manufacturers instructions. | | N/A |
| 3.1.3.3 | Finishes: hardware finishes shall be clean and free of scale, rust and deposits of foreign material other than applied protective coatings. | | PASS |

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025

| SECTION (TEST) | REQUIREMENT | RESULTS | COMPLIANCE |
|----------------|---|---------|------------|
| 3.1.3.4 | Welded Assembly: When components are welded, the welding shall meet ANSI/AWS D1.1 for steel, ANSI/AWS D1.2 for aluminum and ANSI/AWS D1.6 for stainless steel. | | PASS |
| 3.1.3.5 | Fasteners: Manufacturer shall provide or specify fasteners for connecting an anchorage connector to an anchorage in its intended application. Information must be included in the user instructions. | | PASS |
| 3.1.4.1 | Textiles shall not contain natural fibers, and shall be made of pure non-recycled synthetic material, having strength, aging, abrasion and heat resistance characteristics equivalent or superior to polyamide or polyester and shall be marked with any restrictions. | | N/A |
| 3.1.4.2 | Stitching/Cutting: If a subsystem uses stitching for connection of load bearing components it shall meet the following requirements: A) Use lock stitching B) Secure the end of threads by backstitching, overlapping stitching or other methods. C) Threads used for sewing shall be physically compatible with the webbing and of a quality comparable to that of the webbing. D) Hot-cut or fuse thermoplastic materials, cord, tape and webbing to prevent fraying. E) The tread color or shade shall contrast with that of the webbing to facilitate visual inspection. | | N/A |
| 3.1.5.1 | Other load bearing materials used in anchorage connectors shall meet the performance requirements of ANSI Z359.18-2017. | | N/A |
| 3.1.5.2 | Integrally connected components to which another standard in the ANSI Z359 series exists shall meet the requirements of ANSI Z359.18-2017. | | N/A |

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025

| SECTION (TEST) | REQUIREMENT | RESULTS | | | COMPLIANCE | | | | |
|-------------------|--|---------|----------------------|----------------------|------------|--|--|--|----------------------|
| 3.2.2.2/4.2.2.2.4 | <u>Dynamic Strength (Type of Anchor) :</u> <div><div>A) Install anchorage connector, conditioned according the applicable requirements of 4.2.2.1.2 or 4.2.2.1.3 on the test anchorage in accordance with 4.1.2</div><div>B) Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation.</div><div>C) Connect the other end of the test lanyard to the test weight specified in 4.1.3</div><div>D) Raise the test weight to achieve a free-fall distance of 3' (+0.1/-0).</div><div>E) Release the test weight by means of quick release mechanism.</div><div>F) Evaluate the test results per 3.2.2.1</div></div> | | | | PASS | | | | |
| | Dynamic Strength Test | | SAMPLE: 1 | SAMPLE: 2 | | | | | SAMPLE: 3 |
| | Anchorage connector successfully arrest the test weight? | | YES | YES | | | | | YES |
| | If deformation occurred did it create more than 1/8" (3mm) between gate and body? | | NO | NO | | | | | NO |
| | MAF (Ref Only) Lbs. | | 2,593 | 2,610 | | | | | 2,588 |
| | | | | | | | | | |

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025

| | | | | | |
|-----------------|---|------------------|------------------|------------------|------|
| 3.2.3.1/4.2.3.2 | Residual Dynamic Strength Test: 1. <u>Repetition of the test specified in 4.2.2.1 using same anchorage connector without further conditioning and the same test lanyard used in first test.</u> 2. <u>Must support the test weight an additional minute after the residual dynamic drop.</u> 3. <u>Evaluate the test results per 3.2.3.1</u> | | | | PASS |
| | Residual Dynamic Strength | SAMPLE: 1 | SAMPLE: 2 | SAMPLE: 3 | |
| | Anchorage connector successfully arrest the test weight? | YES | YES | YES | |
| | Maintain the test weight for a period of at least 1 minute? | YES | YES | YES | |
| | If deformation occurred did it create more than 1/8" (3mm) between gate and body? | NO | NO | NO | |
| | MAF (Ref Only) Lbs. | 3,291 | 3,209 | 3,222 | |
| | | | | | |
| 3.2.1.1/4.2.1.2 | Static Strength Test for Type of Anchorage Connectors: A) <u>A new anchorage connector may be used for each test.</u> B) <u>Test force shall be 5,000 pounds (+50/-0)</u> C) <u>Install anchorage connector on the test anchorage in accordance with requirements of 4.1.2.</u> D) <u>Apply load to the anchorage connector in the direction(s) of loading specified in 4.1.2.5.</u> E) <u>Apply load at no greater than 2"/min and maintain 5,000 pound test load for at least 3 minutes.</u> F) <u>Release load</u> G) <u>Evaluate the test results per 3.2.1.1</u> | | | | PASS |
| | Static Strength Requirements | SAMPLE 3 | SAMPLE 4 | SAMPLE 5 | |
| | Anchorage resist the test load? | YES | YES | YES | |
| | If deformation occurred did it create more than 1/8" (3mm) between gate and body? | NO | NO | NO | |
| | | | | | |
| | | | | | |

TEST REPORT FOR KSTRONG INC.

Report No.: 106243287CRT-001

Date: September 9, 2025

SECTION 5

REVISION HISTORY

| REPORT NUMBER | DATE OF REVISION | DESCRIPTION OF CHANGE: | PROJECT OWNER | REVIEWED BY |
|------------------|------------------|-----------------------------------|---------------|-----------------|
| 105940655CRT-001 | 09/12/2024 | Original Report | Alex Smith | Matthew Stevens |
| 106243287CRT-001 | 06/17/2025 | Report Extension | Alex Smith | Matthew Stevens |
| 106243287CRT-001 | 09/09/2025 | Corrected Address and photographs | Alex Smith | Matthew Stevens |

SECTION 6

PHOTOGRAPH

