

## Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

Declaration #: DOC-UFA710106

Declaration Date: 09/18/2019

Item #: UFA710106

Description: KStrong® 6 ft. Coated Wire Cable Sling with Large and Small O-Rings (ANSI)

Brand Name: KStrong

Manufacturer: KStrong

Address: 150 N. Radnor Chester Road, Suite F200, Radnor, PA 19087

Additional Items Conforming  
Under this Declaration (If Applicable):

KStrong declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

### ANSI Z359.18-2017 Type A

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014



**Level 1:**

KStrong Lab Outside the Scope of ISO/IEC Standard 17025:2017



**Level 2:**

KStrong Lab Within the Scope of ISO/IEC Standard 17025:2017



**Level 3:**

Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017

Supporting Documentation: KS-Test-UFA710106.pdf

This Certificate is a guarantee that the above standard(s) was met by the requirements of such standard. Testing was performed under normal operation mode. The results of testing apply only to the particular sample tested and the specific test carried out. This Certificate is only issued for products which have passed the testing requirements of listed standard(s).

Authorized Signature:



John H. Kemp Jr.  
President - KStrong

ISO 17025 Accredited Test Laboratory

**intertek**  
Total Quality. Assured.



Intertek Testing Services NA, Inc.  
3933 US Rt. 11  
Cortland, NY 13045  
Tel: 1 607-753-6711  
www.intertek.com

Accrediting Agency



A2LA  
5202 Presidents Court, Ste 220  
Frederick, MD 21703  
Tel: 301.644.3248  
info@A2LA.org

# KSTRONG LLC

# TEST REPORT

**SCOPE OF WORK**

ANSI Z359.18 – 2017 Safety Requirements for Anchorage Connectors for Active Fall Protection Systems

**REPORT NUMBER**

104078489CRT-001

**ISSUE DATE**

September 18, 2019

**PAGES**

14

**DOCUMENT CONTROL NUMBER**

GFT-OP-10a (6-March-2017)

© 2017 INTERTEK





Total Quality. Assured.

3933 US Route 11  
Cortland, New York ,USA  
13045

**TEST REPORT FOR KSTRONG LLC**

Report No.: 104078489CRT-001

Date: September 18, 2019

Telephone: 607-758-6246  
Facsimile: None  
www.intertek.com

KSTRONG LLC  
17330 Preston Road #200 D  
Dallas, TX 7525

**Report Number**..... 104078489CRT-001

**Signed Quote Number**..... Qu-01010377-0

**PO Number**..... N/A

**Name of Testing Laboratory**

**Preparing the Report** ..... Intertek Testing Services NA Inc.

**Test Specification:**

**Standard**..... ANSI/ASSE Z359.18-2017

**Date(s) of Testing**..... 9/4/19

**Product Description:** Anchor

**Product Type:** ..... Type A

**Brand Name:** ..... KStrong

**Model Number(s):** ..... UFA710003

UFA710004

UFA710006

UFA710103

UFA710104

UFA710106

**Date(s) Samples Received** ..... 8/30/19

---

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Date: September 18, 2019

**SECTION 1**



**SUMMARY OF TESTING**

TESTS COMPLETED	ANSI/ASSE Z359.18-2017 CLAUSE	STATUS
Design Requirements	3	PASS
Conditioning (pre-dynamic strength) - Non-Textile Abrasion	4.2.2.1.2	PASS
Dynamic Strength Test- Type A (Choked Orientation)	4.2.2.1.4	PASS
Residual Dynamic Strength-Type A (Choked Orientation)	4.2.3.2	PASS
Static Strength Test- Type A	4.2.1.2	PASS
Serviceability Static Load Test- Type A	4.2.4.2	PASS
Markings and Instructions	5	PASS

**SECTION 2**

**CONCLUSION**

This test report concludes the work anticipated in the testing phase of your project. If there are any questions regarding this report, please contact the undersigned at 607-753-6711.

<b>COMPLETED BY:</b>	Matthew Stevens	<b>REVIEWED BY:</b>	Andrew Rulison
<b>TITLE:</b>	Technician	<b>TITLE:</b>	Engineering Supervisor
<b>SIGNATURE:</b>		<b>SIGNATURE</b>	
<b>DATE</b>	9/4/19	<b>DATE:</b>	9/18/19

Please see attached test data for details.

**SECTION 3**

**TESTING EQUIPMENT CALIBRATION INFORMATION**

USED FOR TEST	DESCRIPTION	MANUFACTURER	CONTROL NO.	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE
X	Drop Test Structure	Intertek	NA	CAT. 3	-	N/A	N/A
X	Test Dead Weight	NA	15064	282 lbs	-	VBU	VBU
	Test Dead Weight	NA	15065	300 lbs	-	VBU	VBU
X	Load Cell	Interface	558451	-	-	12/29/18	12/29/19
X	Tape Measure	Stanley	H339	25'	-	5/9/19	5/9/20

SECTION (TEST)	REQUIREMENT	RESULTS	COMPLIANCE
3	Design Requirements		<b>PASS</b>
3.1.1	Connection points shall meet the following requirements: A) A connection point shall support only one user or system at a time.		<b>PASS</b>
	B) A connection point eye on a type T anchorage connector shall be closed eye with a minimum 1" inside radius.		<b>PASS</b>
	C) Except for cinching anchorage connectors, anchorage connectors shall not have closed loops that are not intended for, or could be mistaken for, a connection point.		<b>PASS</b>
	D) Anchorage connectors that include an operable gate, rings, buckle, adjuster or other hardware covered by ANSI Z359.12 shall use hardware that complies with the requirements of that standard.		<b>PASS</b>
	E) Multiple connection points shall only be permitted on tripod and davit style anchorage connectors.		<b>PASS</b>
3.1.2	Anchorage connector surfaces that can come in contact with other components shall be free of burrs, pits, sharp corners and roughness that could accelerate cutting or abrading of the components.		<b>PASS</b>
3.1.3.1	Corrosion Resistance: all hot-dip galvanized steel shall conform with ASTM A123/A123M, standard specification for Zinc (hot-dip galvanized) Coatings on iron and steel products.		<b>PASS</b>
3.1.3.2.1	Type A and Type T: load bearing metallic materials used in the anchorage connectors shall maintain adequate toughness at temperatures between -30 degrees F (-34C) and +130 degrees F (+54C) or be engineered to account for the reduced toughness at low temperatures. Metallic components that have been tested and certified as meeting ANSI Z359.12 are deemed to comply with this section.		<b>PASS</b>

Date: September 18, 2019

SECTION (TEST)	REQUIREMENT	RESULTS	COMPLIANCE
3.1.3.2.2	Type D anchorage connectors shall be clearly labeled with a minimum service temperature of -10 degrees F (-23 C) if load bearing parts are made of materials specified in sections 3.1.3.2.2		NA
3.1.3.2.3	Where a type D anchorage connector is allowed to be used in temperatures below -10 degrees F (-23 C), a qualified person shall verify the anchorage connector will perform as specified per the manufacturers instructions.		NA
3.1.3.3	Finishes: hardware finishes shall be clean and free of scale, rust and deposits of foreign material other than applied protective coatings.		PASS
3.1.3.4	Welded Assembly: When components are welded, the welding shall meet ANSI/AWS D1.1 for steel, ANSI/AWS D1.2 for aluminum and ANSI/AWS D1.6 for stainless steel.		PASS
3.1.3.5	Fasteners: Manufacturer shall provide or specify fasteners for connecting an anchorage connector to an anchorage in its intended application. Information must be included in the user instructions.		PASS
3.1.4.1	Textiles shall not contain natural fibers, and shall be made of pure non-recycled synthetic material, having strength, aging, abrasion and heat resistance characteristics equivalent or superior to polyamide or polyester and shall be marked with any restrictions.		NA
3.1.4.2	Stitching/Cutting: If a subsystem uses stitching for connection of load bearing components it shall meet the following requirements: A) Use lock stitching B) Secure the end of threads by backstitching, overlapping stitching or other methods. C) Threads used for sewing shall be physically compatible with the webbing and of a quality comparable to that of the webbing. D) Hot-cut or fuse thermoplastic materials, cord, tape and webbing to prevent fraying. E) The tread color or shade shall contrast with that of the webbing to facilitate visual inspection.		NA
3.1.5.1	Other load bearing materials used in anchorage connectors shall meet the performance requirements of ANSI Z359.18-2017.		PASS
3.1.5.2	Integrally connected components to which another standard in the ANSI Z359 series exists shall meet the requirements of ANSI Z359.18-2017.		PASS

Date: September 18, 2019

SECTION (TEST)	REQUIREMENT	RESULTS			COMPLIANCE																
3.2.2.2/4.2.2.2.4	<p><b>Dynamic Strength (Type A Anchor) :</b></p> <p>A) Install anchorage connector, conditioned according the applicable requirements of 4.2.2.1.2 or 4.2.2.1.3 on the test anchorage in accordance with 4.1.2</p> <p>B) Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation.</p> <p>C) Connect the other end of the test lanyard to the test weight specified in 4.1.3</p> <p>D) Raise the test weight to achieve a free-fall distance of 3' (+0.1/-0).</p> <p>E) Release the test weight by means of quick release mechanism.</p> <p>F) Evaluate the test results per 3.2.2.1</p>				PASS																
	<table border="1"> <thead> <tr> <th data-bbox="380 842 789 898">Dynamic Strength Test</th> <th data-bbox="789 842 829 898">SAMPLE: 1</th> <th data-bbox="829 842 964 898">SAMPLE: 2</th> <th data-bbox="964 842 1240 898">SAMPLE: 3</th> </tr> </thead> <tbody> <tr> <td data-bbox="380 898 789 961">Anchorage connector successfully arrest the test weight?</td> <td data-bbox="789 898 829 961">YES</td> <td data-bbox="829 898 964 961">YES</td> <td data-bbox="964 898 1240 961">YES</td> </tr> <tr> <td data-bbox="380 961 789 1052">If deformation occurred did it create more than 1/8" (3mm) between gate and body?</td> <td data-bbox="789 961 829 1052">N/A</td> <td data-bbox="829 961 964 1052">N/A</td> <td data-bbox="964 961 1240 1052">N/A</td> </tr> <tr> <td data-bbox="380 1052 789 1121">MAF (Ref Only) Lbs.</td> <td data-bbox="789 1052 829 1121">3247</td> <td data-bbox="829 1052 964 1121">3044</td> <td data-bbox="964 1052 1240 1121">3168</td> </tr> </tbody> </table>	Dynamic Strength Test	SAMPLE: 1	SAMPLE: 2		SAMPLE: 3	Anchorage connector successfully arrest the test weight?	YES	YES	YES	If deformation occurred did it create more than 1/8" (3mm) between gate and body?	N/A	N/A	N/A	MAF (Ref Only) Lbs.	3247	3044	3168			
	Dynamic Strength Test	SAMPLE: 1	SAMPLE: 2	SAMPLE: 3																	
	Anchorage connector successfully arrest the test weight?	YES	YES	YES																	
	If deformation occurred did it create more than 1/8" (3mm) between gate and body?	N/A	N/A	N/A																	
MAF (Ref Only) Lbs.	3247	3044	3168																		
Anchorage connector successfully arrest the test weight?	YES	YES	YES																		
If deformation occurred did it create more than 1/8" (3mm) between gate and body?	N/A	N/A	N/A																		
MAF (Ref Only) Lbs.	3247	3044	3168																		
<p><b>Note:</b> Choked Orientation around I-Beam</p>																					

Date: September 18, 2019

SECTION (TEST)	REQUIREMENT	RESULTS			COMPLIANCE				
3.2.3.1/4.2.3.2	<p><b>Residual Dynamic Strength Test:</b></p> <ol style="list-style-type: none"> <li><b>1. Repetition of the test specified in 4.2.2.1 using same anchorage connector without further conditioning and the same test lanyard used in first test.</b></li> <li><b>2. Must support the test weight an additional minute after the residual dynamic drop.</b></li> <li><b>3. Evaluate the test results per 3.2.3.1</b></li> </ol>				<b>PASS</b>				
	<table border="1"> <thead> <tr> <th data-bbox="380 533 829 594">Residual Dynamic Strength</th> <th data-bbox="829 533 964 594">SAMPLE: 1</th> <th data-bbox="964 533 1099 594">SAMPLE: 2</th> <th data-bbox="1099 533 1240 594">SAMPLE: 3</th> </tr> </thead> </table>	Residual Dynamic Strength	SAMPLE: 1	SAMPLE: 2		SAMPLE: 3			
	Residual Dynamic Strength	SAMPLE: 1	SAMPLE: 2	SAMPLE: 3					
	Anchorage connector successfully arrest the test weight?	YES	YES	YES					
	Maintain the test weight for a period of at least 1 minute?	YES	YES	YES					
If deformation occurred did it create more than 1/8" (3mm) between gate and body?	N/A	N/A	N/A						



SECTION (TEST)	REQUIREMENT	RESULTS	COMPLIANCE												
3.2.1.1/4.2.1.2	<p><b>Static Strength Test for Type A Anchorage Connectors:</b></p> <p>A) <u>A new anchorage connector may be used for each test.</u></p> <p>B) <u>Test force shall be 5,000 pounds (+50/-0)</u></p> <p>C) <u>Install anchorage connector on the test anchorage in accordance with requirements of 4.1.2.</u></p> <p>D) <u>Apply load to the anchorage connector in the direction(s) of loading specified in 4.1.2.5.</u></p> <p>E) <u>Apply load at no greater than 2"/min and maintain 5,000 pound test load for at least 3 minutes.</u></p> <p>F) <u>Release load</u></p> <p>G) <u>Evaluate the test results per 3.2.1.1</u></p>	<table border="1"> <thead> <tr> <th data-bbox="396 814 763 848">Static Strength Requirements</th> <th data-bbox="763 814 909 848">SAMPLE 3</th> <th data-bbox="909 814 1052 848">SAMPLE 4</th> <th data-bbox="1052 814 1224 848">SAMPLE 5</th> </tr> </thead> <tbody> <tr> <td data-bbox="396 848 763 882">Anchorage resist the test load?</td> <td data-bbox="763 848 909 882">YES</td> <td data-bbox="909 848 1052 882">YES</td> <td data-bbox="1052 848 1224 882">YES</td> </tr> <tr> <td data-bbox="396 882 763 978">If deformation occurred did it create more than 1/8" (3mm) between gate and body?</td> <td data-bbox="763 882 909 978">NA</td> <td data-bbox="909 882 1052 978">NA</td> <td data-bbox="1052 882 1224 978">NA</td> </tr> </tbody> </table>	Static Strength Requirements	SAMPLE 3	SAMPLE 4	SAMPLE 5	Anchorage resist the test load?	YES	YES	YES	If deformation occurred did it create more than 1/8" (3mm) between gate and body?	NA	NA	NA	PASS
Static Strength Requirements	SAMPLE 3	SAMPLE 4	SAMPLE 5												
Anchorage resist the test load?	YES	YES	YES												
If deformation occurred did it create more than 1/8" (3mm) between gate and body?	NA	NA	NA												
3.2.1.1/4.2.4.2	<p><b>Serviceability Load for Type A Anchorage Connectors:</b></p> <p><u>A new anchorage connector may be used for each test.</u></p> <p><u>Test force shall be greater than twice the work load or 2,500 pounds (Whichever is Greater)</u></p> <p><u>Install anchorage connector on the test anchorage in accordance with requirements of 4.1.2.</u></p> <p><u>Apply load at no greater than 90lbs/min and maintain load for at least 3 minutes.</u></p> <p><u>Release load</u></p> <p><u>Evaluate the test results per 3.2.4.2</u></p>	<table border="1"> <thead> <tr> <th data-bbox="396 1570 763 1604">Static Strength Requirements</th> <th data-bbox="763 1570 909 1604">SAMPLE 3</th> <th data-bbox="909 1570 1052 1604">SAMPLE 4</th> <th data-bbox="1052 1570 1224 1604">SAMPLE 5</th> </tr> </thead> <tbody> <tr> <td data-bbox="396 1604 763 1638">Anchorage resist the test load?</td> <td data-bbox="763 1604 909 1638">YES</td> <td data-bbox="909 1604 1052 1638">YES</td> <td data-bbox="1052 1604 1224 1638">YES</td> </tr> <tr> <td data-bbox="396 1638 763 1705">Cracking/Breaking or Deformation</td> <td data-bbox="763 1638 909 1705">NO</td> <td data-bbox="909 1638 1052 1705">NO</td> <td data-bbox="1052 1638 1224 1705">NO</td> </tr> </tbody> </table>	Static Strength Requirements	SAMPLE 3	SAMPLE 4	SAMPLE 5	Anchorage resist the test load?	YES	YES	YES	Cracking/Breaking or Deformation	NO	NO	NO	PASS
Static Strength Requirements	SAMPLE 3	SAMPLE 4	SAMPLE 5												
Anchorage resist the test load?	YES	YES	YES												
Cracking/Breaking or Deformation	NO	NO	NO												

SECTION (TEST)	REQUIREMENT	COMPLIANCE
5	Marking and Instruction Requirements	PASS
5.1.1	The following marking shall appear in English on the label, marking or tag that is designed to last for the lifetime of the anchorage connector and is permanently affixed to the anchorage connector: A) The manufacture’s name or mark	PASS
	B) The year of manufacture	PASS
	C) Model number	PASS
	D) “ANSI Z359.18 and the type	PASS
	E) Marking to indicate restrictions on directions of loading, if applicable	PASS
	F) Where specified by the manufacturer, the working load.	PASS
	G) An individual serial number or a lot or batch number that provides traceability	PASS
	H) Minimum breaking strength followed by “MBS”	PASS
5.1.2	As required for the specific anchorage connector, the following marking shall appear in English on a label, marking or tag that is designed to last for the lifetime of the anchorage connector and is permanently affixed to the anchorage connector.	PASS
5.1.2.1	Anchorage connector that incorporates a closed loop not intended for connection, but may be mistake for a connection point shall be permanently labeled with a warning not to connect a fall protection system or suspended component to the closed loop when used in a cinching application.	PASS
5.1.2.2	For type D anchorage connectors only, any information that is needed for clearances calculations and anchorage strength identification	NA
5.1.2.3	The minimum service temperature the anchorage connector according to 3.1.3.2	PASS
5.1.2.4	For tripods and davit systems, the maximum number of users permitted on the system.	NA
5.2	Instruction Requirements	PASS
5.2.1	Instruction and information shall be provided in English with each anchorage connector.	PASS

SECTION (TEST)	REQUIREMENT	COMPLIANCE
5.2.1.1	<p>Overall:</p> <ul style="list-style-type: none"> <li>A) A statement that the anchorage connector has been tested in compliance with the requirements of ANSI/ASSE Z359.7, and caution that the ANSI compliance and testing covers only the hardware and does not extend to the anchorage and substrate w=to which the anchorage connector is attached.</li> <li>B) Specifications for appropriate anchorage(s) to which the anchorage connector can be attached, including instructions on how to proceed when the user is unable to determine whether the anchorage meets the manufactures specification and instructions that the anchorage connector shall only be connected to anchorages that:                             <ul style="list-style-type: none"> <li>i) Can withstand 5,000 pounds without failure, except that lower strengths are acceptable when permitted by applicable legislation</li> <li>ii) Are certified by a professional engineer as having the required strength for fall arrest or travel restraint, as applicable</li> <li>iii) The manufacturer may provide specifications of allowable materials including the minim shapes, sizes and geometry of structural elements to which the anchors connector may be fastened</li> </ul> </li> <li>C) The manufacturer shall clearly label the minimum service temperature for the anchorage connector according to 3.1.3.2.</li> <li>D) The manufacturer shall supply complete specifications for fasteners</li> <li>E) The anchorage connector type</li> </ul>	<p><b>PASS</b></p>

SECTION (TEST)	REQUIREMENT	COMPLIANCE
5.2.1.1	<p>Overall:</p> <ul style="list-style-type: none"> <li>F) The permitted uses of the anchorage connector</li> <li>G) The connection point(s), working load limit</li> <li>H) The material used in the anchorage connectors construction</li> <li>I) The length of the anchorage connector and any other dimensions that may affect its compatibility with anchorages to which it may be connected.</li> <li>J) The manufacturer shall make available upon request information for the design of systems, such as AAF and/or force vs. displacement curve(s) for the device.</li> <li>K) A statement that only one fall protection system or positioning system may be attached to an individual connection point</li> <li>L) Specification providing the intended direction(s) of loading of the anchorage connector</li> <li>M) A complete list of the anchorage connector components provided by the manufacturer at the time of sale</li> <li>N) A warning against unauthorized alterations, relocations or additions to the anchorage connector</li> </ul>	<p><b>PASS</b></p>
5.2.1.2	<p>Use:</p> <ul style="list-style-type: none"> <li>A) Instructions on proper installation and use, including, but not limited to, compatibility with other fall protection components</li> <li>B) The length of the anchorage connector and any other dimensions that may affect its compatibility with anchorages to which it may be connected</li> <li>C) Where applicable, directions regarding the appropriate length of lanyard to use with the anchorage connector to compensate for the additional length that it may add to the lanyard. (Instructions to include the length of anchorage connector, manner of use and location relative to working surface in the calculation of fall clearance).</li> <li>D) Permitted and forbidden uses, including clear description of and the recommended ways of dealing with the applicable compatibility concerns</li> <li>E) A warning to remove any surface contamination such as concrete, stucco, roofing material, etc., that could accelerate the cutting or abrading of attached components</li> <li>F) Warnings concerning environments and conditions that may degrade the anchorage connector</li> <li>G) Training requirements</li> </ul>	<p><b>PASS</b></p>

SECTION (TEST)	REQUIREMENT	COMPLIANCE
5.2.1.3	<p>Inspection and Field Testing:</p> <ul style="list-style-type: none"> <li>A) Instructions on testing, if needed</li> <li>B) Where applicable, directions for the installer to perform and document proof testing upon installation. Directions shall include proof load forces and acceptable methods</li> <li>C) Field serviceability testing: The manufacturer shall provide guidelines for how often field load testing must be undertaken to prove that the anchorage connector continues to be adequately secured to the structure. These guidelines shall include recommended methods for testing, including the direction and point of application of test loads</li> <li>D) The recommended frequencies and procedures for inspection, maintenance, and when applicable, testing</li> <li>E) Instructions for inspecting and servicing an anchorage connector after it is subjected to a fall or an inspection reveals an unsafe condition</li> <li>F) If applicable, guidelines for the retirement of the anchorage connector</li> <li>G) The action to be taken if an inspection of the anchorage connector reveals an unsafe condition</li> <li>H) The action to be taken after the anchorage connector is subjected to a fall</li> <li>I) Criteria for removal of an anchorage connector from service if deformed from its original installed configuration</li> </ul>	<p><b>PASS</b></p>
5.2.1.4	<p>Clinching and Non-Clinching Style Anchorage Connectors:</p> <ul style="list-style-type: none"> <li>A) Where the anchorage connector includes an abrasion pad, provide directions that the abrasion pad shall be installed between the anchorage and the lead bearing loop</li> <li>B) The proper method of installing the anchorage connector including, as applicable for non-clinching anchorage connectors. The maximum angle permitted between the connection legs</li> </ul>	<p><b>PASS</b></p>

**SECTION 4**  
**PHOTOGRAPHS**



Date: September 18, 2019

**SECTION 5**

**REVISION HISTORY**

<b>REPORT NUMBER</b>	<b>DATE OF REVISION</b>	<b>DESCRIPTION OF CHANGE:</b>	<b>PROJECT OWNER</b>	<b>REVIEWED BY</b>
104078489CRT-001	9/13/19	Original Report	Matthew Stevens	Andrew Rulison