

## Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

Declaration #: DOC-UFL204111

Declaration Date: 08/13/2019

Item #: UFL204111

**Description:** KStrong® 6 ft. Internal design shock absorbing lanyard with snap hook and rebar hook (ANSI)

**Brand Name:** KStrong

**Manufacturer:** KStrong

**Address:** 150 N. Radnor Chester Road, Suite F200, Radnor, PA 19087

**Additional Items Conforming  
Under this Declaration (If Applicable):**

KStrong declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

### ANSI Z359.13-2013

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014



**Level 1:**

KStrong Lab Outside the Scope of ISO/IEC Standard 17025:2017



**Level 2:**

KStrong Lab Within the Scope of ISO/IEC Standard 17025:2017




**Level 3:**

Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017

**Supporting Documentation:** KS-Test-UFL204111.pdf

This Certificate is a guarantee that the above standard(s) was met by the requirements of such standard. Testing was performed under normal operation mode. The results of testing apply only to the particular sample tested and the specific test carried out. This Certificate is only issued for products which have passed the testing requirements of listed standard(s).

**Authorized Signature:**



John H. Kemp Jr.  
President - KStrong

ISO 17025 Accredited Test Laboratory



**INSPEC Technical Services  
(Kunshan) Co Ltd**  
8 Jin Yang East Road,  
Lu Jia Zhen Kunshan, Jiangsu, China  
Tel: +86 (512) 5011 2646  
email: testing@inspec.asia  
www.inspec-international.com



Accrediting Agency

**ANSI National Accreditation Board**  
1899 L Street NW,  
Suite 1100-A  
Washington, DC 20036  
Tel: 414-501-5494  
anab@anab.org



INSPEC Technical Services (Kunshan) Co Ltd • 8 Jin Yang East Road • Lu Jia Zhen • Kunshan • Jiangsu • China  
Email: [testing@inspec.asia](mailto:testing@inspec.asia) Website: [www.inspec-international.com](http://www.inspec-international.com)  
Tel: +86 (512) 5011 2646 Fax: +86 (512) 5011 2656

# Test Report

## Personal Fall Arrest Equipment ANSI Z359.13-2013 Energy Absorbing Lanyards

**Report no:** 2.19.08.09

**Client:** KSTRONG LLC  
17330 Preston Road  
#200 D Dallas  
TX 7525  
U.S.A

**Manufacturer:** KSTRONG LLC

**Client orders:** T/0289 (15 March 2016)  
T/0609 (22 July 2019)

**Model:** UFL204111

**Dates of tests:** 12 April 2016 to 18 May 2016, and 9 August 2019

**Signed:**

Steven Sum, Laboratory Manager

**Issued:** 13 August 2019

Page 1 of 14

### **Conditions**

This report may be reproduced and distributed to your clients, provided that it is reproduced and distributed in full.

Specimens will be disposed of four weeks from the date of this report, unless otherwise instructed.

Opinions, comments and interpretations expressed in this report are shown in italics.

Copies of INSPEC interpretations referenced in this report are available upon request.

Tests marked ☒ are not included in our ANAB Scope of Accreditation.

This report has been provided in accordance with our standard Terms of Business, which can be viewed at, and printed from:

<http://inspec-international.com/ToB.pdf>

If you have difficulty accessing the Terms of Business, you may contact us for a copy.

**Summary of assessment\***

Clause	Requirement	Assessment (See Key)
3.1.6	Activation force	Pass
3.2	Energy absorber	Ltd
3.2.1	Material	NAs
3.2.2	Terminations	Ltd
3.2.3	Connectors	NAs
3.2.4	Dynamic performance – ambient dry	Pass
3.2.5	Dynamic performance – ambient wet	Pass
	Dynamic performance – cold dry	Pass
	Dynamic performance – hot dry	Pass
3.2.6	Static strength	Pass
3.2.7	Static test for wrap-around lanyards (3600 lbf – abraded)	
3.2.8	Static test for wrap-around lanyards (5000 lbf – unabraded)	
3.2.9	Static test for Y-lanyards	
3.2.10.1	Dynamic test for Y-lanyards (Single connection)	
3.2.10.2	Dynamic test for Y-lanyards (Dual connection)	
3.2.10.3	Dynamic test for Y-lanyards (Hip connection)	
5.1 / 5.2	Marking	Ltd
5.3 / 5.4	Instructions	Ltd

**Key**

	Shading shows the clauses requested. Any other clauses were not requested.
Pass	Requirement satisfied.
Ltd	Testing requested was insufficient completely to verify compliance with the clause. Refer to the “Result details” section for more information.
Fail	Requirement not satisfied. Refer to the “Result details” section for more information.
NAs	Assessment not carried out.
NAp	Requirement not applicable.
NT	Requested but not tested due to early termination following failure.

\* Assessment relates only to those specimens which were tested and are the subject of this report.

**Submission details**

Product	Quantity	Date received	INSPEC specimen no.
Energy absorbing lanyard, model UFL204111	01	8 April 2016	2D04901
Energy absorbing lanyard, model UFL204101	16		2D04701 to 2D04716

**Procedures**

The specimens detailed within the submissions above were used for the tests covered by this report.

Testing was performed in accordance with ANSI Z359.13-2013 unless otherwise specified below. Reference should be made to the standard when reading this report.

Unless stated otherwise, specimens were tested in the condition as received by INSPEC.

Testing was performed at INSPEC's laboratory in Kunshan, China.

5        Labels and Instructions were supplied electronically and used for assessment.

The manufacturer declared:

- 1) Energy absorbing lanyard UFL204101 and UFL204111 are of the same family of products. The design, materials and construction are the same except different connectors were used.

Energy absorbing lanyard, model UFL204101 was first tested and reported in Inspec Test Report 2.19.08.08. All performance test results are shared in this test report.

**Result details****3.2 Personal Energy Absorbing Lanyard Component**

Specimen 2D04901 was assessed.

The specimen had an energy absorbing ability that satisfied the design and testing requirements of this standard.

Ltd

**3.1.6 Activation force**

Specimens 2D04713, 2D04714 and 2D04715 were assessed.

The specimens showed no sign of activation when subjected to the 450 pounds static force.

Pass

The permanent elongation of the specimen 2D04713, following the test, was 0.79 inches. This is less than the maximum 2 inches permitted.

Pass

The permanent elongation of the specimen 2D04714, following the test, was 0.79 inches. This is less than the maximum 2 inches permitted.

Pass

The permanent elongation of the specimen 2D04715, following the test, was 0.59 inches. This is less than the maximum 2 inches permitted.

Pass

**3.2.1 Materials**

Specimen 2D04901 was assessed.

Webbing was used on the construction of the energy absorbing lanyard.

The materials used in the construction of this energy absorbing lanyard, and their characteristics, were not assessed. Manufacturer to certify.

NAs

**3.2.2 Terminations**

Specimen 2D04901 was assessed.

The energy absorbing lanyard was constructed of webbing.

The end terminations satisfied 3.2.2.2, as appropriate (see below).

Ltd

**3.2.2.2 Webbing terminations**

Specimen 2D04901 was assessed.

- |    |  |      |
|----|--|------|
| a) | Lock stitches sewn on all stitched eye termination straps were not assessed. Manufacturer to certify.              | NAs  |
| b) | The material and characteristics of thread used was not assessed. Manufacturer to certify.                         | NAs  |
|    | Threads used for sewing the webbing were white colour. This contrasted with the red / black colour of the webbing. | Pass |
| c) | The webbing was protected at load-bearing connector elements.  | Pass |
| e) | The ends of the webbing were hot cut so as to prevent unravelling.   | Pass |

**3.2.3 Connectors**

Specimen 2D04901 was assessed.

It incorporated two integrally attached connectors.

Testing of the connectors was not requested.	NAs
--	-----

**3.2.4 Dynamic performance test – Ambient dry condition (average arrest force)**

Specimens 2D04701 to 2D04703 were assessed.

During the dynamic performance tests, the average arrest force of the specimens were recorded as follows:

Specimen 2D04701 was 825 pounds.	Pass
Specimen 2D04702 was 824 pounds.	Pass
Specimen 2D04703 was 823 pounds.	Pass

These values are less than the maximum 900 pounds permitted.  
See Annex 1 for the plot of force versus time.

**3.2.4 Dynamic performance test – Ambient dry condition (maximum arrest force)**

Specimens 2D04701 to 2D04703 were assessed.

During the dynamic performance tests, the maximum arrest force of the specimens were recorded as follows:

Specimen 2D04701 was 892 pounds.	Pass
Specimen 2D04702 was 885 pounds.	Pass
Specimen 2D04703 was 883 pounds.	Pass

These values are less than the maximum 1,800 pounds permitted.  
See Annex 1 for the plot of force versus time.

**3.2.4 Dynamic performance test – Ambient dry condition (deployment distance)**

Specimens 2D04701 to 2D04703 were assessed.

During the dynamic performance tests, the deployment distance of the specimens were recorded as follows:

Specimen 2D04701 was 34.6 inches.	Pass
Specimen 2D04702 was 34.1 inches.	Pass
Specimen 2D04703 was 34.4 inches.	Pass

These values are less than the maximum 48 inches permitted.

**3.2.5 Dynamic performance test - Ambient wet condition (average arrest force)**

Specimens 2D04704 to 2D04706 were assessed.

During the dynamic performance tests, the average arrest force of the specimens were recorded as follows:

Specimen 2D04704 was 820 pounds.	Pass
Specimen 2D04705 was 834 pounds.	Pass
Specimen 2D04706 was 828 pounds.	Pass

These values are less than the maximum 1,125 pounds permitted.  
See Annex 1 for the plot of force versus time.

**3.2.5 Dynamic performance test - Ambient wet condition (maximum arrest force)**

Specimens 2D04704 to 2D04706 were assessed.

During the dynamic performance tests, the maximum arrest force of the specimens were recorded as follows:

Specimen 2D04704 was 881 pounds.	Pass
Specimen 2D04705 was 887 pounds.	Pass
Specimen 2D04706 was 883 pounds.	Pass

These values are less than the maximum 1,800 pounds permitted.  
See Annex 1 for the plot of force versus time.

**3.2.5 Dynamic performance test - Ambient wet condition (deployment distance)**

Specimens 2D04704 to 2D04706 were assessed.

During the dynamic performance tests, the deployment distance of the specimens were recorded as follows:

Specimen 2D04701 was 34.4 inches.	Pass
Specimen 2D04702 was 32.7 inches.	Pass
Specimen 2D04703 was 32.9 inches.	Pass

These values are less than the maximum 48 inches permitted.



**3.2.5 Dynamic performance test - Cold dry condition (average arrest force)**

Specimens 2D04707 to 2D04709 were assessed.

During the dynamic performance tests, the average arrest force of the specimens were recorded as follows:

Specimen 2D04707 was 923 pounds.

Pass

Specimen 2D04708 was 933 pounds.

Pass

Specimen 2D04709 was 952 pounds.

Pass

These values are less than the maximum 1,125 pounds permitted.

See Annex 1 for the plot of force versus time.

**3.2.5 Dynamic performance test - Cold dry condition (maximum arrest force)**

Specimens 2D04707 to 2D04709 were assessed.

During the dynamic performance tests, the maximum arrest force of the specimens were recorded as follows:

Specimen 2D04707 was 1021 pounds.

Pass

Specimen 2D04708 was 1030 pounds.

Pass

Specimen 2D04709 was 1056 pounds.

Pass

These values are less than the maximum 1,800 pounds permitted.

See Annex 1 for the plot of force versus time.

**3.2.5 Dynamic performance test - Cold dry condition (deployment distance)**

Specimens 2D04707 to 2D04709 were assessed.

During the dynamic performance tests, the deployment distance of the specimens were recorded as follows:

Specimen 2D04707 was 26.8 inches.

Pass

Specimen 2D04708 was 26.0 inches.

Pass

Specimen 2D04709 was 25.8 inches.

Pass

These values are less than the maximum 48 inches permitted.

**3.2.5 Dynamic performance test - Hot dry condition (average arrest force)**

Specimens 2D04710 to 2D04712 were assessed.

During the dynamic performance tests, the average arrest force of the specimens were recorded as follows:

Specimen 2D04710 was 779 pounds.

Pass

Specimen 2D04711 was 785 pounds.

Pass

Specimen 2D04712 was 775 pounds.

Pass

These values are less than the maximum 1,125 pounds permitted.

See Annex 1 for the plot of force versus time.

**3.2.5 Dynamic performance test - Hot dry condition (maximum arrest force)**

Specimens 2D04710 to 2D04712 were assessed.

During the dynamic performance tests, the maximum arrest force of the specimens were recorded as follows:

Specimen 2D04710 was 839 pounds.

Pass

Specimen 2D04711 was 839 pounds.

Pass

Specimen 2D04712 was 843 pounds.

Pass

These values are less than the maximum 1,800 pounds permitted.

See Annex 1 for the plot of force versus time.

**3.2.5 Dynamic performance test - Hot dry condition (deployment distance)**

Specimens 2D04710 to 2D04712 were assessed.

During the dynamic performance tests, the deployment distance of the specimens were recorded as follows:

Specimen 2D04710 was 37.0 inches.

Pass

Specimen 2D04711 was 37.2 inches.

Pass

Specimen 2D04712 was 37.8 inches.

Pass

These values are less than the maximum 48 inches permitted.

**3.2.6 Static strength**

Specimens 2D04701 to 2D04703 were assessed.

The specimens withstood the tensile test of 5,000 pounds applied for 1 minute without breaking respectively.

Pass

## 5 Marking and Reference Literature

### 5.1 General Marking Requirements

5.1.1	Markings shall be in English.	Pass
5.1.2	The legibility and attachment of required markings shall endure for the life of the component, subsystem or system being marked was not assessed. <i>Labels were supplied electronically and used for assessment.</i>	NAs
	When pressure sensitive labels are used, they shall comply with the applicable provision of reference 8.5.1. This requirement was not assessed. Manufacturer to certify.	NAs
5.1.3	Equipment shall be marked with the following:	
	· part number and model designation; [UFL204111]	Pass
	· year of manufacture;	Pass
	· manufacturer's name or logo; [KSTRONG]	Pass
	· capacity rating; [130-310 lbs]	Pass
	· serial number;	Pass
	· standard number; [ANSI Z359.13]	Pass
	· warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer.	Pass

### 5.2 Specific Marking Requirements

5.2.1	Energy absorbing lanyards shall be marked to identify:	
	· the fiber used in the material of construction; [Polyester; Nylon; Steel]	Pass
	· the length; [6 FT]	Pass
	· the need to avoid contact with sharp edges and abrasive surfaces;	Pass
	· the need to make only compatible connections;	Pass
	· the maximum elongation; [48" ]	Pass
	· restriction, if any, on the types of components, subsystems, or systems with which the energy absorber is designed to be used;	Pass
	· the average arrest force, maximum free fall distance and capacity of the energy absorber on a separate label identical in size, color and content as figure 16a and 16b of the standard; [size and color of the label was not assessed]	Ltd
	· 6 ft FF personal energy absorbers shall be in black print on a contrasting white background;	NAs
	· 12 ft FF personal energy absorbers shall be in white print on a contrasting black background;;	NAp
5.2.2	· In addition to 5.2.1, Y-lanyards that fail the Dynamic Hip Test detailed in 3.2.10, must include a warning label on both connecting ends of the lanyard specifically directing users how to safely store the unused leg of the lanyard.	NAp

### 5.3 General Instruction Requirements

The instructions to users have been assessed as detail below, with reference only to the relevant requirements of the Standard.

INSPEC Technical Services has not assessed these instructions with respect to claims made by the manufacturer outside of these requirements, and therefore accepts no responsibility for the legitimacy of any such claims.

- |              |   |     |
|--------------|---|-----|
| <b>5.3.1</b> | Instructions shall be provided to the user, printed in English, and affixed to the equipment at the time of shipment from the manufacturer. | NAs |
|--------------|---|-----|

*However, instructions provided electronically, in English, were used for assessment.*

- |              |   |      |
|--------------|---|------|
| <b>5.3.2</b> | Instructions shall contain the following information:   |      |
|              | · a statement that the manufacturer's instructions shall be provided to users;  | Pass |
|              | · manufacturer's name, address, and telephone number;   | Pass |
|              | · manufacturer's part number and model designation for the equipment;   | Pass |
|              | · intended use and purpose of the equipment;  | Pass |
|              | · proper method of use and limitation on use of the equipment;  | Pass |
|              | · illustrations showing locations of markings on the equipment;   | Pass |
|              | · reproduction of printed information on all markings;  | Pass |
|              | · inspection procedures required to assure the equipment is in serviceable condition and operating correctly;   | Pass |
|              | · anchorage requirements;   | Pass |
|              | · an illustration of how to calculate free fall distances;  | Pass |
|              | · criteria for discarding equipment which fails inspection;   | Pass |
|              | · procedures for cleaning, maintenance, and storage;  | Pass |
|              | · reference to the ANSI/ASSE Z359.13, <i>Personal Energy Absorbers and Energy Absorbing Lanyards</i> , standard and applicable regulations governing occupational safety. | Pass |
| <b>5.3.3</b> | Instructions shall require that only the equipment manufacturer, or persons or entities authorized in writing by the manufacturer, shall make repairs to equipment.       | Pass |
| <b>5.3.4</b> | Instructions shall require the user to remove equipment from field service if it has been subjected to the forces of arresting a fall.                                    | Pass |

## 5.4 Specific Instruction Requirements

<b>5.4.1</b>	In addition to general instruction requirements, written instructions for personal energy absorbers shall include:	
	· the material used in the personal energy absorber construction;	Pass
	· the need to make only compatible connections and limitations of compatibility;	Pass
	· proper method of coupling the personal energy absorber to adjacent components of the system;	Pass
	· the maximum arrest force of the personal energy absorber when dynamically tested in accordance with the requirements of this standard;	Pass
	· the maximum elongation of the personal energy absorber when dynamically tested in accordance with the requirements of this standard.	Pass
	· a reference chart that indicates the deployment distance of the personal energy absorber according to the user weight and free fall distance;	Pass
	· a statement that indicates information necessary in designing fall protection systems shall be made available from the manufacturer.	Pass
	· Manufacturers may provide designers of fall protection systems a representative graph(s) of the time history plot of the loading from a drop test.	NAs

**Estimates of the uncertainty of measurement**

Clause	Test		Uncertainty
3.1.6	Activation force		See Note 1
	Permanent elongation		$\pm 0.33\%$
3.2	Personal Energy Absorber Component, if fitted		See report
3.2.1	Materials		-
3.2.2	Terminations		-
3.2.3	Connectors		See report
3.2.4	Dynamic performance – ambient dry	Force	$\pm 1.2\%$
		Deployment distance	$\pm 1\text{mm}$
3.2.5	Dynamic performance – various conditions	Force	$\pm 1.2\%$
		Deployment distance	$\pm 1\text{mm}$
3.2.6	Static strength – single lanyard		See Note 1
	Static strength – slippage		$\pm 2.1\%$
3.2.7	Abrasion and Static strength - Wrap-around energy absorbing lanyards only		See Note 1
3.2.8	Static strength - Wrap-around energy absorbing lanyards only		See Note 1
3.2.9	Static strength - Y-lanyards only		See Note 1
3.2.10.1	Dynamic test, Y-lanyards only - Single connection	Force	$\pm 1.2\%$
		Deployment distance	$\pm 1\text{mm}$
3.2.10.2	Dynamic test, Y-lanyards only - Dual connection	Force	$\pm 1.2\%$
3.2.10.3	Dynamic test, Y-lanyards only - Hip connection		See Note 1
5.1 / 5.2	Marking		-
5.3 / 5.4	Information		-

Note 1. The acceptance criterion for this test is a straightforward “Pass/Fail”, rather than a numerical value. Consequently, as there is no value to be reported, uncertainty has not been reported either.

Note 2. The uncertainty value is based on a standard uncertainty multiplied by a coverage factor  $k = 2$ , which provides for a confidence level of approximately 95%. Values expressed as a percentage (%) are relative.


Note 3. It should be noted that the above values have not been taken into account when making assessments against the pass/fail criteria.

# ANNEX

This Annex comprises two sections.

1. Plots of arrest force versus time. (12 pages)
2. Photograph of the product tested. (1 page)


Technician:	Tan
Standard	ANSI Z359.13:2013 Energy absorbing lanyard
Sample / File name:	2D04701
Drop item	Drop weight, US - 128kg
Orientation/Attachment Point:	Centre eyebolt
Time and Date of Test:	13:46 21/04/16





INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04702  
Drop item Drop weight, US - 128kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 13:56 21/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

# INSPEC Technical Services


Technician: Tan  
Standard: ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04703  
Drop item: Drop weight, US - 128kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 14:05 21/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04704  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:49 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04705  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:56 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04706  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 17:02 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04707  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:22 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04708  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:32 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services

Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04709  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:38 22/04/16




Results do not achieve full ANAB status until a formal test report has been issued.



INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04710  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 15:54 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services


Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04711  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:05 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

INSPEC Technical Services

Technician: Tan  
Standard ANSI Z359.13:2013 Energy absorbing lanyard  
Sample / File name: 2D04712  
Drop item Drop weight, US - 128 kg  
Orientation/Attachment Point: Centre eyebolt  
Time and Date of Test: 16:15 22/04/16



Results do not achieve full ANAB status until a formal test report has been issued.

KSTRONG LLC – Energy absorbing lanyard,  
model UFL204111

