

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

Declaration #: DOC-UFS310020

Declaration Date: 12/08/2023

Item #: UFS310020

Description: KStrong® BRUTE™ 20 ft. Galvanized Steel Cable SRL with swivel snap hook.
Includes installation carabiner and tagline (ANSI)

Brand Name: KStrong

Manufacturer: KStrong

Address: 150 N. Radnor Chester Road, Suite F200, Radnor, PA 19087

**Additional Items Conforming
Under this Declaration (If Applicable):**

KStrong declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

ANSI Z359.14-2021 Class 1

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014



Level 1:

KStrong Lab Outside the Scope of ISO/IEC Standard 17025:2017



Level 2:

KStrong Lab Within the Scope of ISO/IEC Standard 17025:2017



Level 3:

Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017

Supporting Documentation: KS-Test-UFS310020.pdf

This Certificate is a guarantee that the above standard(s) was met by the requirements of such standard. Testing was performed under normal operation mode. The results of testing apply only to the particular sample tested and the specific test carried out. This Certificate is only issued for products which have passed the testing requirements of listed standard(s).

Authorized Signature:



John H. Kemp Jr.
President - KStrong

ISO 17025 Accredited Test Laboratory

intertek
Total Quality. Assured.



Intertek Testing Services NA, Inc.
3933 US Rt. 11
Cortland, NY 13045
Tel: 1 607-753-6711
www.intertek.com

Accrediting Agency



A2LA
5202 Presidents Court, Ste 220
Frederick, MD 21703
Tel: 301.644.3248
info@A2LA.org

Test Verification of Conformity

Verification Number: 105663091CRT-002

On the basis of the referenced test report(s), sample(s) of the below product have been found to comply with the harmonized standards and Directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it(them).

Applicant Name & Address: KStrong INC
150 N. Radnor Chester Rd.
Suite F200
Radnor, PA 19087
USA

Product Description: Self-Retracting Device

Models/Type References: UFS310010, UFS310020, UFS310030, UFS310050, UFS310100, UFS310150,
UFS310130, UFS330008, UFS480020, UFS480030, UFS480050, UFS310020(SS),
UFS310030(SS), UFS310050(SS), UFS310090, UFS310025(SS), UFS310018(SS)

Brand Name: KStrong INC

Relevant Standards: ANSI/ASSP Z359.14-2021

Verification Issuing Office Name & Address: Intertek Testing Services NA, Inc.
3933 US Rt-11
Cortland, NY 13045
USA

Date of Tests: 03/17/22 – 03/22/22

Test Report Number(s): 105663091CRT-001

Signature:



Name:
Position:
Date:

Matthew Stevens
Team Leader
12/08/2023



This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

KSTRONG INC.

TEST REPORT

SCOPE OF WORKs

ANSI/ASSP Z359.14-2021 – SELF RETRACTING DEVICES

REPORT NUMBER

105663091CRT-001

ORIGINAL REPORT NUMBER

105376372CRT-001

ISSUE DATE

December 8, 2023

PAGES

8

DOCUMENT CONTROL NUMBER

GFT-OP-10a (6-March-2017)

© 2017 INTERTEK





Total Quality. Assured.

Address
3933 US rt. 11 Cortland, NY
13045

TEST REPORT FOR KSTRONG INC.

Report No.: 105663091CRT-001
Date: December 8, 2023

Telephone: 607-758-6246
www.intertek.com

KSTRONG Inc. 150 N. Radnor Chester RD. Suite F200 Radnor, PA 19087 USA	
Report Number	105663091CRT-001
Signed Quote Number	Qu-01405542
PO Number	N/A
Name of Testing Laboratory Preparing the Report	
	Intertek Testing Services NA Inc.
Test Specification:	
Standard	ANSI/ASSP Z359.14-2021
Date(s) of Testing	3/14/22-3/22/22
Product Description:	
Product Type	Self-Retracting Device
Brand Name	KStrong
Model Number(s)	UFS310010, UFS310020, UFS310030, UFS310050, UFS310100, UFS310150, UFS310130, UFS330008, UFS480020, UFS480030, UFS480050, UFS310020(SS), UFS310030(SS), UFS310050(SS), UFS310090, UFS310025(SS), UFS310018(SS)
Model Share	N/A
Dates Samples Received:	3/4/2022

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Date: December 8, 2023

SECTION 1
SUMMARY OF TESTING

TESTS COMPLETED	TEST DATE	ANSI/ASSP Z359.14-2021 CLAUSE	STATUS
General Requirements	3/14/22	3.1	PASS
Markings and instructions/User inspection, Maintenance	3/17/22	5.1, 5.2/6	PASS
Static Strength Testing of SRD's	3/21/22	3.2.1/4.2.1	PASS
Dynamic Performance (ambient)	3/22/22	3.3/4.3.1	PASS

SECTION 2

This test report concludes the work anticipated in the testing phase of your project. If there are any questions regarding this report please contact the undersigned at 607-753-6711.

COMPLETED BY:	Alex Smith	REVIEWED BY:	Matthew Stevens
TITLE:	Technician	TITLE:	Team Leader
SIGNATURE:		SIGNATURE	
DATE	12/8/2023	DATE:	12/8/2023

Please see attached test data for details.

Date: December 8, 2023

SECTION 3

TESTING EQUIPMENT CALIBRATION INFORMATION

USED FOR TEST	DESCRIPTION	MANUFACTURER	CONTROL NO.	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE
X	Test Weight	NA	NA	310 lbs	-	VBU	VBU
X	Load Cell	PCB	N1392	-	-	7/22/21	7/22/22
X	Tape Measure	Stanley	H339	25'	-	5/10/21	5/10/22
X	Load Cell	Interface	L099	-	-	5/10/21	5/10/22

SECTION 4

Section (Test)	Requirement	Results	Compliance																																																																																																														
3	"Marking and Instructions"																																																																																																																
5.1.1	Shall be in English		PASS																																																																																																														
5.1.3	Self-Retracting Devices shall be marked with the following:		PASS																																																																																																														
	<table border="1"> <thead> <tr> <th>Marking</th> <th>Comments</th> <th>YES</th> <th>NO</th> <th>NA</th> </tr> </thead> <tbody> <tr> <td>Part number and model designation</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Year of manufacture</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Manufacturer's name or logo</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Capacity Range</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Unique ID Number</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Standard Number (Z359.14)</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>How to inspect the visual indicator</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning of the need for inspection in accordance with the manufacturer's instructions</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>The fiber or other materials used in the lanyard construction</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>The lanyard working length</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Average arresting force for the SRD class</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Arresting distance</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Proper installation means</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning on the need for testing the device for locking and retraction before each use</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>SRD class and arrest distance</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Free fall limit</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Suitability for use with horizontal lifelines</td> <td></td> <td></td> <td></td> <td>X</td> </tr> <tr> <td>Suitability for horizontal use</td> <td></td> <td></td> <td></td> <td>X</td> </tr> <tr> <td>Suitability for Leading Edge capability</td> <td></td> <td></td> <td></td> <td>x</td> </tr> </tbody> </table>	Marking		Comments	YES	NO	NA	Part number and model designation		X			Year of manufacture		X			Manufacturer's name or logo		X			Capacity Range		X			Unique ID Number		X			Standard Number (Z359.14)		X			How to inspect the visual indicator		X			Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X			Warning of the need for inspection in accordance with the manufacturer's instructions		X			The fiber or other materials used in the lanyard construction		X			The lanyard working length		X			Average arresting force for the SRD class		X			Arresting distance		X			Proper installation means		X			Warning on the need for testing the device for locking and retraction before each use		X			SRD class and arrest distance		X			Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X			Free fall limit		X			Suitability for use with horizontal lifelines				X	Suitability for horizontal use				X	Suitability for Leading Edge capability				x	
Marking	Comments	YES		NO	NA																																																																																																												
Part number and model designation		X																																																																																																															
Year of manufacture		X																																																																																																															
Manufacturer's name or logo		X																																																																																																															
Capacity Range		X																																																																																																															
Unique ID Number		X																																																																																																															
Standard Number (Z359.14)		X																																																																																																															
How to inspect the visual indicator		X																																																																																																															
Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X																																																																																																															
Warning of the need for inspection in accordance with the manufacturer's instructions		X																																																																																																															
The fiber or other materials used in the lanyard construction		X																																																																																																															
The lanyard working length		X																																																																																																															
Average arresting force for the SRD class		X																																																																																																															
Arresting distance		X																																																																																																															
Proper installation means		X																																																																																																															
Warning on the need for testing the device for locking and retraction before each use		X																																																																																																															
SRD class and arrest distance		X																																																																																																															
Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X																																																																																																															
Free fall limit		X																																																																																																															
Suitability for use with horizontal lifelines				X																																																																																																													
Suitability for horizontal use				X																																																																																																													
Suitability for Leading Edge capability				x																																																																																																													
5.2.1	Instructions shall be in English, and affixed to the equipment at time of shipment from the manufacturer		PASS																																																																																																														

Section (Test)	Requirement	Results				Compliance																																																																																																	
5.2.2	Instructions shall contain the following information: <table border="1" data-bbox="293 432 1349 1572"> <thead> <tr> <th data-bbox="293 432 745 464">Instructions</th> <th data-bbox="745 432 1127 464">Comments</th> <th data-bbox="1127 432 1211 464">YES</th> <th data-bbox="1211 432 1284 464">NO</th> <th data-bbox="1284 432 1349 464">NA</th> </tr> </thead> <tbody> <tr> <td data-bbox="293 464 745 522">A statement that the manufacturer's instructions shall be provided to the users</td> <td data-bbox="745 464 1127 522"></td> <td data-bbox="1127 464 1211 522">X</td> <td data-bbox="1211 464 1284 522"></td> <td data-bbox="1284 464 1349 522"></td> </tr> <tr> <td data-bbox="293 522 745 581">Manufacturers name, address, and telephone number</td> <td data-bbox="745 522 1127 581"></td> <td data-bbox="1127 522 1211 581">X</td> <td data-bbox="1211 522 1284 581"></td> <td data-bbox="1284 522 1349 581"></td> </tr> <tr> <td data-bbox="293 581 745 640">Manufacturer's part number and model designation for the equipment</td> <td data-bbox="745 581 1127 640"></td> <td data-bbox="1127 581 1211 640">X</td> <td data-bbox="1211 581 1284 640"></td> <td data-bbox="1284 581 1349 640"></td> </tr> <tr> <td data-bbox="293 640 745 699">Intended use and purpose of the equipment</td> <td data-bbox="745 640 1127 699"></td> <td data-bbox="1127 640 1211 699">X</td> <td data-bbox="1211 640 1284 699"></td> <td data-bbox="1284 640 1349 699"></td> </tr> <tr> <td data-bbox="293 699 745 758">Proper method of use and limitations on use of the equipment</td> <td data-bbox="745 699 1127 758"></td> <td data-bbox="1127 699 1211 758">X</td> <td data-bbox="1211 699 1284 758"></td> <td data-bbox="1284 699 1349 758"></td> </tr> <tr> <td data-bbox="293 758 745 816">Illustrations showing locations of markings on the equipment</td> <td data-bbox="745 758 1127 816"></td> <td data-bbox="1127 758 1211 816">X</td> <td data-bbox="1211 758 1284 816"></td> <td data-bbox="1284 758 1349 816"></td> </tr> <tr> <td data-bbox="293 816 745 875">Reproduction of printed information on all markings</td> <td data-bbox="745 816 1127 875"></td> <td data-bbox="1127 816 1211 875">X</td> <td data-bbox="1211 816 1284 875"></td> <td data-bbox="1284 816 1349 875"></td> </tr> <tr> <td data-bbox="293 875 745 934">Inspection procedures required to assure the equipment is in serviceable condition and operating correctly</td> <td data-bbox="745 875 1127 934"></td> <td data-bbox="1127 875 1211 934">X</td> <td data-bbox="1211 875 1284 934"></td> <td data-bbox="1284 875 1349 934"></td> </tr> <tr> <td data-bbox="293 934 745 993">Anchorage requirements</td> <td data-bbox="745 934 1127 993"></td> <td data-bbox="1127 934 1211 993">X</td> <td data-bbox="1211 934 1284 993"></td> <td data-bbox="1284 934 1349 993"></td> </tr> <tr> <td data-bbox="293 993 745 1052">Criteria for discarding equipment which fails inspection</td> <td data-bbox="745 993 1127 1052"></td> <td data-bbox="1127 993 1211 1052">X</td> <td data-bbox="1211 993 1284 1052"></td> <td data-bbox="1284 993 1349 1052"></td> </tr> <tr> <td data-bbox="293 1052 745 1110">Procedures for cleaning, maintenance, and storage</td> <td data-bbox="745 1052 1127 1110"></td> <td data-bbox="1127 1052 1211 1110">X</td> <td data-bbox="1211 1052 1284 1110"></td> <td data-bbox="1284 1052 1349 1110"></td> </tr> <tr> <td data-bbox="293 1110 745 1169">Reference to Z359 standards</td> <td data-bbox="745 1110 1127 1169"></td> <td data-bbox="1127 1110 1211 1169">X</td> <td data-bbox="1211 1110 1284 1169"></td> <td data-bbox="1284 1110 1349 1169"></td> </tr> <tr> <td data-bbox="293 1169 745 1228">Proper installation means and limitations on the type of anchorage connectors used</td> <td data-bbox="745 1169 1127 1228"></td> <td data-bbox="1127 1169 1211 1228">X</td> <td data-bbox="1211 1169 1284 1228"></td> <td data-bbox="1284 1169 1349 1228"></td> </tr> <tr> <td data-bbox="293 1228 745 1287">The fiber or other materials used in the lanyard construction</td> <td data-bbox="745 1228 1127 1287"></td> <td data-bbox="1127 1228 1211 1287">X</td> <td data-bbox="1211 1228 1284 1287"></td> <td data-bbox="1284 1228 1349 1287"></td> </tr> <tr> <td data-bbox="293 1287 745 1346">The lanyard length</td> <td data-bbox="745 1287 1127 1346"></td> <td data-bbox="1127 1287 1211 1346">X</td> <td data-bbox="1211 1287 1284 1346"></td> <td data-bbox="1284 1287 1349 1346"></td> </tr> <tr> <td data-bbox="293 1346 745 1404">The average arresting force when dynamically tested in accordance with the requirements of the standard</td> <td data-bbox="745 1346 1127 1404"></td> <td data-bbox="1127 1346 1211 1404">X</td> <td data-bbox="1211 1346 1284 1404"></td> <td data-bbox="1284 1346 1349 1404"></td> </tr> <tr> <td data-bbox="293 1404 745 1463">SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard</td> <td data-bbox="745 1404 1127 1463"></td> <td data-bbox="1127 1404 1211 1463">X</td> <td data-bbox="1211 1404 1284 1463"></td> <td data-bbox="1284 1404 1349 1463"></td> </tr> <tr> <td data-bbox="293 1463 745 1522">How to determine fall clearance</td> <td data-bbox="745 1463 1127 1522"></td> <td data-bbox="1127 1463 1211 1522">X</td> <td data-bbox="1211 1463 1284 1522"></td> <td data-bbox="1284 1463 1349 1522"></td> </tr> <tr> <td data-bbox="293 1522 745 1572">Testing the device for locking before each use</td> <td data-bbox="745 1522 1127 1572"></td> <td data-bbox="1127 1522 1211 1572">X</td> <td data-bbox="1211 1522 1284 1572"></td> <td data-bbox="1284 1522 1349 1572"></td> </tr> </tbody> </table>	Instructions	Comments	YES	NO	NA	A statement that the manufacturer's instructions shall be provided to the users		X			Manufacturers name, address, and telephone number		X			Manufacturer's part number and model designation for the equipment		X			Intended use and purpose of the equipment		X			Proper method of use and limitations on use of the equipment		X			Illustrations showing locations of markings on the equipment		X			Reproduction of printed information on all markings		X			Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X			Anchorage requirements		X			Criteria for discarding equipment which fails inspection		X			Procedures for cleaning, maintenance, and storage		X			Reference to Z359 standards		X			Proper installation means and limitations on the type of anchorage connectors used		X			The fiber or other materials used in the lanyard construction		X			The lanyard length		X			The average arresting force when dynamically tested in accordance with the requirements of the standard		X			SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X			How to determine fall clearance		X			Testing the device for locking before each use		X				PASS
Instructions	Comments	YES	NO	NA																																																																																																			
A statement that the manufacturer's instructions shall be provided to the users		X																																																																																																					
Manufacturers name, address, and telephone number		X																																																																																																					
Manufacturer's part number and model designation for the equipment		X																																																																																																					
Intended use and purpose of the equipment		X																																																																																																					
Proper method of use and limitations on use of the equipment		X																																																																																																					
Illustrations showing locations of markings on the equipment		X																																																																																																					
Reproduction of printed information on all markings		X																																																																																																					
Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X																																																																																																					
Anchorage requirements		X																																																																																																					
Criteria for discarding equipment which fails inspection		X																																																																																																					
Procedures for cleaning, maintenance, and storage		X																																																																																																					
Reference to Z359 standards		X																																																																																																					
Proper installation means and limitations on the type of anchorage connectors used		X																																																																																																					
The fiber or other materials used in the lanyard construction		X																																																																																																					
The lanyard length		X																																																																																																					
The average arresting force when dynamically tested in accordance with the requirements of the standard		X																																																																																																					
SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X																																																																																																					
How to determine fall clearance		X																																																																																																					
Testing the device for locking before each use		X																																																																																																					
5.2.3	Instructions shall require that only the equipment manufacturer, or persons or entities authorized in writing by the manufacturer, shall make repairs to the equipment					PASS																																																																																																	
5.2.4	Instructions shall require the user to remove equipment from service if it has been subjected to the forces of arresting a fall or affecting a rescue					PASS																																																																																																	
5.2.5	Instructions shall require the user to have a written rescue plan and the means at hand to implement it when using the equipment					PASS																																																																																																	

Section (Test)	Requirement	Results	Compliance			
5.2.6	Instructions shall provide warnings regarding:		PASS			
	Warnings	Comments		YES	NO	NA
	Altering the equipment			X		
	Misusing the equipment			X		
	Using combinations of components or sub-systems, or both, which may affect or interfere with the safe function of each other			X		
	Exposing the equipment to chemicals, high heat, severe cold, or other harsh environments which may produce a harmful effect and to consult the manufacturer in case of doubt			X		
	Using the equipment around moving machinery and electrical hazards			X		
	Using the equipment near sharp edges or abrasive surfaces			X		
	Risk of striking an object or obstruction during a swing fall			X		
	That the consequences of improperly using the device, not following instructions or markings may cause serious injury or death			X		

SUPPLEMENTAL TEST DATA

Section (Test)	Requirement	Results	Compliance								
3.2.1/4.2 .1	Static Strength: (ambient) shall withstand 3,000 lbs. when tested to: - apply a 3,000 lbs ,(+60/-0 lbs) load and maintain for 1-minute to the point of SRL line connection to the SRL drum (across the device)	<table border="1"> <thead> <tr> <th></th> <th>Sample: 1</th> <th>Sample: 2</th> <th>Sample: 3</th> </tr> </thead> <tbody> <tr> <td>Withstand load</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> </tbody> </table>		Sample: 1	Sample: 2	Sample: 3	Withstand load	YES	YES	YES	PASS
	Sample: 1	Sample: 2	Sample: 3								
Withstand load	YES	YES	YES								

Section (Test)	Requirement	Results			Compliance																																												
3.3/4.3.1	<p>Dynamic Performance: "AMBIENT"</p> <ol style="list-style-type: none"> 1. connect 310 lb. weight 2. extract enough line for a 36-inch free fall per Fig 5 in Test Standard. 3. release the test weight 4. Max Arrest distance shall not exceed 42 inches. <table border="1" data-bbox="321 636 1346 1176"> <thead> <tr> <th></th> <th>Sample: 4</th> <th>Sample: 5</th> <th>Sample: 6</th> </tr> </thead> <tbody> <tr> <td>Conditioning in:</td> <td></td> <td></td> <td></td> </tr> <tr> <td>SN or ID:</td> <td>4</td> <td>5</td> <td>6</td> </tr> <tr> <td>Payout and retract the line per 3.3.1.2 following test</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> <tr> <td>Lock function shall operate per 3.3.1.1</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> <tr> <td>Visual indicator shall activate</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> <tr> <td>Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.</td> <td>965</td> <td>892</td> <td>919</td> </tr> <tr> <td>Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.</td> <td>719</td> <td>652</td> <td>773</td> </tr> <tr> <td>Distance Initial (in): D1</td> <td>58"</td> <td>58"</td> <td>58"</td> </tr> <tr> <td>Distance Final (in): D2</td> <td>72"</td> <td>73 ¾"</td> <td>71 ½"</td> </tr> <tr> <td>Arrest Distance (in): D2-D1 < 42 Inches</td> <td>14"</td> <td>15 ¾"</td> <td>13 ½"</td> </tr> </tbody> </table>		Sample: 4	Sample: 5	Sample: 6	Conditioning in:				SN or ID:	4	5	6	Payout and retract the line per 3.3.1.2 following test	YES	YES	YES	Lock function shall operate per 3.3.1.1	YES	YES	YES	Visual indicator shall activate	YES	YES	YES	Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	965	892	919	Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.	719	652	773	Distance Initial (in): D1	58"	58"	58"	Distance Final (in): D2	72"	73 ¾"	71 ½"	Arrest Distance (in): D2-D1 < 42 Inches	14"	15 ¾"	13 ½"				PASS
	Sample: 4	Sample: 5	Sample: 6																																														
Conditioning in:																																																	
SN or ID:	4	5	6																																														
Payout and retract the line per 3.3.1.2 following test	YES	YES	YES																																														
Lock function shall operate per 3.3.1.1	YES	YES	YES																																														
Visual indicator shall activate	YES	YES	YES																																														
Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	965	892	919																																														
Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.	719	652	773																																														
Distance Initial (in): D1	58"	58"	58"																																														
Distance Final (in): D2	72"	73 ¾"	71 ½"																																														
Arrest Distance (in): D2-D1 < 42 Inches	14"	15 ¾"	13 ½"																																														

SECTION 5
REVISION HISTORY

REPORT NUMBER	DATE OF REVISION	DESCRIPTION OF CHANGE:	PROJECT OWNER	REVIEWED BY
104972747CRT-001	3/22/22	Original Report	Steve Morey	Matthew Stevens
105376372CRT-001	3/24/23	Report Extension	Alex Smith	Matthew Stevens
105663091CRT-001	12/8/2023	Report Revision: Added Model and Picture	Alex Smith	Matthew Stevens

SECTION 6
PHOTOGRAPH

UFS310090



USF310025(SS)

