

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

Declaration #: DOC-UFS314006LD

Declaration Date: 03/27/2023

Item #: UFS314006LD

Description: KStrong® BRUTE™ Backer™ LE Dual 8.5 ft. Cable SRL with rebar hooks at anchorage end, other end dorsal connector shock pack assembly (ANSI)

Brand Name: KStrong

Manufacturer: KStrong

Address: 150 N. Radnor Chester Road, Suite F200, Radnor, PA 19087

**Additional Items Conforming
Under this Declaration (If Applicable):**

KStrong declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

ANSI Z359.14-2021 Class 2

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014



Level 1:

KStrong Lab Outside the Scope of ISO/IEC Standard 17025:2017



Level 2:

KStrong Lab Within the Scope of ISO/IEC Standard 17025:2017



Level 3:

Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017

Supporting Documentation: KS-Test-UFS314006LD.pdf

This Certificate is a guarantee that the above standard(s) was met by the requirements of such standard. Testing was performed under normal operation mode. The results of testing apply only to the particular sample tested and the specific test carried out. This Certificate is only issued for products which have passed the testing requirements of listed standard(s).

Authorized Signature:



John H. Kemp Jr.
President - KStrong

ISO 17025 Accredited Test Laboratory

intertek
Total Quality. Assured.



Intertek Testing Services NA, Inc.
3933 US Rt. 11
Cortland, NY 13045
Tel: 1 607-753-6711
www.intertek.com

Accrediting Agency



A2LA
5202 Presidents Court, Ste 220
Frederick, MD 21703
Tel: 301.644.3248
info@A2LA.org

Test Verification of Conformity

Verification Number: 105376372CRT-008

On the basis of the referenced test report(s), sample(s) of the below product have been found to comply with the harmonized standards and Directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it(them).

Applicant Name & Address: KStrong INC
150 N. Radnor Chester Rd.
Suite F200
Radnor, PA 19087
USA

Product Description: Self-Retracting Device

Models/Type References: UFS310206L, UFS310206LD, UFS314006L, UFS314006LD, UFS316106L, UFS316106LD, UFS319006L, UFS319006LD

Brand Name: KStrong

Relevant Standards: ANSI/ASSP Z359.14-2021

Verification Issuing Office Name & Address: Intertek Testing Services NA, Inc.
3933 US Rt-11
Cortland, NY 13045
USA

Date of Tests: 8/17/22 – 11/15/22

Test Report Number(s): 105376372CRT-007

Signature:



Name:

Matthew Stevens

Position:

Team Leader

Date:

03/27/2023



This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

KSTRONG INC

TEST REPORT

SCOPE OF WORKs

ANSI/ASSP Z359.14-2021 – SELF RETRACTING DEVICES [LEADING EDGE CAPABILITY]

REPORT NUMBER

105376372CRT-007

ORIGINAL REPORT NUMBER

105113592CRT-002

ISSUE DATE

3/27/23

PAGES

8

DOCUMENT CONTROL NUMBER

GFT-OP-10a (6-March-2017)

© 2017 INTERTEK





Total Quality. Assured.

Address
3933 US rt. 11 Cortland, NY 13045

Telephone: 607-758-6246
www.intertek.com

TEST REPORT FOR KSTRONG INC

Report No.: 105376372CRT-007

Date: March 27, 2023

KSTRONG Inc.
150 N. Radnor Chester RD.
Suite F200
Radnor, PA 19087
USA

Report Number..... 105376372CRT-007

Signed Quote Number..... Qu-01339713-1

PO Number.....: N/A

Name of Testing Laboratory
Preparing the Report Intertek Testing Services NA Inc.

Test Specification:

Standard..... ANSI/ASSP Z359.14-2021

Date(s) of Testing..... 8/17/2022-11/15/2022

Product Description: Self-Retracting Device

Product Type: Leading Edge (Class 2)

Brand Name: KStrong

Model Number(s): UFS310206L, UFS310206LD, UFS314006L, UFS314006LD,
UFS316106L, UFS316106LD, UFS319006L, UFS319006LD

Additional Models Covered:..... N/A

Date(s) Samples Received 8/10/2022-10/26/22

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Date: March 27, 2023



SECTION 1

SUMMARY OF TESTING

VERIFICATION TESTS COMPLETED	ANSI/ASSP Z359.14-2021 CLAUSE	DATE TESTED	STATUS
General Requirements	3.1	8/17/2022	PASS
Static Strength	4.2.1	8/19/2022	PASS
Dynamic Performance Testing of SRD (Ambient)	4.3.3	8/17/2022	PASS
Static Strength, For Dual SRL-P's	4.6.1	11/14/2022	PASS
SRL-P Dual Connection	4.6.2	11/14/2022	PASS
SRL-P Wrap Around Static Strength (Includes 4.1.8 Abrasion)	4.6.3	11/10/2022	PASS
Markings and Instructions	5.1, 5.2	8/18/2022	PASS
Design-Function	4.3.4.1	8/18/2022	PASS
User Inspection, Maintenance and Storage of Equipment	6.0	8/18/2022	PASS

SECTION 2

This test report concludes the work anticipated in the testing phase of your project. If there are any questions regarding this report please contact the undersigned at 607-753-6711.

COMPLETED BY:	Alex Smith	REVIEWED BY:	Matthew Stevens
TITLE:	Technician	TITLE:	Team Leader
SIGNATURE:		SIGNATURE	
DATE	3/24/23	DATE:	3/27/23

Please see attached test data for details.

Date: March 27, 2023

SECTION 3

TESTING EQUIPMENT CALIBRATION INFORMATION

USED FOR TEST	DESCRIPTION	MANUFACTURER	CONTROL NO.	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE
X	Test Weight	NA	NA	310 Lbs	-	VBU	VBU
X	Leading Edge Bar	Intertek	G147	CAT 3	-	Single Use VBU	
X	Load Cell	Interface	G138	-	-	5/28/22	5/28/23
X	Load Cell	Interface	L137	-	-	5/25/22	5/25/23
X	Tape Measure	Stanley	N1407	-	-	2/16/22	2/16/23

SECTION 4

SUPPLEMENTAL TEST DATA

SECTION (TEST)	REQUIREMENT	RESULTS	COMPLIANCE	
4.3.1.7	<u>DYNAMIC PERFORMANCE: "Ambient"</u>		PASS	
	<ol style="list-style-type: none"> 1. Connect 310 lb. weight 2. Drop test weight from a level 5 feet +/- 1 inch 3. Allow weight to swing unrestrained for a period of not less than 10 seconds 4. Record the maximum and average arresting forces 5. Line must retain 1,000 lb. static load after drops 			
	SRL LINE ORIENTATION: PERPENDICULAR			SAMPLE: 1
	Lock function shall operate per 3.1.2			YES
	Visual indicator shall activate			YES
	Max. Arrest Force: (lbs.) < 1,800 lbs.			1143
	Avg Arrest Force (lbs.): < 1,575 lbs.			795
	Arrest Distance (in):			154 ½
	Retain a minimum of 1,000 lbs of residual tensile strength following the test			YES
	SRL LINE ORIENTATION: 5' OFFSET			SAMPLE: 4
	Lock function shall operate per 3.1.2			YES
	Visual indicator shall activate			YES
	Max. Arrest Force: (lbs.) < 1,800 lbs.			1108
	Avg Arrest Force (lbs.): < 1,575 lbs.			839
	Arrest Distance (in):			150 ¾
Retain a minimum of 1,000 lbs of residual tensile strength following the test		YES		

Date: March 27, 2023

SECTION (TEST)	REQUIREMENT	RESULTS				COMPLIANCE
3.2.1/4.2.1	<p>Static Strength: (ambient) shall withstand 3,000 lbs. when tested to:</p> <ul style="list-style-type: none"> - apply a 3,000 lbs ,(+60/-0 lbs) load and maintain for 1-minute to the point of SRL line connection to the SRL drum (across the device) 		Sample: 1	Sample: 2	Sample: 3	PASS
		Withstand load	YES	YES	YES	
3.6.1/4.6.1	<p>Static Strength Testing of SRL-P (Multiple Orientations for Twin Units): (ambient) shall withstand <u>3,600 lbs.</u></p>		Sample: 1	Sample: 2	Sample: 3	PASS
		Withstand load	YES	YES	YES	
3.6.2/4.6.2	<p>SRL-P Dual Connection: Raise 24 inches drop: Record MAF</p>		Sample: 4	Sample: 5	Sample: 6	PASS
		Mass Force	834	817	881	
		Sample Break?	NO	NO	NO	
3.6.3/4.6.3	<p>SRL-P Wrap Around Static Strength (Includes 4.1.8 Abrasion): (ambient) shall withstand 3,600 lbs. when tested</p>		Sample: 1	Sample: 2	Sample: 3	PASS
		Withstand Abrasion 2500 cycles?	YES	YES	YES	
		Withstand load	YES	YES	YES	

Section (Test)	Requirement	Results	Compliance																																																																																																													
3	"Marking and Instructions"																																																																																																															
5.1.1	Shall be in English		PASS																																																																																																													
5.1.3	Self-Retracting Devices shall be marked with the following:		PASS																																																																																																													
	<table border="1"> <thead> <tr> <th>Marking</th> <th>Comments</th> <th>YES</th> <th>NO</th> <th>NA</th> </tr> </thead> <tbody> <tr> <td>Part number and model designation</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Year of manufacture</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Manufacturer's name or logo</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Capacity Range</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Unique ID Number</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Standard Number (Z359.14)</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>How to inspect the visual indicator</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning of the need for inspection in accordance with the manufacturer's instructions</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>The fiber or other materials used in the lanyard construction</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>The lanyard working length</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Average arresting force for the SRD class</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Arresting distance</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Proper installation means</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning on the need for testing the device for locking and retraction before each use</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>SRD class and arrest distance</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Free fall limit</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Suitability for use with horizontal lifelines</td> <td></td> <td></td> <td></td> <td>X</td> </tr> <tr> <td>Suitability for horizontal use</td> <td></td> <td></td> <td></td> <td>X</td> </tr> <tr> <td>Suitability for Leading Edge capability</td> <td></td> <td></td> <td></td> <td>x</td> </tr> </tbody> </table>	Marking		Comments	YES	NO	NA	Part number and model designation		X			Year of manufacture		X			Manufacturer's name or logo		X			Capacity Range		X			Unique ID Number		X			Standard Number (Z359.14)		X			How to inspect the visual indicator		X			Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X			Warning of the need for inspection in accordance with the manufacturer's instructions		X			The fiber or other materials used in the lanyard construction		X			The lanyard working length		X			Average arresting force for the SRD class		X			Arresting distance		X			Proper installation means		X			Warning on the need for testing the device for locking and retraction before each use		X			SRD class and arrest distance		X			Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X			Free fall limit		X			Suitability for use with horizontal lifelines				X	Suitability for horizontal use				X	Suitability for Leading Edge capability				x
Marking	Comments	YES		NO	NA																																																																																																											
Part number and model designation		X																																																																																																														
Year of manufacture		X																																																																																																														
Manufacturer's name or logo		X																																																																																																														
Capacity Range		X																																																																																																														
Unique ID Number		X																																																																																																														
Standard Number (Z359.14)		X																																																																																																														
How to inspect the visual indicator		X																																																																																																														
Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X																																																																																																														
Warning of the need for inspection in accordance with the manufacturer's instructions		X																																																																																																														
The fiber or other materials used in the lanyard construction		X																																																																																																														
The lanyard working length		X																																																																																																														
Average arresting force for the SRD class		X																																																																																																														
Arresting distance		X																																																																																																														
Proper installation means		X																																																																																																														
Warning on the need for testing the device for locking and retraction before each use		X																																																																																																														
SRD class and arrest distance		X																																																																																																														
Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X																																																																																																														
Free fall limit		X																																																																																																														
Suitability for use with horizontal lifelines				X																																																																																																												
Suitability for horizontal use				X																																																																																																												
Suitability for Leading Edge capability				x																																																																																																												
5.2.1	Instructions shall be in English, and affixed to the equipment at time of shipment from the manufacturer		PASS																																																																																																													

Section (Test)	Requirement	Results				Compliance																																																																																																	
5.2.2	Instructions shall contain the following information: <table border="1" data-bbox="282 401 1341 1541"> <thead> <tr> <th data-bbox="282 401 737 428">Instructions</th> <th data-bbox="737 401 1117 428">Comments</th> <th data-bbox="1117 401 1203 428">YES</th> <th data-bbox="1203 401 1276 428">NO</th> <th data-bbox="1276 401 1341 428">NA</th> </tr> </thead> <tbody> <tr> <td data-bbox="282 428 737 489">A statement that the manufacturer’s instructions shall be provided to the users</td> <td data-bbox="737 428 1117 489"></td> <td data-bbox="1117 428 1203 489">X</td> <td data-bbox="1203 428 1276 489"></td> <td data-bbox="1276 428 1341 489"></td> </tr> <tr> <td data-bbox="282 489 737 550">Manufacturers name, address, and telephone number</td> <td data-bbox="737 489 1117 550"></td> <td data-bbox="1117 489 1203 550">X</td> <td data-bbox="1203 489 1276 550"></td> <td data-bbox="1276 489 1341 550"></td> </tr> <tr> <td data-bbox="282 550 737 611">Manufacturer’s part number and model designation for the equipment</td> <td data-bbox="737 550 1117 611"></td> <td data-bbox="1117 550 1203 611">X</td> <td data-bbox="1203 550 1276 611"></td> <td data-bbox="1276 550 1341 611"></td> </tr> <tr> <td data-bbox="282 611 737 672">Intended use and purpose of the equipment</td> <td data-bbox="737 611 1117 672"></td> <td data-bbox="1117 611 1203 672">X</td> <td data-bbox="1203 611 1276 672"></td> <td data-bbox="1276 611 1341 672"></td> </tr> <tr> <td data-bbox="282 672 737 732">Proper method of use and limitations on use of the equipment</td> <td data-bbox="737 672 1117 732"></td> <td data-bbox="1117 672 1203 732">X</td> <td data-bbox="1203 672 1276 732"></td> <td data-bbox="1276 672 1341 732"></td> </tr> <tr> <td data-bbox="282 732 737 793">Illustrations showing locations of markings on the equipment</td> <td data-bbox="737 732 1117 793"></td> <td data-bbox="1117 732 1203 793">X</td> <td data-bbox="1203 732 1276 793"></td> <td data-bbox="1276 732 1341 793"></td> </tr> <tr> <td data-bbox="282 793 737 854">Reproduction of printed information on all markings</td> <td data-bbox="737 793 1117 854"></td> <td data-bbox="1117 793 1203 854">X</td> <td data-bbox="1203 793 1276 854"></td> <td data-bbox="1276 793 1341 854"></td> </tr> <tr> <td data-bbox="282 854 737 947">Inspection procedures required to assure the equipment is in serviceable condition and operating correctly</td> <td data-bbox="737 854 1117 947"></td> <td data-bbox="1117 854 1203 947">X</td> <td data-bbox="1203 854 1276 947"></td> <td data-bbox="1276 854 1341 947"></td> </tr> <tr> <td data-bbox="282 947 737 974">Anchorage requirements</td> <td data-bbox="737 947 1117 974"></td> <td data-bbox="1117 947 1203 974">X</td> <td data-bbox="1203 947 1276 974"></td> <td data-bbox="1276 947 1341 974"></td> </tr> <tr> <td data-bbox="282 974 737 1035">Criteria for discarding equipment which fails inspection</td> <td data-bbox="737 974 1117 1035"></td> <td data-bbox="1117 974 1203 1035">X</td> <td data-bbox="1203 974 1276 1035"></td> <td data-bbox="1276 974 1341 1035"></td> </tr> <tr> <td data-bbox="282 1035 737 1096">Procedures for cleaning, maintenance, and storage</td> <td data-bbox="737 1035 1117 1096"></td> <td data-bbox="1117 1035 1203 1096">X</td> <td data-bbox="1203 1035 1276 1096"></td> <td data-bbox="1276 1035 1341 1096"></td> </tr> <tr> <td data-bbox="282 1096 737 1123">Reference to Z359 standards</td> <td data-bbox="737 1096 1117 1123"></td> <td data-bbox="1117 1096 1203 1123">X</td> <td data-bbox="1203 1096 1276 1123"></td> <td data-bbox="1276 1096 1341 1123"></td> </tr> <tr> <td data-bbox="282 1123 737 1184">Proper installation means and limitations on the type of anchorage connectors used</td> <td data-bbox="737 1123 1117 1184"></td> <td data-bbox="1117 1123 1203 1184">X</td> <td data-bbox="1203 1123 1276 1184"></td> <td data-bbox="1276 1123 1341 1184"></td> </tr> <tr> <td data-bbox="282 1184 737 1245">The fiber or other materials used in the lanyard construction</td> <td data-bbox="737 1184 1117 1245"></td> <td data-bbox="1117 1184 1203 1245">X</td> <td data-bbox="1203 1184 1276 1245"></td> <td data-bbox="1276 1184 1341 1245"></td> </tr> <tr> <td data-bbox="282 1245 737 1272">The lanyard length</td> <td data-bbox="737 1245 1117 1272"></td> <td data-bbox="1117 1245 1203 1272">X</td> <td data-bbox="1203 1245 1276 1272"></td> <td data-bbox="1276 1245 1341 1272"></td> </tr> <tr> <td data-bbox="282 1272 737 1365">The average arresting force when dynamically tested in accordance with the requirements of the standard</td> <td data-bbox="737 1272 1117 1365"></td> <td data-bbox="1117 1272 1203 1365">X</td> <td data-bbox="1203 1272 1276 1365"></td> <td data-bbox="1276 1272 1341 1365"></td> </tr> <tr> <td data-bbox="282 1365 737 1457">SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard</td> <td data-bbox="737 1365 1117 1457"></td> <td data-bbox="1117 1365 1203 1457">X</td> <td data-bbox="1203 1365 1276 1457"></td> <td data-bbox="1276 1365 1341 1457"></td> </tr> <tr> <td data-bbox="282 1457 737 1484">How to determine fall clearance</td> <td data-bbox="737 1457 1117 1484"></td> <td data-bbox="1117 1457 1203 1484">X</td> <td data-bbox="1203 1457 1276 1484"></td> <td data-bbox="1276 1457 1341 1484"></td> </tr> <tr> <td data-bbox="282 1484 737 1541">Testing the device for locking before each use</td> <td data-bbox="737 1484 1117 1541"></td> <td data-bbox="1117 1484 1203 1541">X</td> <td data-bbox="1203 1484 1276 1541"></td> <td data-bbox="1276 1484 1341 1541"></td> </tr> </tbody> </table>	Instructions	Comments	YES	NO	NA	A statement that the manufacturer’s instructions shall be provided to the users		X			Manufacturers name, address, and telephone number		X			Manufacturer’s part number and model designation for the equipment		X			Intended use and purpose of the equipment		X			Proper method of use and limitations on use of the equipment		X			Illustrations showing locations of markings on the equipment		X			Reproduction of printed information on all markings		X			Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X			Anchorage requirements		X			Criteria for discarding equipment which fails inspection		X			Procedures for cleaning, maintenance, and storage		X			Reference to Z359 standards		X			Proper installation means and limitations on the type of anchorage connectors used		X			The fiber or other materials used in the lanyard construction		X			The lanyard length		X			The average arresting force when dynamically tested in accordance with the requirements of the standard		X			SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X			How to determine fall clearance		X			Testing the device for locking before each use		X				PASS
Instructions	Comments	YES	NO	NA																																																																																																			
A statement that the manufacturer’s instructions shall be provided to the users		X																																																																																																					
Manufacturers name, address, and telephone number		X																																																																																																					
Manufacturer’s part number and model designation for the equipment		X																																																																																																					
Intended use and purpose of the equipment		X																																																																																																					
Proper method of use and limitations on use of the equipment		X																																																																																																					
Illustrations showing locations of markings on the equipment		X																																																																																																					
Reproduction of printed information on all markings		X																																																																																																					
Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X																																																																																																					
Anchorage requirements		X																																																																																																					
Criteria for discarding equipment which fails inspection		X																																																																																																					
Procedures for cleaning, maintenance, and storage		X																																																																																																					
Reference to Z359 standards		X																																																																																																					
Proper installation means and limitations on the type of anchorage connectors used		X																																																																																																					
The fiber or other materials used in the lanyard construction		X																																																																																																					
The lanyard length		X																																																																																																					
The average arresting force when dynamically tested in accordance with the requirements of the standard		X																																																																																																					
SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X																																																																																																					
How to determine fall clearance		X																																																																																																					
Testing the device for locking before each use		X																																																																																																					
5.2.3	Instructions shall require that only the equipment manufacturer, or persons or entities authorized in writing by the manufacturer, shall make repairs to the equipment					PASS																																																																																																	
5.2.4	Instructions shall require the user to remove equipment from service if it has been subjected to the forces of arresting a fall or affecting a rescue					PASS																																																																																																	
5.2.5	Instructions shall require the user to have a written rescue plan and the means at hand to implement it when using the equipment					PASS																																																																																																	

Date: March 27, 2023

5.2.6	Instructions shall provide warnings regarding:					PASS
	Warnings	Comments	YES	NO	NA	
	Altering the equipment		X			
	Misusing the equipment		X			
	Using combinations of components or sub-systems, or both, which may affect or interfere with the safe function of each other		X			
	Exposing the equipment to chemicals, high heat, severe cold, or other harsh environments which may produce a harmful effect and to consult the manufacturer in case of doubt		X			
	Using the equipment around moving machinery and electrical hazards		X			
	Using the equipment near sharp edges or abrasive surfaces		X			
	Risk of striking an object or obstruction during a swing fall		X			
	That the consequences of improperly using the device, not following instructions or markings may cause serious injury or death		X			
6.0	User Inspection, Maintenance and Storage of Equipment					PASS

**SECTION 5
REVISION HISTORY**

REPORT NUMBER	DATE OF REVISION	DESCRIPTION OF CHANGE:	PROJECT OWNER	REVIEWED BY
105113592CRT-002	11/18/2022	Original Report	Steven Morey	Matthew Stevens
105376372CRT-007	3/27/2023	Report Extension	Alex Smith	Matthew Stevens