

## Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019

Declaration #: DOC-UFS330008(SS)

Declaration Date: 12/08/2023

Item #: UFS330008(SS)

**Description:** KStrong® BRUTE™ 8 ft. Stainless Steel Cable SRL with swivel snap hook. Includes installation carabiner (ANSI)

**Brand Name:** KStrong

**Manufacturer:** KStrong

**Address:** 150 N. Radnor Chester Road, Suite F200, Radnor, PA 19087

**Additional Items Conforming Under this Declaration (If Applicable):**

KStrong declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

### ANSI Z359.14-2021 Class 1

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014



**Level 1:**

KStrong Lab Outside the Scope of ISO/IEC Standard 17025:2017



**Level 2:**

KStrong Lab Within the Scope of ISO/IEC Standard 17025:2017



**Level 3:**

Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2017

**Supporting Documentation:** KS-Test-UFS330008.pdf

This Certificate is a guarantee that the above standard(s) was met by the requirements of such standard. Testing was performed under normal operation mode. The results of testing apply only to the particular sample tested and the specific test carried out. This Certificate is only issued for products which have passed the testing requirements of listed standard(s).

Authorized Signature:



John H. Kemp Jr.  
President - KStrong

ISO 17025 Accredited Test Laboratory

**intertek**  
Total Quality. Assured.



Intertek Testing Services NA, Inc.  
3933 US Rt. 11  
Cortland, NY 13045  
Tel: 1 607-753-6711  
www.intertek.com

Accrediting Agency



A2LA  
5202 Presidents Court, Ste 220  
Frederick, MD 21703  
Tel: 301.644.3248  
info@A2LA.org

# Test Verification of Conformity

Verification Number: 105663091CRT-002

On the basis of the referenced test report(s), sample(s) of the below product have been found to comply with the harmonized standards and Directives listed on this verification at the time the tests were carried out. Other standards and Directives may be relevant to the product. This verification is part of the full test report(s) and should be read in conjunction with it(them).

Applicant Name & Address: KStrong INC  
150 N. Radnor Chester Rd.  
Suite F200  
Radnor, PA 19087  
USA

Product Description: Self-Retracting Device

Models/Type References: UFS310010, UFS310020, UFS310030, UFS310050, UFS310100, UFS310150,  
UFS310130, UFS330008, UFS480020, UFS480030, UFS480050, UFS310020(SS),  
UFS310030(SS), UFS310050(SS), UFS310090, UFS310025(SS), UFS310018(SS)

Brand Name: KStrong INC

Relevant Standards: ANSI/ASSP Z359.14-2021

Verification Issuing Office Name & Address: Intertek Testing Services NA, Inc.  
3933 US Rt-11  
Cortland, NY 13045  
USA

Date of Tests: 03/17/22 – 03/22/22

Test Report Number(s): 105663091CRT-001

Signature:



Name:

Matthew Stevens

Position:

Team Leader

Date:

12/08/2023



This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

# KSTRONG INC.

## TEST REPORT

**SCOPE OF WORKs**

ANSI/ASSP Z359.14-2021 – SELF RETRACTING DEVICES

**REPORT NUMBER**

105663091CRT-001

**ORIGINAL REPORT NUMBER**

105376372CRT-001

**ISSUE DATE**

December 8, 2023

**PAGES**

8

**DOCUMENT CONTROL NUMBER**

GFT-OP-10a (6-March-2017)

© 2017 INTERTEK





Total Quality. Assured.

Address  
3933 US rt. 11 Cortland, NY  
13045

**TEST REPORT FOR KSTRONG INC.**

Report No.: 105663091CRT-001  
Date: December 8, 2023

Telephone: 607-758-6246  
www.intertek.com

KSTRONG Inc. 150 N. Radnor Chester RD. Suite F200 Radnor, PA 19087 USA	
<b>Report Number</b> .....	105663091CRT-001
<b>Signed Quote Number</b> .....	Qu-01405542
<b>PO Number</b> .....	N/A
<b>Name of Testing Laboratory Preparing the Report</b> .....	
	Intertek Testing Services NA Inc.
<b>Test Specification:</b>	
<b>Standard</b> .....	ANSI/ASSP Z359.14-2021
<b>Date(s) of Testing</b> .....	3/14/22-3/22/22
<b>Product Description:</b>	
<b>Product Type</b> .....	Self-Retracting Device
<b>Brand Name</b> .....	KStrong
<b>Model Number(s)</b> .....	UFS310010, UFS310020, UFS310030, UFS310050, UFS310100, UFS310150, UFS310130, UFS330008, UFS480020, UFS480030, UFS480050, UFS310020(SS), UFS310030(SS), UFS310050(SS), UFS310090, UFS310025(SS), UFS310018(SS)
<b>Model Share</b> .....	N/A
<b>Dates Samples Received:</b>	3/4/2022

---

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



Date: December 8, 2023

**SECTION 1**  
**SUMMARY OF TESTING**

TESTS COMPLETED	TEST DATE	ANSI/ASSP Z359.14-2021 CLAUSE	STATUS
General Requirements	3/14/22	3.1	PASS
Markings and instructions/User inspection, Maintenance	3/17/22	5.1, 5.2/6	PASS
Static Strength Testing of SRD's	3/21/22	3.2.1/4.2.1	PASS
Dynamic Performance (ambient)	3/22/22	3.3/4.3.1	PASS

**SECTION 2**

This test report concludes the work anticipated in the testing phase of your project. If there are any questions regarding this report please contact the undersigned at 607-753-6711.

<b>COMPLETED BY:</b>	Alex Smith	<b>REVIEWED BY:</b>	Matthew Stevens
<b>TITLE:</b>	Technician	<b>TITLE:</b>	Team Leader
<b>SIGNATURE:</b>		<b>SIGNATURE</b>	
<b>DATE</b>	12/8/2023	<b>DATE:</b>	12/8/2023

Please see attached test data for details.

**SECTION 3**

**TESTING EQUIPMENT CALIBRATION INFORMATION**

USED FOR TEST	DESCRIPTION	MANUFACTURER	CONTROL NO.	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE
X	Test Weight	NA	NA	310 lbs	-	VBU	VBU
X	Load Cell	PCB	N1392	-	-	7/22/21	7/22/22
X	Tape Measure	Stanley	H339	25'	-	5/10/21	5/10/22
X	Load Cell	Interface	L099	-	-	5/10/21	5/10/22

**SECTION 4**

Section (Test)	Requirement	Results	Compliance																																																																																																														
3	"Marking and Instructions"																																																																																																																
5.1.1	Shall be in English		PASS																																																																																																														
5.1.3	Self-Retracting Devices shall be marked with the following:		PASS																																																																																																														
	<table border="1"> <thead> <tr> <th>Marking</th> <th>Comments</th> <th>YES</th> <th>NO</th> <th>NA</th> </tr> </thead> <tbody> <tr> <td>Part number and model designation</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Year of manufacture</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Manufacturer's name or logo</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Capacity Range</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Unique ID Number</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Standard Number (Z359.14)</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>How to inspect the visual indicator</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning of the need for inspection in accordance with the manufacturer's instructions</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>The fiber or other materials used in the lanyard construction</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>The lanyard working length</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Average arresting force for the SRD class</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Arresting distance</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Proper installation means</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning on the need for testing the device for locking and retraction before each use</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>SRD class and arrest distance</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Free fall limit</td> <td></td> <td>X</td> <td></td> <td></td> </tr> <tr> <td>Suitability for use with horizontal lifelines</td> <td></td> <td></td> <td></td> <td>X</td> </tr> <tr> <td>Suitability for horizontal use</td> <td></td> <td></td> <td></td> <td>X</td> </tr> <tr> <td>Suitability for Leading Edge capability</td> <td></td> <td></td> <td></td> <td>x</td> </tr> </tbody> </table>	Marking		Comments	YES	NO	NA	Part number and model designation		X			Year of manufacture		X			Manufacturer's name or logo		X			Capacity Range		X			Unique ID Number		X			Standard Number (Z359.14)		X			How to inspect the visual indicator		X			Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X			Warning of the need for inspection in accordance with the manufacturer's instructions		X			The fiber or other materials used in the lanyard construction		X			The lanyard working length		X			Average arresting force for the SRD class		X			Arresting distance		X			Proper installation means		X			Warning on the need for testing the device for locking and retraction before each use		X			SRD class and arrest distance		X			Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X			Free fall limit		X			Suitability for use with horizontal lifelines				X	Suitability for horizontal use				X	Suitability for Leading Edge capability				x	
Marking	Comments	YES		NO	NA																																																																																																												
Part number and model designation		X																																																																																																															
Year of manufacture		X																																																																																																															
Manufacturer's name or logo		X																																																																																																															
Capacity Range		X																																																																																																															
Unique ID Number		X																																																																																																															
Standard Number (Z359.14)		X																																																																																																															
How to inspect the visual indicator		X																																																																																																															
Warning to follow the manufacturer's instructions included with the equipment at time of shipment from the manufacturer		X																																																																																																															
Warning of the need for inspection in accordance with the manufacturer's instructions		X																																																																																																															
The fiber or other materials used in the lanyard construction		X																																																																																																															
The lanyard working length		X																																																																																																															
Average arresting force for the SRD class		X																																																																																																															
Arresting distance		X																																																																																																															
Proper installation means		X																																																																																																															
Warning on the need for testing the device for locking and retraction before each use		X																																																																																																															
SRD class and arrest distance		X																																																																																																															
Warning of the need to avoid lanyard contact with sharp edges and abrasive surfaces (not required for LE devices)		X																																																																																																															
Free fall limit		X																																																																																																															
Suitability for use with horizontal lifelines				X																																																																																																													
Suitability for horizontal use				X																																																																																																													
Suitability for Leading Edge capability				x																																																																																																													
5.2.1	Instructions shall be in English, and affixed to the equipment at time of shipment from the manufacturer		PASS																																																																																																														

Section (Test)	Requirement	Results				Compliance																																																																																																	
5.2.2	Instructions shall contain the following information: <table border="1" data-bbox="293 430 1349 1572"> <thead> <tr> <th data-bbox="293 430 745 464">Instructions</th> <th data-bbox="745 430 1127 464">Comments</th> <th data-bbox="1127 430 1211 464">YES</th> <th data-bbox="1211 430 1284 464">NO</th> <th data-bbox="1284 430 1349 464">NA</th> </tr> </thead> <tbody> <tr> <td data-bbox="293 464 745 520">A statement that the manufacturer's instructions shall be provided to the users</td> <td data-bbox="745 464 1127 520"></td> <td data-bbox="1127 464 1211 520">X</td> <td data-bbox="1211 464 1284 520"></td> <td data-bbox="1284 464 1349 520"></td> </tr> <tr> <td data-bbox="293 520 745 577">Manufacturers name, address, and telephone number</td> <td data-bbox="745 520 1127 577"></td> <td data-bbox="1127 520 1211 577">X</td> <td data-bbox="1211 520 1284 577"></td> <td data-bbox="1284 520 1349 577"></td> </tr> <tr> <td data-bbox="293 577 745 634">Manufacturer's part number and model designation for the equipment</td> <td data-bbox="745 577 1127 634"></td> <td data-bbox="1127 577 1211 634">X</td> <td data-bbox="1211 577 1284 634"></td> <td data-bbox="1284 577 1349 634"></td> </tr> <tr> <td data-bbox="293 634 745 690">Intended use and purpose of the equipment</td> <td data-bbox="745 634 1127 690"></td> <td data-bbox="1127 634 1211 690">X</td> <td data-bbox="1211 634 1284 690"></td> <td data-bbox="1284 634 1349 690"></td> </tr> <tr> <td data-bbox="293 690 745 747">Proper method of use and limitations on use of the equipment</td> <td data-bbox="745 690 1127 747"></td> <td data-bbox="1127 690 1211 747">X</td> <td data-bbox="1211 690 1284 747"></td> <td data-bbox="1284 690 1349 747"></td> </tr> <tr> <td data-bbox="293 747 745 804">Illustrations showing locations of markings on the equipment</td> <td data-bbox="745 747 1127 804"></td> <td data-bbox="1127 747 1211 804">X</td> <td data-bbox="1211 747 1284 804"></td> <td data-bbox="1284 747 1349 804"></td> </tr> <tr> <td data-bbox="293 804 745 861">Reproduction of printed information on all markings</td> <td data-bbox="745 804 1127 861"></td> <td data-bbox="1127 804 1211 861">X</td> <td data-bbox="1211 804 1284 861"></td> <td data-bbox="1284 804 1349 861"></td> </tr> <tr> <td data-bbox="293 861 745 917">Inspection procedures required to assure the equipment is in serviceable condition and operating correctly</td> <td data-bbox="745 861 1127 917"></td> <td data-bbox="1127 861 1211 917">X</td> <td data-bbox="1211 861 1284 917"></td> <td data-bbox="1284 861 1349 917"></td> </tr> <tr> <td data-bbox="293 917 745 974">Anchorage requirements</td> <td data-bbox="745 917 1127 974"></td> <td data-bbox="1127 917 1211 974">X</td> <td data-bbox="1211 917 1284 974"></td> <td data-bbox="1284 917 1349 974"></td> </tr> <tr> <td data-bbox="293 974 745 1031">Criteria for discarding equipment which fails inspection</td> <td data-bbox="745 974 1127 1031"></td> <td data-bbox="1127 974 1211 1031">X</td> <td data-bbox="1211 974 1284 1031"></td> <td data-bbox="1284 974 1349 1031"></td> </tr> <tr> <td data-bbox="293 1031 745 1087">Procedures for cleaning, maintenance, and storage</td> <td data-bbox="745 1031 1127 1087"></td> <td data-bbox="1127 1031 1211 1087">X</td> <td data-bbox="1211 1031 1284 1087"></td> <td data-bbox="1284 1031 1349 1087"></td> </tr> <tr> <td data-bbox="293 1087 745 1144">Reference to Z359 standards</td> <td data-bbox="745 1087 1127 1144"></td> <td data-bbox="1127 1087 1211 1144">X</td> <td data-bbox="1211 1087 1284 1144"></td> <td data-bbox="1284 1087 1349 1144"></td> </tr> <tr> <td data-bbox="293 1144 745 1201">Proper installation means and limitations on the type of anchorage connectors used</td> <td data-bbox="745 1144 1127 1201"></td> <td data-bbox="1127 1144 1211 1201">X</td> <td data-bbox="1211 1144 1284 1201"></td> <td data-bbox="1284 1144 1349 1201"></td> </tr> <tr> <td data-bbox="293 1201 745 1257">The fiber or other materials used in the lanyard construction</td> <td data-bbox="745 1201 1127 1257"></td> <td data-bbox="1127 1201 1211 1257">X</td> <td data-bbox="1211 1201 1284 1257"></td> <td data-bbox="1284 1201 1349 1257"></td> </tr> <tr> <td data-bbox="293 1257 745 1314">The lanyard length</td> <td data-bbox="745 1257 1127 1314"></td> <td data-bbox="1127 1257 1211 1314">X</td> <td data-bbox="1211 1257 1284 1314"></td> <td data-bbox="1284 1257 1349 1314"></td> </tr> <tr> <td data-bbox="293 1314 745 1371">The average arresting force when dynamically tested in accordance with the requirements of the standard</td> <td data-bbox="745 1314 1127 1371"></td> <td data-bbox="1127 1314 1211 1371">X</td> <td data-bbox="1211 1314 1284 1371"></td> <td data-bbox="1284 1314 1349 1371"></td> </tr> <tr> <td data-bbox="293 1371 745 1428">SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard</td> <td data-bbox="745 1371 1127 1428"></td> <td data-bbox="1127 1371 1211 1428">X</td> <td data-bbox="1211 1371 1284 1428"></td> <td data-bbox="1284 1371 1349 1428"></td> </tr> <tr> <td data-bbox="293 1428 745 1484">How to determine fall clearance</td> <td data-bbox="745 1428 1127 1484"></td> <td data-bbox="1127 1428 1211 1484">X</td> <td data-bbox="1211 1428 1284 1484"></td> <td data-bbox="1284 1428 1349 1484"></td> </tr> <tr> <td data-bbox="293 1484 745 1541">Testing the device for locking before each use</td> <td data-bbox="745 1484 1127 1541"></td> <td data-bbox="1127 1484 1211 1541">X</td> <td data-bbox="1211 1484 1284 1541"></td> <td data-bbox="1284 1484 1349 1541"></td> </tr> </tbody> </table>	Instructions	Comments	YES	NO	NA	A statement that the manufacturer's instructions shall be provided to the users		X			Manufacturers name, address, and telephone number		X			Manufacturer's part number and model designation for the equipment		X			Intended use and purpose of the equipment		X			Proper method of use and limitations on use of the equipment		X			Illustrations showing locations of markings on the equipment		X			Reproduction of printed information on all markings		X			Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X			Anchorage requirements		X			Criteria for discarding equipment which fails inspection		X			Procedures for cleaning, maintenance, and storage		X			Reference to Z359 standards		X			Proper installation means and limitations on the type of anchorage connectors used		X			The fiber or other materials used in the lanyard construction		X			The lanyard length		X			The average arresting force when dynamically tested in accordance with the requirements of the standard		X			SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X			How to determine fall clearance		X			Testing the device for locking before each use		X			<p><b>PASS</b></p>	
Instructions	Comments	YES	NO	NA																																																																																																			
A statement that the manufacturer's instructions shall be provided to the users		X																																																																																																					
Manufacturers name, address, and telephone number		X																																																																																																					
Manufacturer's part number and model designation for the equipment		X																																																																																																					
Intended use and purpose of the equipment		X																																																																																																					
Proper method of use and limitations on use of the equipment		X																																																																																																					
Illustrations showing locations of markings on the equipment		X																																																																																																					
Reproduction of printed information on all markings		X																																																																																																					
Inspection procedures required to assure the equipment is in serviceable condition and operating correctly		X																																																																																																					
Anchorage requirements		X																																																																																																					
Criteria for discarding equipment which fails inspection		X																																																																																																					
Procedures for cleaning, maintenance, and storage		X																																																																																																					
Reference to Z359 standards		X																																																																																																					
Proper installation means and limitations on the type of anchorage connectors used		X																																																																																																					
The fiber or other materials used in the lanyard construction		X																																																																																																					
The lanyard length		X																																																																																																					
The average arresting force when dynamically tested in accordance with the requirements of the standard		X																																																																																																					
SRD class and arrest distance when dynamically tested in accordance with the requirements of the standard		X																																																																																																					
How to determine fall clearance		X																																																																																																					
Testing the device for locking before each use		X																																																																																																					
5.2.3	Instructions shall require that only the equipment manufacturer, or persons or entities authorized in writing by the manufacturer, shall make repairs to the equipment		<p><b>PASS</b></p>																																																																																																				
5.2.4	Instructions shall require the user to remove equipment from service if it has been subjected to the forces of arresting a fall or affecting a rescue		<p><b>PASS</b></p>																																																																																																				
5.2.5	Instructions shall require the user to have a written rescue plan and the means at hand to implement it when using the equipment		<p><b>PASS</b></p>																																																																																																				

Section (Test)	Requirement	Results	Compliance			
5.2.6	Instructions shall provide warnings regarding:		PASS			
	Warnings	Comments		YES	NO	NA
	Altering the equipment			X		
	Misusing the equipment			X		
	Using combinations of components or sub-systems, or both, which may affect or interfere with the safe function of each other			X		
	Exposing the equipment to chemicals, high heat, severe cold, or other harsh environments which may produce a harmful effect and to consult the manufacturer in case of doubt			X		
	Using the equipment around moving machinery and electrical hazards			X		
	Using the equipment near sharp edges or abrasive surfaces			X		
	Risk of striking an object or obstruction during a swing fall			X		
	That the consequences of improperly using the device, not following instructions or markings may cause serious injury or death			X		

**SUPPLEMENTAL TEST DATA**

Section (Test)	Requirement	Results	Compliance								
3.2.1/4.2 .1	<b>Static Strength:</b> (ambient) shall withstand 3,000 lbs. when tested to: - apply a 3,000 lbs ,(+60/-0 lbs) load and maintain for 1-minute to the point of SRL line connection to the SRL drum (across the device)	<table border="1"> <thead> <tr> <th></th> <th>Sample: 1</th> <th>Sample: 2</th> <th>Sample: 3</th> </tr> </thead> <tbody> <tr> <td>Withstand load</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> </tbody> </table>		Sample: 1	Sample: 2	Sample: 3	Withstand load	YES	YES	YES	PASS
	Sample: 1	Sample: 2	Sample: 3								
Withstand load	YES	YES	YES								



Section (Test)	Requirement	Results			Compliance																																												
3.3/4.3.1	<p><b>Dynamic Performance: "AMBIENT"</b></p> <ol style="list-style-type: none"> <li>1. connect 310 lb. weight</li> <li>2. extract enough line for a 36-inch free fall per Fig 5 in Test Standard.</li> <li>3. release the test weight</li> <li>4. Max Arrest distance shall not exceed 42 inches.</li> </ol> <table border="1" data-bbox="321 636 1346 1176"> <thead> <tr> <th></th> <th>Sample: 4</th> <th>Sample: 5</th> <th>Sample: 6</th> </tr> </thead> <tbody> <tr> <td>Conditioning in:</td> <td></td> <td></td> <td></td> </tr> <tr> <td>SN or ID:</td> <td>4</td> <td>5</td> <td>6</td> </tr> <tr> <td>Payout and retract the line per 3.3.1.2 following test</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> <tr> <td>Lock function shall operate per 3.3.1.1</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> <tr> <td>Visual indicator shall activate</td> <td>YES</td> <td>YES</td> <td>YES</td> </tr> <tr> <td>Max. Arrest Force: (lbs.) Class A &amp; B &lt; 1,800 lbs.</td> <td>965</td> <td>892</td> <td>919</td> </tr> <tr> <td>Avg Arrest Force (lbs.): Class A &lt;1,350 lbs. Class B &lt; 900 lbs.</td> <td>719</td> <td>652</td> <td>773</td> </tr> <tr> <td>Distance Initial (in): D1</td> <td>58"</td> <td>58"</td> <td>58"</td> </tr> <tr> <td>Distance Final (in): D2</td> <td>72"</td> <td>73 ¾"</td> <td>71 ½"</td> </tr> <tr> <td>Arrest Distance (in): D2-D1 &lt; 42 Inches</td> <td>14"</td> <td>15 ¾"</td> <td>13 ½"</td> </tr> </tbody> </table>		Sample: 4	Sample: 5	Sample: 6	Conditioning in:				SN or ID:	4	5	6	Payout and retract the line per 3.3.1.2 following test	YES	YES	YES	Lock function shall operate per 3.3.1.1	YES	YES	YES	Visual indicator shall activate	YES	YES	YES	Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	965	892	919	Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.	719	652	773	Distance Initial (in): D1	58"	58"	58"	Distance Final (in): D2	72"	73 ¾"	71 ½"	Arrest Distance (in): D2-D1 < 42 Inches	14"	15 ¾"	13 ½"				<b>PASS</b>
	Sample: 4	Sample: 5	Sample: 6																																														
Conditioning in:																																																	
SN or ID:	4	5	6																																														
Payout and retract the line per 3.3.1.2 following test	YES	YES	YES																																														
Lock function shall operate per 3.3.1.1	YES	YES	YES																																														
Visual indicator shall activate	YES	YES	YES																																														
Max. Arrest Force: (lbs.) Class A & B < 1,800 lbs.	965	892	919																																														
Avg Arrest Force (lbs.): Class A <1,350 lbs. Class B < 900 lbs.	719	652	773																																														
Distance Initial (in): D1	58"	58"	58"																																														
Distance Final (in): D2	72"	73 ¾"	71 ½"																																														
Arrest Distance (in): D2-D1 < 42 Inches	14"	15 ¾"	13 ½"																																														

**SECTION 5**  
**REVISION HISTORY**

REPORT NUMBER	DATE OF REVISION	DESCRIPTION OF CHANGE:	PROJECT OWNER	REVIEWED BY
104972747CRT-001	3/22/22	Original Report	Steve Morey	Matthew Stevens
105376372CRT-001	3/24/23	Report Extension	Alex Smith	Matthew Stevens
105663091CRT-001	12/8/2023	Report Revision: Added Model and Picture	Alex Smith	Matthew Stevens

**SECTION 6**  
**PHOTOGRAPH**

UFS310090



USF310025(SS)

